SAFETY DATA SHEETS

This SDS packet was issued with item: 076209522

N/A



Revision: 4

1. Substance / Preparation and Company Name

Product Name: Riva Luting Plus (powder)

Recommended use: Powder for the making of dental restorative cement by dental professionals.

SDI Inc.

Brasil

Telephone:

Telephone:

729 N.Route 83, Suite 315

Bensenville 60106 IL, USA

630 238 8300 (Business hours)

SDI Brasil Indústria e Comércio Ltda

Pinheiros, São Paulo, 05415-020

+55 11 3092 7100 (Business Hours)

Rua Dr. Virgílio de Carvalho Pinto, 612

Manufacturer / Supplier

SDI Limited 3-13 Brunsdon Street, Bayswater Victoria, 3153, Australia

Telephone:

+61 3 8727 7111 (Business hours)

Southern Dental Industries Ltd Block 8, St Johns Court Swords Road Santry, Dublin 9, Ireland

Telephone:

+353 1 886 9577 (Business Hours)

Emergency contact number: +61 3 8727 7111

2. Composition / Information on Ingredients

Composition:	<u>CAS No.</u>	<u>Wt %</u>
Fluoroaluminosilicate glass powder		95-100

3. Hazard Identification

Powder is an irritant. Avoid creating and inhaling dust.

Risk Phrases:	36 37 38	Irritating to eyes. Irritating to respiratory system. Irritating to skin.
Safety Phrases:	25 26	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	28	After contact with skin, wash immediately with water and soap.

4. First Aid Measures

Eye (contact): Wash thoroughly with water and seek medical attention.

Skin (contact): Remove using a cloth or sponge soaked in alcohol. Wash thoroughly with water.

Ingestion: Drink plenty of water/milk. Seek medical attention if symptoms persist.

Inhalation: (powder) Remove to fresh air. If breathing is difficult, seek medical attention.



Page 2 of 4

Revision: 4

5. Fire Fighting Measures

Suitable Extinguishing Media:	None required.
Unusual Fire and Explosion Hazards:	None.
Special Protective Equipment:	No special protective equipment required.

6. Accidental Release Measures

Personal Precautions:	Avoid contact with eyes, skin or clothing.
Environmental Precautions:	Clear up spillages. Transfer to a container for disposal.
Method for Cleaning Spills:	Wash the spillage area clean with water.

7. Handling and storage

Handling

Store sealed containers away from heat and light.

<u>Storage</u>

Storage by the end user (Dental Clinic) is recommended to be at temperatures between 4° - 20° C (39° - 68° F) and should be kept away from direct sunlight.

Distribution

During distribution, to our customers, this product can be transported in non-refrigerated conditions between 15° to 25° C. This product can also withstand temperatures up to 40° C for short periods (2 to 3 days) and intermittent peaks up to 50° C.

8. Exposure Controls / Personal Protection

Respiratory Protection:	Face mask.
Hand Protection:	Safety / rubber gloves.
Eye Protection:	Safety glasses, goggles or face shield.
General Safety and Hygiene Measures:	None

9. Physical and Chemical Properties

Appearance: Fine white pow	
Odour:	None
Boiling Point:	Not applicable
Melting Point:	>750°C
Specific Gravity:	2.8 g / cm ³
Flash Point:	Not applicable



Page 3 of 4

Revision: 4

9.	Physical	and	Chemical	Properties	(Cont'd)
					(001100)

Flammable:	Not applicable
Autoflammability:	Not applicable
Explosive Properties:	Not known
Oxidising Properties:	Not known
Vapour Pressure (@ 20°C):	None
Vapour Pressure (@ 20°C): Vapour Density:	None None
•	Hone

10. Stability and Reactivity

Stable under normal conditions.
None known
None known
None known
None known

11. Toxicological Information

Acute Toxicity:	Contact with skin and eyes may cause irritation.
Eye (contact):	May cause irritation due to foreign body reaction.
Skin (contact):	Possible skin irritant.
Inhalation:	Possible respiratory irritant.
Ingestion:	Irritant not likely in small amounts.

12. Ecological Information

Self-Assessment: Not readily biodegradable. Slightly hazardous for water.

13. Disposal Considerations

Dispose in accordance with local official regulations.

14. Transport Information

This product is not considered to be a dangerous good within the meaning of transportation regulations.



Page 4 of 4

Revision: 4

15. Regulatory Information

This product is regulated by:

TGA Medical Devices Directive 93/42/EEC FDA National regulations

16. Other Information

Preparation of MSDS:

Prepared by: SDI Limited 3-13 Brunsdon Street, Bayswater Victoria, 3153, Australia **Phone Number:** +61 3 8727 7111

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Department issuing MSDS:Research and DevelopmentContact:Operations Director



SDI Limited

Version No: 6.1.1.1 Safety Data Sheet according to WHS and ADG requirements

Issue Date: 18/03/2016 Print Date: 23/03/2016 Initial Date: Not Available L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Riva Luting Plus (powder)	
Synonyms	Not Available	
Other means of identification	Not Available	
Relevant identified uses of the substance or mixture and uses advised against		

Relevant identified uses Powder for the making of dental restorative cement by dental professionals.	
---	--

Details of the supplier of the safety data sheet

Registered company name	SDI Limited SDI Brazil Industria E Comercio Ltda SDI		SDI Germany GmbH	
Address	3-15 Brunsdon Street VIC Bayswater 3153 Australia	Rua Dr. Virgilio de Carvalho Pinto, 612 São Paulo CEP 05415-020 Brazil	Hansestrasse 85 Cologne D-51149 Germany	
Telephone	+61 3 8727 7111 (Business Hours)	+55 11 3092 7100	+49 0 2203 9255 0	
Fax	+61 3 8727 7222	+55 11 3092 7101	+49 0 2203 9255 200	
Website	www.sdi.com.au	om.au www.sdi.com.au www.sdi.com.au		
Email	info@sdi.com.au	brasil@sdi.com.au	germany@sdi.com.au	
Registered company name	SDI (North America) Inc.			
Address	1279 Hamilton Parkway IL Itasca 60143 United S	1279 Hamilton Parkway IL Itasca 60143 United States		
Telephone	+1 630 361 9200 (Business hours)	+1 630 361 9200 (Business hours)		
Fax	Not Available			
Website	Not Available			
Email	USA.Canada@sdi.com.au			

Emergency telephone number

Association / Organisation	SDI Limited	Not Available	Not Available
Emergency telephone numbers	+61 3 8727 7111	Not Available	Not Available
Other emergency telephone numbers	ray.cahill@sdi.com.au	Not Available	Not Available
Association / Organisation	Not Available		
Emergency telephone numbers	+61 3 8727 7111		
Other emergency telephone numbers	Not Available		

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification	Not Applicable
Label elements	
GHS label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	95-100	glass powder

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Seek medical attention.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Seek medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Foam is generally ineffective.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 		
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. May emit poisonous fumes.May emit corrosive fumes.Decomposes on heating and produces; carbon dioxide (CO2) 		

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator.
--------------	---

	 Use dry clean up procedures and avoid generating dust. Sweep up, shovel up or Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Place spilled material in clean, dry, sealable, labelled container.
Major Spills	 Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

	1
	Avoid all personal contact, including inhalation.
	Wear protective clothing when risk of exposure occurs.
	► Use in a well-ventilated area.
	 Prevent concentration in hollows and sumps.
	DO NOT enter confined spaces until atmosphere has been checked.
	DO NOT allow material to contact humans, exposed food or food utensils.
	Avoid contact with incompatible materials.
Safe handling	When handling, DO NOT eat, drink or smoke.
	 Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately. Launder contaminated clothing before re-use.
	Use good occupational work practice.
	 Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
	Store between 5 and 25 deg. C.
Other information	Do not store in direct sunlight.
	Store in a dry and well ventilated-area, away from heat and sunlight.
ditions for safe stora	e, including any incompatibilities
iunions for sale storag	ge, including any incompatibilities

Suitable container	DO NOT repack. Use containers supplied by manufacturer only. Check that containers are clearly labelled and free from leaks	
Storage incompatibility	None known	

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Riva Luting Plus (powder)	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
glass powder	Not Available		Not Available	

MATERIAL DATA

Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and
	"removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Appropriate engineering	Employers may need to use multiple types of controls to prevent employee overexposure.
controls	
	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
	If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
	(a): particle dust respirators, if necessary, combined with an absorption cartridge;
	(b): filter respirators with absorption cartridge or canister of the right type;
	(c): fresh-air hoods or masks.

A :=

mine the "conture valuation" of freeh sirevulating oir

Riva Luting Plus (powder)

minerate generated in the workplace persons yer ing "ecopera" valerities which in turn date

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	ir Speed: -2.5 m/s (200-500
into zone of rapid air motion) f/n	,
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high 2.5	/min.)
	5-10 m/s (500-2000 ′min.)
Within each range the appropriate value depends on:	
Lower end of the range Upper end of the range	
1: Room air currents minimal or favourable to capture 1: Disturbing room air currents	
2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity	
3: Intermittent, low production. 3: High production, heavy use	
4: Large hood or large air mass in motion 4: Small hood-local control only	
Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decrodingly, after distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f) crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits with apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Personal protection Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or Image: tessential that tessentis thessential theoretical air velocities are mu	after reference to f/min) for extraction of vithin the extraction or used.
Eye and face protection Eye an	ble equipment should be le. Lens should be removed
Skin protection See Hand protection below	
Hands/feet protection Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber Rubber Gloves 	
Body protection See Other protection below	
Other protection No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit.	
Thermal hazards Not Available	

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Fine white odourless powder, insoluble in water.		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available

pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.		
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.		
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dematitis (nonallergic). The dermatitis often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctivita (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	Limited evidence suggests that repeated or long-term oc	disease of the airways involving difficult breathing and related systemic problems. cupational exposure may produce cumulative health effects involving organs or biochemical systems. ise changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron is breathlessness. Lung shadows show on X-ray.	
Riva Luting Plus (powder)	TOXICITY Not Available	IRRITATION Not Available	
Legend:	Value obtained from Europe ECHA Registered Substa extracted from RTECS - Register of Toxic Effect of chen	nces - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data ical Substances	

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	\odot	Reproductivity	\otimes
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	\otimes	STOT - Repeated Exposure	0

Mutagenicity

Aspiration Hazard

Legend:

X – Data available but does not fill the criteria for classification

Data required to make classification available
 Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
Bioaccumulative potential		
Ingredient	Bioaccumulation	
	No Data available for all ingredients	
Mobility in soil		
Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods	
Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

•	
National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	Υ
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Y
New Zealand - NZIoC	Υ

Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC — TWA: Permissible Concentration-Time Weighted Average PC — STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia

Phone Number: +61 3 8727 7111

Date of preparation/revision: 23rd September 2015

Department issuing SDS: Research and Development

Contact: Technical Director