SAFETY DATA SHEETS

This SDS packet was issued with item:

071156587

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070413187 071156546 071156553 071156561 071156595 071156611 071156629

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

070413161 070413179



Safety Data Sheet acc. to OSHA HCS

Version 1

Reviewed on 04/10/2019

1 Identification

- · Product identifier
- · Trade name: PANAVIA SA Cement Universal
- · Article number: US231
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Resin-based dental adhesive cement
- · Details of the supplier of the safety data sheet
- · Manufacturer:

Kuraray Noritake Dental Inc. 1621 Sakazu, Kurashiki, Okayama 710-0801, Japan

- Contact information : Kuraray America, Inc.
 33 Maiden Lane, 6th Floor, New York, NY 10038 U.S.A.
 Tel: 800-879-1676
 Fax: 888-700-5200
 Website: www.kuraraydental.com
 Emergency telephone number:
- For chemical emergency spill, leak, fire, exposure or accident Call CHEMTREC day and night Within USA and Canada: 1-800-424-9300 CCN706984 or +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling: bisphenol A diglycidylmethacrylate triethylene glycol dimethacrylate sodium fluoride 2-hydroxyethyl methacrylate · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray P261 P264 Wash thoroughly after handling. P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/10/2019

Version 1

Reviewed on 04/10/2019

Trade name: PANAVIA SA Cement Universal

	(Contd. of page 1)
P305+P351+P3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

· Other hazards

 \cdot Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerou	s components:	
1565-94-2	bisphenol A diglycidylmethacrylate	1-10%
	🐼 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
109-16-0	triethylene glycol dimethacrylate	1-10%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
868-77-9	2-hydroxyethyl methacrylate	1-3%
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
7681-49-4	sodium fluoride	<1%
	🚸 Acute Tox. 3, H301; 🚸 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
· Other ing		
	arium glass filler	
	olloidal silica	
	oxide filler	
	ryloyloxydecyl dihydrogen phosphate	
• 1	ic aromatic dimethacrylate	
Silane coup dl-Campho		
Peroxide	rquinoite	
Accelerato	rs	
Catalysts		
Pigments		

4 First-aid measures

7 First-alu incasures
· Description of first aid measures
· General information:
Avoid contact with eyes.
Avoid contact with skin.
· After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· After skin contact:
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
· After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 3)
(



Safety Data Sheet acc. to OSHA HCS

Version 1

Reviewed on 04/10/2019

(Contd. of page 2)

Trade name: PANAVIA SA Cement Universal

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures See Section 8.

- \cdot Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Pick up mechanically.
- \cdot Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

\cdot Protective Action Criteria for Chemicals

· PAC-1:		
109-16-0	triethylene glycol dimethacrylate	33 mg/m ³
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
7681-49-4	sodium fluoride	17 mg/m ³
· PAC-2:		
109-16-0	triethylene glycol dimethacrylate	360 mg/m ³
868-77-9	2-hydroxyethyl methacrylate	21 mg/m ³
7681-49-4	sodium fluoride	90 mg/m ³
· PAC-3:		
109-16-0	triethylene glycol dimethacrylate	2,100 mg/m ³
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m ³
7681-49-4	sodium fluoride	1,100 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location (2-25°C).
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- Store away from reducing agents.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Version 1

Reviewed on 04/10/2019

(Contd. of page 3)

Trade name: PANAVIA SA Cement Universal

Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

• **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

7681-49-4 sodium fluoride

PEL Long-term value: 2.5 mg/m³ as F REL Long-term value: 2.5 mg/m³ as F

TLV Long-term value: 2.5 mg/m³ as F, BEI

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• **Breathing equipment:** Not required.

• Protection of hands:

Neoprene gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

· Information on basic phy	sical and chemical properties	
· General Information	- •	
· Appearance:		
Form:	Pasty	
Color:	Coloured	
· Odor:	Odorless	



Version 1

Reviewed on 04/10/2019

Trade name: PANAVIA SA Cement Universal

		(Contd. of page 4)
· Odor threshold:	Not determined	
· pH-value:	Not determined	
· Change in condition		
Melting point/Melting range:	Not determined	
Boiling point/Boiling range:	Not determined	
· Flash point:	Not determined	
· Flammability (solid, gaseous):	Not determined	
· Ignition temperature:	Not determined	
· Decomposition temperature:	Not determined	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined	
Upper:	Not determined	
· Oxidizing properties	Not determined	
· Vapor pressure:	Not determined	
· Density:	1.8-1.9g/cm ³	
· Relative density	Not determined	
· Vapor density	Not determined	
· Evaporation rate	Not determined	
\cdot Solubility in / Miscibility with		
Water:	Insoluble.	
· Partition coefficient (n-octanol/wat	ter): Not determined	
· Viscosity:	Not determined	
· Dynamic:	Not determined	
· Kinematic:	Not determined	
 Other information 	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- \cdot Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- \cdot LD/LC50 values that are relevant for classification:

868-77-9 2-hydroxyethyl methacrylate

Oral LD50 4,680 mg/kg (guinea pig)

3,275 mg/kg (mouse)

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/10/2019

Version 1

Reviewed on 04/10/2019

(Contd. of page 5)

3

Trade name: PANAVIA SA Cement Universal

5,050 mg/kg (rat)

- · Primary irritant effect:
- \cdot on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- \cdot Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:
- Irritant
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

7681-49-4 sodium fluoride

- \cdot NTP (National Toxicology Program)
- None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- \cdot Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, ADN, IMDG, IATA	Void	
UN proper shipping name		
DOT	Void	
ADR, ADN, IMDG, IATA	Void	



Version 1

Printing date 05/10/2019

Reviewed on 04/10/2019

Trade name: PANAVIA SA Cement Universal

		(Contd. of page 6
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Void	
· Packing group		
· DOT, ADR, IMDG, IATA	Void	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

· Sara

 \cdot Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- SARA 311/312: See Section 2 for the information on physical and health hazards.
- · Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

 \cdot Cancerogenity categories :

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

7681-49-4 sodium fluoride

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 2\\ \textbf{Fire} = 0\\ \textbf{Reactivity} = 0 \end{array}$

(Contd. on page 8)

A4



Version 1

Reviewed on 04/10/2019

Trade name: PANAVIA SA Cement Universal

· HMIS-ratings (scale 0 - 4)



· Abbreviations and acronyms:

Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 (Contd. of page 7)