

SAFETY DATA SHEETS

This SDS packet was issued with item:

073239456

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

073239449 073239464 073239472 073239480 073239498 073239506

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 1 of 4

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Luxatemp-Ultra

Company/undertaking identification

| | | | |
|---------------|--|----------|------------------------|
| Company name: | DMG Chemisch-Pharmazeutische Fabrik GmbH | | |
| Street: | Elbgaustraße 248 | | |
| Place: | D-22547 Hamburg | | |
| Telephone: | +49. (0) 40. 84006-0 | Telefax: | +49. (0) 40. 84006-222 |
| Internet: | www.dmg-dental.com | e-mail: | info@dmg-dental.com |

2. Hazards identification**Classification**

Indications of danger : Irritant
R-phrases:
Irritating to eyes, respiratory system and skin.

Explication of special hazards for human health and environment

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

chemical characterization (preparation): Acrylate.-resin.

4. First aid measures**After inhalation**

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

5. Fire-fighting measures**Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Extinguishing media which must not be used for safety reasons**

High power water jet.

6. Accidental release measures**Personal precautions**

Provide adequate ventilation.

Environmental precautions

Do not empty into drains or the aquatic environment.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 2 of 4

Methods for cleaning up/taking up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

7. Handling and storage**Handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

Storage**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

8. Exposure controls/personal protection**Exposure limit values****Exposure controls****Protective and hygiene measures**

When using do not eat or drink.

Respiratory protection

The following must be prevented: inhalation.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Eye protection

Tightly sealed safety glasses.

9. Physical and chemical properties**General information**

| | |
|-----------------|----------------|
| Physical state: | Paste |
| Colour: | characteristic |
| Odour: | ester |

Important health, safety and environmental information

| | Test method |
|--------------------------------------|-----------------------|
| pH-Value (at 20 °C): | ca. 7 |
| Changes in the physical state | |
| Boiling point: | >250 °C |
| point of decomposition: | 200 °C |
| Flash point: | >150 °C |
| Vapour pressure: (at 20 °C) | 1 hPa |
| Density: | 1,5 g/cm ³ |
| Water solubility: | 10 g/L |
| Vapour density: | 1 |

Other information

| | |
|-----------------------|---------|
| Ignition temperature: | >380 °C |
|-----------------------|---------|

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 3 of 4

10. Stability and reactivity**Conditions to avoid**

heat. Light.
Decomposition takes place from temperatures above: 200 °C
Decomposition under formation of: Acrylate.

Materials to avoid

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

11. Toxicological information**Acute toxicity**

LD50: Rat. 5000mg/kg

Corrosive and irritant effects

Frequently or prolonged contact with skin may cause dermal irritation.
Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

12. Ecological information**Ecotoxicity**

Acute fish toxicity LC50: >360 mg/l/48h

Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

13. Disposal considerations**Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.
Paste: Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

14. Transport information**Other applicable information**

Not a hazardous material with respect to these transportation regulations.

15. Regulatory information**Labelling**

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 4 of 4

Danger symbols: Xi - Irritant

Hazardous components which must be listed on the label

Methacrylic esters.

R phrases

36/37/38 Irritating to eyes, respiratory system and skin.

S phrases

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of Water and soap. .

National regulatory information**16. Other information****Full text of R-phrases referred to under sections 2 and 3**

36/37/38 Irritating to eyes, respiratory system and skin.

Emergency contact: Infotrac-(800)535-5053

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 1 of 4

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Luxatemp-Ultra

Company/undertaking identification

| | | | |
|---------------|--|----------|------------------------|
| Company name: | DMG Chemisch-Pharmazeutische Fabrik GmbH | | |
| Street: | Elbgaustraße 248 | | |
| Place: | D-22547 Hamburg | | |
| Telephone: | +49. (0) 40. 84006-0 | Telefax: | +49. (0) 40. 84006-222 |
| Internet: | www.dmg-dental.com | e-mail: | info@dmg-dental.com |

2. Hazards identification**Classification**

Indications of danger : Irritant
R-phrases:
Irritating to eyes, respiratory system and skin.

Explication of special hazards for human health and environment

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

chemical characterization (preparation): Acrylate.-resin.

4. First aid measures**After inhalation**

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

5. Fire-fighting measures**Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Extinguishing media which must not be used for safety reasons**

High power water jet.

6. Accidental release measures**Personal precautions**

Provide adequate ventilation.

Environmental precautions

Do not empty into drains or the aquatic environment.

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 2 of 4

Methods for cleaning up/taking up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

7. Handling and storage**Handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

Storage**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

8. Exposure controls/personal protection**Exposure limit values****Exposure controls****Protective and hygiene measures**

When using do not eat or drink.

Respiratory protection

The following must be prevented: inhalation.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Eye protection

Tightly sealed safety glasses.

9. Physical and chemical properties**General information**

| | |
|-----------------|----------------|
| Physical state: | Paste |
| Colour: | characteristic |
| Odour: | ester |

Important health, safety and environmental information

| | Test method |
|--------------------------------------|-------------|
| pH-Value (at 20 °C): | ca. 7 |
| Changes in the physical state | |
| Boiling point: | >250 °C |
| point of decomposition: | 200 °C |
| Flash point: | >150 °C |
| Vapour pressure: | 1 hPa |
| (at 20 °C) | |
| Density: | 1,5 g/cm³ |
| Water solubility: | 10 g/L |
| Vapour density: | 1 |

Other information

| | |
|-----------------------|---------|
| Ignition temperature: | >380 °C |
|-----------------------|---------|

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 3 of 4

10. Stability and reactivity**Conditions to avoid**

heat. Light.
Decomposition takes place from temperatures above: 200 °C
Decomposition under formation of: Acrylate.

Materials to avoid

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

11. Toxicological information**Acute toxicity**

LD50: Rat. 5000mg/kg

Corrosive and irritant effects

Frequently or prolonged contact with skin may cause dermal irritation.
Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

12. Ecological information**Ecotoxicity**

Acute fish toxicity LC50: >360 mg/l/48h

Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

13. Disposal considerations**Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.
Paste: Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

14. Transport information**Other applicable information**

Not a hazardous material with respect to these transportation regulations.

15. Regulatory information**Labelling**

Safety Data Sheet

according to Regulation (EU) No. 1907/2006

Luxatemp-Ultra

Print date: 17.06.2010

MSDS: 1300

Page 4 of 4

Danger symbols: Xi - Irritant

Hazardous components which must be listed on the label

Methacrylic esters.

R phrases

36/37/38 Irritating to eyes, respiratory system and skin.

S phrases

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of Water and soap. .

National regulatory information**16. Other information****Full text of R-phrases referred to under sections 2 and 3**

36/37/38 Irritating to eyes, respiratory system and skin.

Emergency contact: Infotrac-(800)535-5053

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)