

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

073239498

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

073239449 073239456 073239464 073239472 073239480 073239506

**Safety Data Sheet**

according to Regulation (EU) No. 1907/2006

**Luxatemp-Ultra**

Print date: 17.06.2010

MSDS: 1300

Page 1 of 4

**1. Identification of the substance/preparation and of the company/undertaking****Identification of the substance or preparation**

Luxatemp-Ultra

**Company/undertaking identification**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH		
Street:	Elbgaustraße 248		
Place:	D-22547 Hamburg		
Telephone:	+49. (0) 40. 84006-0	Telefax:	+49. (0) 40. 84006-222
Internet:	www.dmg-dental.com	e-mail:	info@dmg-dental.com

**2. Hazards identification****Classification**

Indications of danger : Irritant  
R-phrases:  
Irritating to eyes, respiratory system and skin.

**Explication of special hazards for human health and environment**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**3. Composition/information on ingredients****Chemical characterization ( Mixture )**

chemical characterization (preparation): Acrylate.-resin.

**4. First aid measures****After inhalation**

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

**After contact with skin**

After contact with skin, wash immediately with: Water and soap.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**After ingestion**

Consult physician.

**5. Fire-fighting measures****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).**Extinguishing media which must not be used for safety reasons**

High power water jet.

**6. Accidental release measures****Personal precautions**

Provide adequate ventilation.

**Environmental precautions**

Do not empty into drains or the aquatic environment.

**Safety Data Sheet**

according to Regulation (EU) No. 1907/2006

**Luxatemp-Ultra**

Print date: 17.06.2010

MSDS: 1300

Page 2 of 4

**Methods for cleaning up/taking up**

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

**7. Handling and storage****Handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

**Storage****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.  
Store only in original container.

**8. Exposure controls/personal protection****Exposure limit values****Exposure controls****Protective and hygiene measures**

When using do not eat or drink.

**Respiratory protection**

The following must be prevented: inhalation.

**Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

**Eye protection**

Tightly sealed safety glasses.

**9. Physical and chemical properties****General information**

Physical state:	Paste
Colour:	characteristic
Odour:	ester

**Important health, safety and environmental information**

	Test method
pH-Value (at 20 °C):	ca. 7
<b>Changes in the physical state</b>	
Boiling point:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Vapour pressure:	1 hPa
(at 20 °C)	
Density:	1,5 g/cm <sup>3</sup>
Water solubility:	10 g/L
Vapour density:	1

**Other information**

Ignition temperature:	>380 °C
-----------------------	---------

**Safety Data Sheet**

according to Regulation (EU) No. 1907/2006

**Luxatemp-Ultra**

Print date: 17.06.2010

MSDS: 1300

Page 3 of 4

**10. Stability and reactivity****Conditions to avoid**

heat. Light.  
Decomposition takes place from temperatures above: 200 °C  
Decomposition under formation of: Acrylate.

**Materials to avoid**

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

**Hazardous decomposition products**

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

**11. Toxicological information****Acute toxicity**

LD50: Rat. 5000mg/kg

**Corrosive and irritant effects**

Frequently or prolonged contact with skin may cause dermal irritation.  
Irritant effect on the eye:

**Additional information on tests**

Contains Methacrylic esters.: May produce an allergic reaction.

**12. Ecological information****Ecotoxicity**

Acute fish toxicity LC50: >360 mg/l/48h

**Persistence and degradability**

Preparation not tested.

**Further information**

Do not empty into drains or the aquatic environment.

**13. Disposal considerations****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.  
Paste: Carry out a burning of hazardous waste according to official regulations.

**Waste disposal number of waste from residues/unused products**

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

**14. Transport information****Other applicable information**

Not a hazardous material with respect to these transportation regulations.

**15. Regulatory information****Labelling**

**Safety Data Sheet**

according to Regulation (EU) No. 1907/2006

**Luxatemp-Ultra**

Print date: 17.06.2010

MSDS: 1300

Page 4 of 4

Danger symbols: Xi - Irritant

**Hazardous components which must be listed on the label**

Methacrylic esters.

**R phrases**

36/37/38 Irritating to eyes, respiratory system and skin.

**S phrases**

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of Water and soap. .

**National regulatory information****16. Other information****Full text of R-phrases referred to under sections 2 and 3**

36/37/38 Irritating to eyes, respiratory system and skin.

**Emergency contact: Infotrac-(800)535-5053**

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 1 of 5

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Luxatemp Ultra

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company Name: DMG AMERICA LLC  
Address: 242 South Dean Street  
City, State, Zip Code: Englewood, NJ. 07631  
Telephone: (800) 662-6383  
email address: [Info@dmg-america.com](mailto:Info@dmg-america.com)  
Website: [www.dmg-america.com](http://www.dmg-america.com)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant  
R phrases:  
Irritating to eyes, respiratory system and skin.  
May cause sensitisation by skin contact.

#### GHS classification

Hazard Statements:  
May cause respiratory irritation.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.

#### 2.2. Label elements

Signal word: Warning  
Pictograms: GHS07



#### Hazard statements

H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

#### Precautionary statements

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

#### 2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 2 of 5

### Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Dimethacrylate Resin	
41637-38-1	Xi - Irritant R36/37/38-43	35-45 %

Full text of R and H phrases: see Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

#### Extinguishing media which must not be used for safety reasons

High power water jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 3 of 5

Store only in original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls



#### Protective and hygiene measures

When using do not eat or drink.

#### Respiratory protection

The following must be prevented: inhalation.

#### Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

#### Eye protection

Tightly sealed safety glasses.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	characteristic
Odour:	ester

#### Test method

pH-Value (at 20 °C):	ca. 7
----------------------	-------

#### Changes in the physical state

Boiling point:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm <sup>3</sup>
Water solubility:	10 g/L
Vapour density:	1

### SECTION 10: Stability and reactivity

#### 10.4. Conditions to avoid

heat. Light.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

#### 10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).



# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 4 of 5

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

LD50: Rat. 5000 mg/kg

##### Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

##### Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

#### 12.2. Persistence and degradability

Preparation not tested.

#### Further information

Do not empty into drains or the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

##### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

### SECTION 14: Transport information

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

#### Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 5 of 5

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.*