

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

073261013

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

073260072

MS130304

**EXAFLEX & EXAFST PUTTY**  
**MATERIAL SAFETY DATA SHEET**

Page 1 of 2

**SECTION 1 - SOURCE/IDENTITY/USE INFORMATION****MANUFACTURER**

GC AMERICA INC.

3737 West 127th St.

Alsip, Illinois, 60803

Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

**COMMON NAME:** EXAFLEX PUTTY BASE AND CATALYST**EXAFST PUTTY BASE AND CATALYST****CHEMICAL NAME:** N.A.**PRODUCT USE:** Dental Impressions

*The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed two paste system.*

**SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

COMPONENT	C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polydimethyl Siloxane	(not listed)	N.E.	LD50 = 5mg/m <sup>3</sup> (oral rat)	11
Vinyl Dimethyl Polydimethyl Siloxane	68083-19-2	N.E.	N.E.	11
Silica-Amorphous	112926-00-8	PEL=10.0mg/m <sup>3</sup> TLV/TWA=10.0mg/m <sup>3</sup> (as dust) (ACGIH)	N.E.	78

**SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES****BOILING POINT:** 160°C**VAPOR PRESSURE:** 100/50°C**VAPOR DENSITY:** 2.56**SOLUBILITY IN WATER:** Insoluble**COEFFICIENT OF OIL/WATER DISTRIBUTION:** N.E.**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.67**MELTING POINT:** N.E.**EVAPORATION RATE:** N.E.**ODOR THRESHOLD:** N.A.**APPEARANCE AND ODOR:** A yellow or blue paste. Both are odorless.**SECTION 4 - FIRE AND EXPLOSION DATA****FLASH POINT:** Not Flammable per ASTM D92**FLAMMABLE LIMITS:** N.A.**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, alcohol foam**SPECIAL FIRE FIGHTING PROCEDURES:** Water is not effective medium. Firefighters should wear self-contained breathing apparatus and full protective clothing.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Irritating and/or toxic aerosols or gases may be present.**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Dioxide, Carbon Monoxide, Sulfur dioxide, Hydrogen Sulfide**SECTION 5 - REACTIVITY DATA****STABILITY:** Stable ☒Unstable ☐**POLYMERIZATION:** Will Not Occur ☒Will Occur ☐**CONDITIONS TO AVOID:** High temperatures (> 121°C); open flames**INCOMPATIBILITY (Materials to Avoid):** Strong acids, bases, oxidizers.**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** N.E.

**SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION**

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS		X						
TERATOGENIC AFFECTS		X						
REPRODUCTIVE TOXIN		X						
CARCINOGENICITY	X (as Silica dust)					X		
SENSITIZER		X						

ROUTES OF ENTRY: Inhalation ☒ Skin ☒ Ingestion ☒

**HEALTH HAZARD (Acute and Chronic):** Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE:** Headaches

**CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** N.E.

**EMERGENCY FIRST AID PROCEDURES:**

**INHALATION:** Remove to fresh air if irritation develops.

**EYES:** Flush with large volumes of water, consult a physician if irritation develops.

**SKIN:** Wash thoroughly with soap and water

**INGESTION:** Do not induce vomiting. Dilute by drinking several glasses of water. Seek medical attention.

**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE**

**IN CASE OF RELEASE OR SPILL:** Absorb with inert material; transfer to container for disposal

**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and Federal Regulations

**STORAGE, HANDLING, AND SPECIAL PRECAUTIONS:** Store at normal room temperature in a well ventilated area

**SECTION 8 - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** N.A.

**VENTILATION:** Local Exhaust: Recommended      Mechanical: N.E.      Special: N.E.      Other: N.E.

**PROTECTIVE GLOVES:** Synthetic/Vinyl Gloves

**EYE PROTECTION:** Safety glasses or goggles

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** N.E.

**WORK/HYGIENIC PRACTICE:** N.E.

**SECTION 9 - PREPARATION INFORMATION**

*This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200 and W.H.M.I.S. CPR*

**DATE:** 09 January 2006

**REVIEWED:** 21 February 2012

N.A. = NOT APPLICABLE

N.E. = NOT ESTABLISHED

*The information herein is given in good faith but no warranty expressed or implied is made.*

FIRE - 0

TOXICITY - 1

NFPA  
REACTIVITY - 1

SPECIAL -

MS130304

**EXAFLEX & EXAFST PUTTY**  
**MATERIAL SAFETY DATA SHEET**

Page 1 of 2

**SECTION 1 - SOURCE/IDENTITY/USE INFORMATION****MANUFACTURER**

GC AMERICA INC.

3737 West 127th St.

Alsip, Illinois, 60803

Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

**COMMON NAME:** EXAFLEX PUTTY BASE AND CATALYST**EXAFST PUTTY BASE AND CATALYST****CHEMICAL NAME:** N.A.**PRODUCT USE:** Dental Impressions

*The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed two paste system.*

**SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

COMPONENT	C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polydimethyl Siloxane	(not listed)	N.E.	LD50 = 5mg/m <sup>3</sup> (oral rat)	11
Vinyl Dimethyl Polydimethyl Siloxane	68083-19-2	N.E.	N.E.	11
Silica-Amorphous	112926-00-8	PEL=10.0mg/m <sup>3</sup> TLV/TWA=10.0mg/m <sup>3</sup> (as dust) (ACGIH)	N.E.	78

**SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES****BOILING POINT:** 160°C**VAPOR PRESSURE:** 100/50°C**VAPOR DENSITY:** 2.56**SOLUBILITY IN WATER:** Insoluble**COEFFICIENT OF OIL/WATER DISTRIBUTION:** N.E.**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.67**MELTING POINT:** N.E.**EVAPORATION RATE:** N.E.**ODOR THRESHOLD:** N.A.**APPEARANCE AND ODOR:** A yellow or blue paste. Both are odorless.**SECTION 4 - FIRE AND EXPLOSION DATA****FLASH POINT:** Not Flammable per ASTM D92**FLAMMABLE LIMITS:** N.A.**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, alcohol foam**SPECIAL FIRE FIGHTING PROCEDURES:** Water is not effective medium. Firefighters should wear self-contained breathing apparatus and full protective clothing.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Irritating and/or toxic aerosols or gases may be present.**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Dioxide, Carbon Monoxide, Sulfur dioxide, Hydrogen Sulfide**SECTION 5 - REACTIVITY DATA****STABILITY:** Stable ☒Unstable ☐**POLYMERIZATION:** Will Not Occur ☒Will Occur ☐**CONDITIONS TO AVOID:** High temperatures (> 121°C); open flames**INCOMPATIBILITY (Materials to Avoid):** Strong acids, bases, oxidizers.**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** N.E.

**SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION**

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS		X						
TERATOGENIC AFFECTS		X						
REPRODUCTIVE TOXIN		X						
CARCINOGENICITY	X (as Silica dust)					X		
SENSITIZER		X						

ROUTES OF ENTRY: Inhalation ☒ Skin ☒ Ingestion ☒

**HEALTH HAZARD (Acute and Chronic):** Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE:** Headaches

**CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** N.E.

**EMERGENCY FIRST AID PROCEDURES:**

**INHALATION:** Remove to fresh air if irritation develops.

**EYES:** Flush with large volumes of water, consult a physician if irritation develops.

**SKIN:** Wash thoroughly with soap and water

**INGESTION:** Do not induce vomiting. Dilute by drinking several glasses of water. Seek medical attention.

**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE**

**IN CASE OF RELEASE OR SPILL:** Absorb with inert material; transfer to container for disposal

**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and Federal Regulations

**STORAGE, HANDLING, AND SPECIAL PRECAUTIONS:** Store at normal room temperature in a well ventilated area

**SECTION 8 - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** N.A.

**VENTILATION:** Local Exhaust: Recommended      Mechanical: N.E.      Special: N.E.      Other: N.E.

**PROTECTIVE GLOVES:** Synthetic/Vinyl Gloves

**EYE PROTECTION:** Safety glasses or goggles

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** N.E.

**WORK/HYGIENIC PRACTICE:** N.E.

**SECTION 9 - PREPARATION INFORMATION**

*This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200 and W.H.M.I.S. CPR*

**DATE:** 09 January 2006

**REVIEWED:** 21 February 2012

N.A. = NOT APPLICABLE

N.E. = NOT ESTABLISHED

*The information herein is given in good faith but no warranty expressed or implied is made.*

FIRE - 0

TOXICITY - 1

NFPA  
REACTIVITY - 1

SPECIAL -



## Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015


Version US-EN-Rev 1

Reviewed on 02/24/2015

### 1 Identification

- **Product identifier**
- **Trade name:** EXAFAST PUTTY (Base)
- **Relevant identified uses of the substance or mixture and uses advised against**  
Dental material  
The product is intended for professional use.  
To avoid risks for humans and environment obtain instructions.
- **Application of the substance / the mixture** Dental impression material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GC America Inc.  
3737 W. 127th Street  
Alsip, IL 60803  
USA  
  
sds@gcamerica.com
- **Information department:** Regulatory Affairs
- **Emergency telephone number:**  
During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900  
Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Acute Tox. 4 H332 Harmful if inhaled.  
STOT SE 3 H335 May cause respiratory irritation.  
Eye Irrit. 2B H320 Causes eye irritation.
- **Additional information:**  
The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**  
  
GHS07
- **Signal word** Warning
- **Hazard statements**  
Harmful if inhaled.  
Causes eye irritation.  
May cause respiratory irritation.

(Contd. on page 2)

-USA-

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 1)

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

6 % of the mixture consists of component(s) of unknown toxicity.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 0

Reactivity = 1

- **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 0

Reactivity = 1

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

112926-00-8	silicon dioxide, amorphous	60-80%
-------------	----------------------------	--------

- **Additional information:**

If a substance is marked with \*\*, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

- **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

Do not use mouth to mouth or mouth to nose resuscitation.

- **After skin contact:**

Rinse with warm water.

(Contd. on page 3)

-USA-

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 2)

- If symptoms persist consult doctor.
- **After eye contact:**  
Protect unharmed eye.  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Remove persons from danger area.  
Avoid formation of dust.  
Avoid contact with the eyes and skin.  
Wear protective clothing.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**  
Pick up mechanically.  
Prevent formation of dust.  
Dispose of the collected material according to regulations.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

— USA —

(Contd. on page 4)



# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 3)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
  - Observe instructions for use.
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of dust.
  - Do not inhale dust / smoke / mist.
  - Any deposit of dust which cannot be avoided must be regularly removed.
  - Avoid contact with the eyes and skin.
- **Information about protection against explosions and fires:**
  - Dust can combine with air to form an explosive mixture.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Observe instructions for use / storage.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

#### Components with limit values that require monitoring at the workplace:

##### 112926-00-8 silicon dioxide, amorphous

PEL	Long-term value: 2 mg/m <sup>3</sup> 20mppcf or 80mg/m <sup>3</sup> /%SiO <sub>2</sub> ; 1mppcf = 0.1 mg/m <sup>3</sup>
REL	Long-term value: 6 mg/m <sup>3</sup> See Pocket Guide App. C
TLV	TLV Withdrawn

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - The usual precautionary measures for handling chemicals should be followed.
  - Do not inhale dust / smoke / mist.
  - Avoid contact with the eyes and skin.
  - Wash hands before breaks and at the end of work.
  - Immediately remove all soiled and contaminated clothing.
- **Breathing equipment:** Suitable respiratory protective device recommended.
- **Protection of hands:** Protective gloves
- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

USA

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 4)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Pasty

Color: Yellow

- **Odor:** Odorless

- **Odor threshold:** Not determined.

- **pH-value:** Not applicable.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 160 °C (320 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not determined.

- **Ignition temperature:** Undetermined.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure:** Not applicable.

- **Density at 20 °C (68 °F):** 1.67 g/cm<sup>3</sup> (13.936 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not applicable.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

Water: Insoluble.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not applicable.

Kinematic: Not applicable.

- **Solvent content:**

Organic solvents: 0.0 %

Solids content: 100.0 %

(Contd. on page 6)

USA

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFAST PUTTY (Base)

(Contd. of page 5)

· **Other information**

No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable at ambient temperature.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** No further relevant information available.
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

silicon dioxide, amorphous	3
antimony nickel titanium oxide yellow	3
- **NTP (National Toxicology Program)**

None of the ingredients is listed.
------------------------------------
- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.
------------------------------------
- **Carcinogenic categories' legend:**  
IARC Group 1: The agent is carcinogenic to humans.  
IARC Group 2A: The agent is probably carcinogenic to humans.  
IARC Group 2B: The agent is possibly carcinogenic to humans.  
IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.  
IARC Group 4: The agent is probably not carcinogenic to humans.  
NTP K: Known to be human carcinogen.  
NTP R: Reasonably anticipated to be human carcinogen.

USA

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

Trade name: EXAFAST PUTTY (Base)

(Contd. of page 6)

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |                 |
|--|-----------------|
| · <b>UN-Number</b>   |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   | Void            |
| · <b>UN proper shipping name</b>   |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   | Void            |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   |                 |
| · <b>Class</b>   | Void            |
| · <b>Packing group</b>   |                 |
| · <b>DOT, ADR, IMDG, IATA</b>  | Void            |
| · <b>Environmental hazards:</b>  |                 |
| · <b>Marine pollutant:</b>   | No              |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |

(Contd. on page 8)

USA

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 7)

· **UN "Model Regulation":**

-

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **SARA (Superfund Amendments and Reauthorization Act)**

- **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

vinyl dimethylpolysiloxane

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

antimony nickel titanium oxide yellow

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard statements**

Harmful if inhaled.

Causes eye irritation.

May cause respiratory irritation.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

- **Department issuing MSDS:** Regulatory Affairs

(Contd. on page 9)

-USA-

# Safety Data Sheet

## acc. to OSHA HCS 29 CFR 1910.1200

Printing date 02/24/2015

Version US-EN-Rev 1

Reviewed on 02/24/2015

**Trade name:** EXAFAST PUTTY (Base)

(Contd. of page 8)

**· Contact:**

Regulatory Affairs  
Telephone No. +1 (708) 597-0900  
sds@gcamerica.com

**· Date of preparation / last revision 02/24/2015 / -**
**· Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
HCS: Hazard Communication Standard (USA)  
MSDS: Material Safety Data Sheet  
SDS: Safety Data Sheet  
ADN: Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways)  
ECHA: European Chemicals Agency  
OSHA: Occupational Safety and Health Administration (USA)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

**· Sources**

- Manufacturers' MSDSs/SDSs
- OSHA (<https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html>)
- TOXNET (<http://toxnet.nlm.nih.gov/>)
- ECHA (<http://echa.europa.eu/>)
- EnviChem ([www.echemportal.org](http://www.echemportal.org))

**· Notes:**

CAS Registry Number is a Registered Trademark of the American Chemical Society.  
CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

- **\* Data compared to the previous version altered.** This version replaces all previous versions.

**· Disclaimer:**

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

USA