SAFETY DATA SHEETS

This SDS packet was issued with item:

073262110

N/A



Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

1 Identification

- · Product identifier
- · Trade name: EXAFLEX PUTTY (Base)
- · Application of the substance / the mixture Dental impression material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

- · Information department: Regulatory Affairs
- · Emergency telephone number:

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard identification

· Classification of the substance or mixture

Eye Irritation - Category 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - H335 May cause respiratory irritation.

Category 3

· Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Causes serious eye irritation. May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 0 Reactivity = 1

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 0 Reactivity = 1

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 112926-00-8	silicon dioxide, amorphous	60 - 100% w/w
	polyethylene glycol derivative**	3 - 7% w/w

· Additional information:

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

After inhalation:

Supply fresh air: consult doctor in case of complaints.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Rinse with warm water.

If symptoms persist consult doctor.

After eye contact:

Protect unharmed eve.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 2)

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid formation of dust.

Avoid contact with the eyes and skin.

Wear protective clothing.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Prevent formation of dust.

Dispose of the collected material according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Observe instructions for use.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

(Contd. on page 4)

according to HPR, Schedule 1 Sheet Safety Data

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

(Contd. of page 3)

(Base) Trade name: EXAFLEX PUTTY

Any deposit of dust which cannot be avoided must be regularly removed.

Avoid contact with the eyes and skin. Information about protection against explosions and fires:

Dust can combine with air to form an explosive mixture.

Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Observe instructions for use / storage.

Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see item
- · Control parameters
- Components with limit values that require monitoring at the workplace:

CAS: 112926-00-8 silicon dioxide, amorphous

EL Long-term value: 4* 1.5** mg/m³
Precipitated and gel;*total;**respirable

EV Long-term value: 10 mg/m3

- Additional information: The lists that were valid during the creation were used as basis.
- **Exposure controls**
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

Breathing equipment:



Suitable respiratory protective device recommended.

Protection of hands:



Protective gloves

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

· Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

9 Physical and chemical prope	erties
 Information on basic physical and General Information Appearance: 	chemical properties
Form:	Pasty
Color:	Yellow
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 160 °C
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	Undetermined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not applicable.
 Density at 20 °C: Relative density Vapor density Evaporation rate 	1.67 g/cm ³ Not determined. Not applicable. Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
· Solvent content:	
Solids content:	100.0 %

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable at ambient temperature.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: No further relevant information available.
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

İrritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
silicon dioxide, amorphous	3
antimony nickel titanium oxide yellow	3

NTP (National Toxicology Program)

None of the ingredients is listed.

· Carcinogenic categories' legend:

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

- · Repeated dose toxicity. No further relevant information available.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

No further relevant information available.

CA -

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of contents / container in accordance with local / regional / national / international regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· ON-Number · DOT, TDG, ADN, IMDG, IATA	Void	
	v Old	
· UN proper shipping name · DOT, TDG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, TDG, ADN, IMDG, IATA		
· Class	Void	
Packing group		
DOT, TĎĞ, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	

(Contd. on page 8)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 7)

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

antimony nickel titanium oxide yellow

· TSCA (Toxic Substances Control Act):

vinyl dimethylpolysiloxane

polyethylene glycol derivative**

antimony nickel titanium oxide yellow

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

vinyl dimethylpolysiloxane

polyethylene glycol derivative**

antimony nickel titanium oxide yellow

methylhydrogen dimethylpolysiloxane

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- Signal word Warning
- · Hazard statements

Causes serious eye irritation.

May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

Version CA-EN-Rev 1 Printing date 03/13/2018 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Base)

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Department issuing SDS: Regulatory Affairs

· Contact:

Regulatory Affairs

Telephone No. +1 (708) 597-0900

sds@gcamerica.com

Date of preparation / last revision 03/13/2018 / -

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

ADN: Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways)

ECHA: European Chemicals Agency

OSHA: Occupational Safety and Health Administration (USA)

LEL: Lower Explosive Limit

UEL: Upper Explosive Limit

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Sources

- Manufacturers' MSDSs/SDSs
- OSHA (https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html)
- TOXNET (http://toxnet.nlm.nih.gov/)
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

· Notes:

CAS Registry Number is a Registered Trademark of the American Chemical Society. CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

* Data compared to the previous version altered. This version replaces all previous versions.

· Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.



Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

1 Identification

- · Product identifier
- Trade name: EXAFLEX PUTTY (Catalyst)
- · Application of the substance / the mixture Dental impression material
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

- · Information department: Regulatory Affairs
- · Emergency telephone number:

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard identification

· Classification of the substance or mixture

Eye Irritation - Category 2B H320 Causes eye irritation.

· Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Causes eye irritation.

· Precautionary statements

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 0 Reactivity = 1

(Contd. on page 2)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)



Health = 1 Fire = 0 Reactivity = 1

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous compo	onents:	
CAS: 112926-00-8	silicon dioxide, amorphous	60 - 100% w/w
	catalyst**	3 - 7% w/w

· Additional information:

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Rinse with warm water.

If symptoms persist consult doctor.

After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

CA-

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid formation of dust.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Prevent formation of dust.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Observe instructions for use.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

Any deposit of dust which cannot be avoided must be regularly removed.

Avoid contact with the eyes and skin.

· Information about protection against explosions and fires:

Dust can combine with air to form an explosive mixture.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

(Contd. on page 4)

according to HPR, Schedule 1 Safety Data Sheet

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 3) Information about storage in one common storage facility: Store away from foodstuffs.
 Further information about storage conditions:
 Observe instructions for use / storage.

Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see item
- Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 112926-00-8 silicon dioxide, amorphous

Long-term value: 4* 1.5** mg/m³ Precipitated and gel;*total;**respirable

Long-term value: 10 mg/m³ <u>></u>

catalyst**

EL |Long-term value: 1* 0.002** mg/m3 *metal;**soluble salts (as Pt): S Long-term value: 1* 0.002** mg/m3 Ε

*metal; ** water-soluble compounds (as Pt)

- Additional information: The lists that were valid during the creation were used as basis.
- **Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Breathing equipment:



Suitable respiratory protective device recommended.

Protection of hands:



Protective gloves

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Version CA-EN-Rev 1 Printing date 03/13/2018 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

· Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

9 Physical and chemical prope	erties
· Information on basic physical and	chemical properties
· General Information	• •
· Appearance:	
Form:	Pasty
Color:	Blue
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	160 ℃
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	Undetermined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C:	1.67 g/cm ³
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Solids content:	100.0 %
	(Contd. on page

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable at ambient temperature.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: No further relevant information available.
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

İrritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
silicon dioxide, amorphous	3
cobalt aluminate blue spinel	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· Carcinogenic categories' legend:

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

- · Repeated dose toxicity. No further relevant information available.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

No further relevant information available.

CA -

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of contents / container in accordance with local / regional / national / international regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· ON-Number · DOT, TDG, ADN, IMDG, IATA	Void	
	v Old	
· UN proper shipping name · DOT, TDG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, TDG, ADN, IMDG, IATA		
· Class	Void	
Packing group		
DOT, TĎĞ, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	

(Contd. on page 8)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 7)

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

vinyl dimethylpolysiloxane

catalyst**

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

vinyl dimethylpolysiloxane

catalyst**

iron oxide

cobalt aluminate blue spinel

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

catalyst**

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- · Hazard statements

Causes eve irritation.

· Precautionary statements

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

- Department issuing SDS: Regulatory Affairs
- · Contact:

Regulatory Affairs

Telephone No. +1 (708) 597-0900

sds@gcamerica.com

· Date of preparation / last revision 03/13/2018 / -

(Contd. on page 9)

Printing date 03/13/2018 Version CA-EN-Rev 1 Reviewed on 01/09/2018

Trade name: EXAFLEX PUTTY (Catalyst)

(Contd. of page 8)

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

ADN: Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways)

ECHA: European Chemicals Agency

OSHA: Occupational Safety and Health Administration (USA)

LEL: Lower Explosive Limit
UEL: Upper Explosive Limit

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation
IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Sources

- Manufacturers' MSDSs/SDSs
- OSHA (https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html)
- TOXNET (http://toxnet.nlm.nih.gov/)
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

· Notes:

CAS Registry Number is a Registered Trademark of the American Chemical Society. CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

· * Data compared to the previous version altered. This version replaces all previous versions.

· Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.