## **SAFETY DATA SHEETS**

## This SDS packet was issued with item: 073777760

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071225267

# **COLTENE**

## Endo-Ice® Refrigerant Spray Coltène/Whaledent GmbH & Co. KG

Version No: 1.1

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 21/04/2022 Print Date: 25/01/2023 L.GHS.CAN.EN

#### **SECTION 1 Identification**

#### **Product Identifier**

Product name	Endo-Ice® Refrigerant Spray
Chemical Name	1,1,1,2-tetrafluoroethane
Synonyms	Endo Ice
Proper shipping name	REFRIGERANT GAS R 134a; or 1,1,1,2-TETRAFLUOROETHANE
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

Relevant identified uses	For dental use only

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Coltène/Whaledent GmbH & Co. KG	Coltène/Whaledent Inc.
Address	Raiffeisenstrasse 30 89129 Langenau Germany	235 Ascot Parkway Cuyahoga Falls, Ohio 44223 United States
Telephone	+49 (7345) 805 0	+1 330 916 8800
Fax	+49 (7345) 805 201	+1 330 916 7077
Website	www.coltene.com	www.coltene.com
Email	msds@coltene.com	info.us@coltene.com

#### **Emergency phone number**

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+1 867 670 2867
Other emergency telephone numbers	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

Une fois connecté et si le message n'est pas dans votre langue préférée alors s'il vous plaît cadran 07

#### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

C	lassification	Simple Asphyxiant, Gases Under Pressure (Compressed Gas)

#### Label elements

Hazard pictogram(s)	
Signal word	Warning

#### Hazard statement(s)

H280	Contains gas under pressure; may explode if heated.
	May displace oxygen and cause rapid suffocation

## Physical and Health hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) Prevention

Not Applicable

#### Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

P410+P403 Protect from sunlight. Store in a well-ventilated place.

## Precautionary statement(s) Disposal

Not Applicable

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
811-97-2	60-100	1,1,1,2-tetrafluoroethane

## **SECTION 4 First-aid measures**

#### Description of first aid measures

	<ul> <li>If product comes in contact with eyes remove the patient from gas source or contaminated area.</li> <li>Take the patient to the nearest eye wash, shower or other source of clean water.</li> <li>Open the eyelid(s) wide to allow the material to evaporate.</li> <li>Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.</li> </ul>
	The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.
Eye Contact	<ul> <li>Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)</li> <li>Transport to hospital or doctor.</li> </ul>
	Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.
	If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.
	Ensure verbal communication and physical contact with the patient.
	DO NOT allow the patient to rub the eyes
	DO NOT allow the patient to tightly shut the eyes
	DO NOT introduce oil or ointment into the eye(s) without medical advice
	DO NOT use hot or tepid water.

Skin Contact	If skin or hair contact occurs: <ul> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>Following exposure to gas, remove the patient from the gas source or contaminated area.</li> <li>NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.</li> <li>Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>If the patient is not breathing spontaneously, administer rescue breathing.</li> <li>If the patient does not have a pulse, administer CPR.</li> <li>If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.</li> <li>Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction.</li> <li>Keep the patient warm, comfortable and at rest while awaiting medical care.</li> <li>MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.</li> <li>Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.</li> </ul>
Ingestion	<ul> <li>Not considered a normal route of entry.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> <li>If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:

There is no specific antidote

C: Decontamination

- ▶ Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)
- D: Enhanced elimination:

+ There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

- POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition
- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- ▶ If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient
- For frost-bite caused by liquefied petroleum gas:
- If part has not thawed, place in warm water bath (41-46 C) for 15-20 minutes, until the skin turns pink or red.
- Analgesia may be necessary while thawing.
- If there has been a massive exposure, the general body temperature must be depressed, and the patient must be immediately rewarmed by whole-body immersion, in a bath at the above temperature.
- Shock may occur during rewarming.
- Administer tetanus toxoid booster after hospitalization.
- Prophylactic antibiotics may be useful.
- The patient may require anticoagulants and oxygen.

[Shell Australia 22/12/87]

For gas exposures:

#### -----

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 I/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

Positive-pressure ventilation using a bag-valve mask might be of use.

Monitor and treat, where necessary, for arrhythmias.

- + Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.

Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

#### **SECTION 5 Fire-fighting measures**

#### Extinguishing media

SMALL FIRE: Use extinguishing agent suitable for type of surrounding fire.

LARGE FIRE: Cool cylinder.

DO NOT direct water at source of leak or venting safety devices as icing may occur.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

<ul> <li>Altern Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus and protective gloves.</li> <li>Fight fire from a safe distance, with adequate cover.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>DO NOT approach cylinders suspected to be hot.</li> <li>Cool fire exposed cylinders with water spray from a protected location.</li> <li>If safe to do so, remove cylinders from path of fire.</li> <li>SPECIAL REQUIREMENTS:         <ul> <li>Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion.</li> <li>Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter.</li> <li>Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire.</li> <li>FIRE FIGHTING REQUIREMENTS:                  <ul> <li>Fire Fighting safety professional.</li> <li>Containers may explode when heated - Ruptured cylinders may rocket</li> <li>Fire exposed containers may explode when heated - Ruptured cylinders may rocket</li> <li>Fire sposed containers may explode when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>May decompose explosively when heated or involved in fire.</li> </ul> </li> </ul></li></ul>		GENERAL
Fire Fighting       SPECIAL REQUIREMENTS:         • Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion.         • Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter.         • Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire.         • FIRE FIGHTING REQUIREMENTS:         • The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional.         • Containers may explode when heated - Ruptured cylinders may rocket         • Fire exposed containers may vent contents through pressure relief devices.         • High concentrations of gas may cause asphyxiation without warning.		<ul> <li>Wear breathing apparatus and protective gloves.</li> <li>Fight fire from a safe distance, with adequate cover.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>DO NOT approach cylinders suspected to be hot.</li> <li>Cool fire exposed cylinders with water spray from a protected location.</li> <li>If safe to do so, remove cylinders from path of fire.</li> </ul>
<ul> <li>Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter.</li> <li>Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire.</li> <li>FIRE FIGHTING REQUIREMENTS:</li> <li>The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional.</li> <li>Containers may explode when heated - Ruptured cylinders may rocket</li> <li>Fire exposed containers may vent contents through pressure relief devices.</li> <li>High concentrations of gas may cause asphyxiation without warning.</li> </ul>	Fire Fighting	
Image: Containers may explode when heated - Ruptured cylinders may rocket         • Fire exposed containers may vent contents through pressure relief devices.         • High concentrations of gas may cause asphyxiation without warning.		<ul> <li>Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter.</li> <li>Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if</li> </ul>
The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional.         • Containers may explode when heated - Ruptured cylinders may rocket         • Fire exposed containers may vent contents through pressure relief devices.         • High concentrations of gas may cause asphyxiation without warning.		FIRE FIGHTING REQUIREMENTS:
<ul> <li>Fire exposed containers may vent contents through pressure relief devices.</li> <li>High concentrations of gas may cause asphyxiation without warning.</li> </ul>		The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting
<ul> <li>Contact with gas may cause burns, severe injury and/ or frostbite.</li> <li>Decomposition may produce toxic fumes of:</li> </ul>		<ul> <li>Fire exposed containers may vent contents through pressure relief devices.</li> <li>High concentrations of gas may cause asphyxiation without warning.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>Contact with gas may cause burns, severe injury and/ or frostbite.</li> </ul>
Fire/Explosion Hazard       , carbon monoxide (CO)         Combustion products include:       , carbon dioxide (CO2)	Fire/Explosion Hazard	Combustion products include:
hydrogen fluoride		, hydrogen fluoride
<ul> <li>, other pyrolysis products typical of burning organic material.</li> <li>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.</li> <li>Vented gas is more dense than air and may collect in pits, basements.</li> </ul>		Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

<sup>-----</sup>

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.</li> <li>DO NOT enter confined spaces where gas may have accumulated.</li> <li>Increase ventilation.</li> <li>Clear area of personnel.</li> <li>Stop leak only if safe to so do.</li> <li>Remove leaking cylinders to safe place. Release pressure under safe controlled conditions by opening valve.</li> <li>Do not exert excessive pressure on the valve; do not attempt to operate a damaged valve</li> <li>Orientate cylinder so that the leak is gas, not liquid, to minimise rate of leakage</li> <li>Keep area clear of personnel until gas has dispersed.</li> </ul>
Major Spills	<ul> <li>Clear area of all unprotected personnel and move upwind.</li> <li>Alert Emergency Authority and advise them of the location and nature of hazard.</li> <li>Wear breathing apparatus and protective gloves.</li> <li>Prevent by any means available, spillage from entering drains and water-courses.</li> <li>Consider evacuation.</li> <li>Increase ventilation.</li> <li>No smoking or naked lights within area.</li> <li>Stop leak only if safe to so do.</li> <li>Water spray or fog may be used to disperse vapour.</li> <li>DO NOT enter confined space where gas may have collected.</li> <li>Keep area clear until gas has dispersed.</li> <li>Remove leaking cylinders to a safe place.</li> <li>Fit vent pipes. Release pressure under safe, controlled conditions</li> <li>Burn issuing gas at vent pipes.</li> <li>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

Precautions for safe handling		
Safe handling	DO NOT transfer gas from one cylinder to another.	
Other information		

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>DO NOT use aluminium or galvanised containers</li> <li>Cylinder:</li> <li>Ensure the use of equipment rated for cylinder pressure.</li> <li>Ensure the use of compatible materials of construction.</li> <li>Valve protection cap to be in place until cylinder is secured, connected.</li> <li>Cylinder must be properly secured either in use or in storage.</li> <li>Cylinder valve must be closed when not in use or when empty.</li> <li>Segregate full from empty cylinders.</li> </ul>
Storage incompatibility	As a general rule, hydrofluorocarbons tend to be flammable unless they contain more fluorine atoms than hydrogen atoms. Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances

## **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits (OEL)

INGREDIENT DATA

#### **Emergency Limits**

Ingredient	TEEL-1	TEEL-2		TEEL-3
1,1,1,2-tetrafluoroethane	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
1,1,1,2-tetrafluoroethane	Not Available		Not Available	

#### MATERIAL DATA

May act as a simple asphyxiants; these are gases which, when present in high concentrations, reduce the oxygen content in air below that required to support breathing, consciousness and life; loss of consciousness, with death by suffocation may rapidly occur in an oxygen deficient atmosphere. **CARE**: Most simple asphyxiants are odourless or possess low odour and there is no warning on entry into an oxygen deficient atmosphere. If there is any doubt, oxygen content can be checked simply and quickly. It may not be appropriate to only recommend an exposure standard for simple asphyxiants rather it is essential that sufficient oxygen be maintained. Air normally has 21 percent oxygen by volume, with 18 percent regarded as minimum under normal atmospheric pressure to maintain consciousness / life. At pressures significantly higher or lower than normal atmospheric pressure, expert guidance should be sought.

#### Exposure controls

Exposure controls				
Appropriate engineering	<ul> <li>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</li> <li>The basic types of engineering controls are:</li> <li>Process controls which involve changing the way a job activity or process is done to reduce the risk.</li> <li>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</li> <li>Employers may need to use multiple types of controls to prevent employee overexposure.</li> <li>Areas where cylinders are stored require good ventilation and, if enclosed, need discrete/controlled exhaust ventilation.</li> <li>Secondary containment and exhaust gas treatment may be required by certain jurisdictions.</li> <li>Local exhaust ventilation may be required in work areas.</li> <li>Consideration should be given to the use of diaphragm or bellows-sealed, soft-seat valves; backflow prevention devices and flow-monitoring or limiting devices.</li> <li>Automated alerting systems with automatic shutdown of gas-flow may be appropriate and may in fact be mandatory in certain jurisdictions.</li> <li>Respiratory protection in the form of air-supplied or self-contained breathing equipment must be worn if the oxygen concentration in the workplace air is less than 19%.</li> <li>Cartridge respirators do NOT give protection and may result in rapid suffocation.</li> </ul>			
	velocities" of fresh circulating air required to effectively remove the contamina Type of Contaminant:		Air Speed:	
	gas discharge (active generation into zone of rapid air mot	ion)	1-2.5 m/s (200-500 f/min.)	
	Within each range the appropriate value depends on:			
	Lower end of the range	Upp	per end of the range	
	1: Room air currents minimal or favourable to capture	1: C	Disturbing room air currents	
	2: Contaminants of low toxicity or of nuisance value only.	2: 0	Contaminants of high toxicity	
	3: Intermittent, low production.	3: ⊦	ligh production, heavy use	
	4: Large hood or large air mass in motion	4: 5	Small hood-local control only	
	Simple theory shows that air velocity falls rapidly with distance generally decreases with the square of distance from the ext extraction point should be adjusted, accordingly, after referent extraction fan, for example, should be a minimum of 1-2.5 m distant from the extraction point. Other mechanical considerat apparatus, make it essential that theoretical air velocities are installed or used.	raction nce to /s (20 ations	n point (in simple cases). Therefore the air speed at the distance from the contaminating source. The air velocity at the 0-500 f/min.) for extraction of gases discharged 2 meters , producing performance deficits within the extraction	

Personal protection



- Safety glasses with side shields
- Chemical goggles.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should

	be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Skin protection	See Hand protection below
Hands/feet protection	When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	<ul> <li>Protective overalls, closely fitted at neck and wrist.</li> <li>Eye-wash unit.</li> <li>Ensure availability of lifeline in confined spaces.</li> <li>Staff should be trained in all aspects of rescue work.</li> <li>Rescue gear: Two sets of SCBA breathing apparatus Rescue Harness, lines etc.</li> </ul>

#### **Respiratory protection**

Full face respirator with supplied air.

- + Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- + Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

#### **SECTION 9** Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Colourless		
	- -		1
Physical state	Compressed Gas	Relative density (Water = 1)	1.22
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>93	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.6	VOC g/L	Not Available

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7

#### Page 8 of 13

## Endo-Ice® Refrigerant Spray

Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	
SECTION 11 Toxicological information		

## Information on toxicological effects

1,1,1,2-tetrafluoroethane	TOXICITY Inhalation(Rat) LC50: 359453.102 ppm4h <sup>[2]</sup>	IRRITATION Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

1,1,1,2- TETRAFLUOROETHANE	* with added oxygen - ZhongHao New Chemical Materials MSDS Excessive concentration can have a narcotic effect; inhalation of high concentrations of decomposition products can cause lung oedema.					
Endo-Ice® Refrigerant Spray & 1,1,1,2- TETRAFLUOROETHANE	halogenated haloalkanes tend to act by tree radical or nongenotoxic mechanisms (such as generating peroxisome-proliferative					
Acute Toxicity	×	Carcinogenicity	×			
Skin Irritation/Corrosion	×	Reproductivity	×			

Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
Legend: X – Data either not available or does not fill the criteria for classification			

✔ – Data available to make classification

## **SECTION 12 Ecological information**

#### Toxicity

Endo-Ice® Refrigerant Spray	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Source
1,1,1,2-tetrafluoroethane	NOEC(ECx)	96h	Fish	300mg/l	Not Availab
	EC50	96h	Algae or other aquatic plants	142mg/l	2
	EC50	72h	Algae or other aquatic plants	>114mg/l	2
	LC50	96h	Fish	450mg/l	Not Availab
	EC50	48h	Crustacea	980mg/l	Not Availab

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

they have an ozone Depletion Potential (ODP) of 0. However, certain HFCs have high Global warming Potential (GWPs). Perfluorinated fluorocarbons (PFCs) have extremely high GWPs and long atmospheric lifetimes. They do not deplete stratospheric ozone, but the U.S. Environmental Protection Agency (EPA) is concerned about their impact on global warming.

Unlike other greenhouse gases in the Paris Agreement, hydrofluorocarbons have other international negotiations.

In September 2016, the New York Declaration on Forests urged a global reduction in the use of HFCs On 15 October 2016, due to these chemicals' contribution to climate change, negotiators from 197 nations meeting at the summit of the United Nations Environment Programme in Kigali, Rwanda reached a legally-binding accord to phase out hydrofluorocarbons (HFCs) in an amendment to the Montreal Protocol:

The final deal will divide the world economy into three tracks.

• The richest countries, including the United States and those in the European Union, will freeze the production and consumption of HFCs by 2018, reducing them to about 15 percent of 2012 levels by 2036.

• Much of the rest of the world, including China, Brazil and all of Africa, will freeze HFC use by 2024, reducing it to 20 percent of 2021 levels by 2045.

• A small group of the world s hottest countries — India, Pakistan, Iran, Saudi Arabia and Kuwait — will have the most lenient schedule, freezing HFC use by 2028 and reducing it to about 15 percent of 2025 levels by 2047.

#### 90halkane

In addition to carbon dioxide (CO2), methane (CH4) and nitrous oxide (N2O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and exhibiting very high specific radiative forcing (radiative forcing is the change in the balance between radiation coming into the atmosphere and radiation out; a positive radiative forcing tends on average to warm the surface of the earth). These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF6).

The greenhouse potential of these substances, expressed as multiples of that of CO2, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF6. Once emitted into the atmosphere, these substances have an impact on the environment for decades, centuries, or in certain instances, for thousands of years.

Many of these substances have only been commercialised for a few years, and still only contribute only a small percentage of those gases released to the atmosphere by humans (anthropogenic) which increase the greenhouse effect. However, a rapid increase can be seen in their consumption and emission, and therefore in their contribution to the anthropogenic increase in the greenhouse effect.

Since the adoption of the Kyoto Protocol, new fluorinated substances have appeared on the market, which are stable in air and have a high greenhouse potential; these include nitrogen trifluoride (NF3) and fluoroethers.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1,1,1,2-tetrafluoroethane	HIGH	HIGH

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
1,1,1,2-tetrafluoroethane	LOW (LogKOW = 1.68)

#### Mobility in soil

Ingredient	Mobility
1,1,1,2-tetrafluoroethane	LOW (KOC = 96.63)

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

#### **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant	NO

#### Land transport (TDG)

UN number	3159
UN proper shipping name	REFRIGERANT GAS R 134a; or 1,1,1,2-TETRAFLUOROETHANE

Transport hazard class(es)	Class     2.2       Subrisk     Not Applicable		
Packing group	Not Applica	ble	
Environmental hazard	Not Applica	able	
Special precautions for user	Special p Explosive ERAP Inc	Limit and Limited Quantity Index	Not Applicable 0.125 L Not Applicable

#### Air transport (ICAO-IATA / DGR)

UN number	3159				
UN proper shipping name	1,1,1,2-Tetrafluoroethane; Refrigerant gas R 134a				
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	2.2 Not Applicable 2L			
Packing group	Not Applicable	Not Applicable			
Environmental hazard	Not Applicable				
	Special provisions		Not Applicable		
	Cargo Only Packing Ir	nstructions	200		
	Cargo Only Maximum	Qty / Pack	150 kg		
Special precautions for user	Passenger and Cargo Packing Instructions		200		
usei	Passenger and Cargo Maximum Qty / Pack		75 kg		
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden		
	Passenger and Cargo	Limited Maximum Qty / Pack	Forbidden		

#### Sea transport (IMDG-Code / GGVSee)

UN number	3159	3159		
UN proper shipping name	1,1,1,2-TETRAFLUC	DROETHANE (REFRIGERANT GAS R 134a)		
Transport hazard class(es)	IMDG Class	2.2		
	IMDG Subrisk	Not Applicable		
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
	EMS Number	F-C, S-V		
Special precautions for user	Special provisions	Not Applicable		
	Limited Quantities	120 mL		

#### Transport in bulk according to Annex II of MARPOL and the IBC code

### Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
1,1,1,2-tetrafluoroethane	Not Available

## Transport in bulk in accordance with the ICG Code

Product name	Ship Type
1,1,1,2-tetrafluoroethane	Not Available

## **SECTION 15 Regulatory information**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

1,1,1,2-tetrafluoroethane is found on the following regulatory lists	
Canada Categorization decisions for all DSL substances	Canada Toxicological Index Service - Workplace Hazardous Materials
Canada Domestic Substances List (DSL)	Information System - WHMIS GHS
	International Agency for Research on Cancer (IARC) - Agents Classified by
	the IARC Monographs - Not Classified as Carcinogenic

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (1,1,1,2-tetrafluoroethane)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	21/04/2022
Initial Date	25/03/2022

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals **DSL:** Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.