SAFETY DATA SHEETS

This SDS packet was issued with item:

074265500

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

074290565 074290896 074290904

MATERIAL SAFETY DATA SHEET

SILANE PRIMER

1 - IDENTIFICATION

Manufacturer: Kerr Corporation

Address:1717 West Collins AvenueCity, State, Zip:Orange, CA 92867-5422Telephone:1-800-KERR-123

Emergency: Chemtrec 1-800-424-9300

Date Prepared: July 2009

2 - COMPOSITION INFORMATION

Hazardous Ingredients

<u>CAS # PEL TLV %</u>
Ethyl Alcohol 64-17-5 1000 ppm 1000 ppm 80-85

Other Ingredients

Organosilane Ester N/A N/A 15-20

3 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 173°F (78.5°C) Specific Gravity (H₂0 = 1): ~0.85 Vapor Pressure (mm Hg): 40mm Hg

Melting Point: N/A

Vapor Density (AIR = 1): 1.59 Solubility in Water: Soluble Reactivity in Water: N/A

Appearance and Odor: Clear, colorless liquid with alcohol odor

4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 55°F (13°C)
Flammable Limits: LEL: 4.3 UEL: 19

Extinguishing Media: Carbon dioxide, dry chemical, water spray

Special Fire Fighting Procedures: None Unusual Fire and Explosion Hazards: None

5 - REACTIVITY DATA

Stability: Stable if stored as directed.

Conditions to Avoid: Heat, sparks, open flame

Incompatibility (Material to Avoid): Strong oxidizing agents **Hazardous Decomposition Products:** Carbon monoxide, Carbon

dioxide.

Hazardous Polymerization: Will not occur

6 - HEALTH HAZARD DATA

Routes of Entry:

Skin: May cause a mild irritation. **Eyes:** May cause a mild irritation.

Inhalation: May cause irritation of the throat.
Ingestion: May be poisonous by ingestion.
Carcinogenicity - NTP: No

IARC Monographs: No OSHA Regulated Carcinogen: No

7 - EMERGENCY FIRST AID PROCEDURES

Skin: Wash thoroughly with soap and water. Use hand cream.

Eyes: Flush with water for at 15 minutes.

Inhalation: Remove to fresh air. Restore breathing if necessary. **Ingestion:** Do not give liquids. If victim is unconscious, contact

physician.

8 - PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken in case material is released or spilled: Dilute with water, wipe with cloth and transfer to suitable container for disposal. **Waste Disposal Method:** Material should not be allowed to drain to sewers. Incinerate liquid in proper equipment. Dispose of in accordance with local regulations.

Precautions to be taken in handling and storing: Store in a cool, dry

place. Keep away from ignition sources.

Other precautions: Use according to directions.

9 - CONTROL MEASURES

Respiratory Protection (Specify Type): Not needed

VENTILATION:

Local Exhaust: Recommended to keep exposure under 1000ppm.

Mechanical (General): Should be sufficient

Protective Gloves: Recommended

Eye Protection: Safety glasses with side shields

Work/Hygiene Practices: Handle in accordance with good personal hygiene and safety practices. These practices include avoiding

unnecessary exposure.

10 - TRANSPORTATION INFORMATION

Regulated: DOT, IATA, IMO
Proper Shipping Name: Ethyl Alcohol Solution

Hazard Class: 3
Identification Number: 1170
Packaging Group: II

Label: Flammable Liquid
NOTE: May be shipped ORM-D

See 49CFR 173.4

11 - SPECIAL INFORMATION

HMIS (Hazardous Material Identification System) Rating:

H1 F3 R1

[HMIS Index: 4 - Severe Hazard; 3 -Serious Hazard;

2 - Moderate Hazard; 1 - Slight Hazard; 0 - Minimum Hazard]

Note: This MSDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product. The information in this MSDS is, to the best of our knowledge, believed to be accurate.



SAFETY DATA SHEET

Silane Primer

Section 1. Identification

GHS product identifier

Other means of identification

: Silane Primer

: Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Dental product: Dental Restoration

Area of application : Professional applications.

Manufacturer : Kerr Corporation

> 1717 West Collins Avenue Orange, CA 92867-5422

Telephone no.: 1-800-KERR-123

e-mail address of person responsible for this SDS

: edwin.varela@kavokerrgroup.com

Emergency telephone number (with hours of

operation)

: CHEMTREC® (24 hours) U.S. : 1-800-424-9300 International: +1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Health effects are based on the uncured material.

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation and Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 10.5%

GHS label elements

Hazard pictograms







Signal word

Danger

Hazard statements

: Highly flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Date of issue/Date of revision 1/12 : 03/26/2015 Date of previous issue : No previous validation Version: 1

Section 2. Hazards identification

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response

: Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage Disposal

- : Store locked up. Store in a well-ventilated place. Keep cool.
- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification : Mixture: Not available.

CAS number/other identifiers

CAS number : Not applicable.

Product code : Not available.

Ingredient name	Other names	%	CAS number
ethanol	ethanol	60-100	64-17-5
Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	Not available.	1-5	41637-38-1
2,2'-ethylenedioxydiethyl dimethacrylate	2,2'-ethylenedioxydiethyl dimethacrylate	1-5	109-16-0
3-trimethoxysilylpropyl methacrylate	3-trimethoxysilylpropyl methacrylate	1-5	2530-85-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: No special measures are required. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.

Inhalation

: No special measures required. If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact

: No special measures required. In case of contact, immediately flush skin with plenty of water. Get medical attention if symptoms occur.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 2/12

Section 4. First aid measures

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Can cause central nervous system (CNS) depression. Irritating to mouth, throat and

stomach.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : In case of major fire and large quantities: No action shall be taken involving any

personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Date of issue/Date of revision: 03/26/2015Date of previous issue: No previous validationVersion: 13/12

Section 5. Fire-fighting measures

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: In case of major fire and large quantities: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Low release. For professional use only. Handling of product in very small amounts or in situations where release is highly unlikely

For emergency responders: Low release. See also the information in "For non-emergency personnel".

Environmental precautions

: Low release. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: No special measures are required for small quantities under normal and intended conditions of product use. For professional use only. Put on appropriate personal protective equipment (see Section 8). Handle with care and dispose in a safe manner.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version: 1 4/12

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
ethanol	ACGIH TLV (United States, 4/2014). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989)	
	TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours.	
	TWA: 1000 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.	

Appropriate engineering controls

Environmental exposure controls

- : No special measures are required for small quantities under normal and intended conditions of product use.
- : No special measures are required for small quantities under normal and intended conditions of product use.

Individual protection measures

Hygiene measures

: No special measures are required for small quantities under normal and intended conditions of product use.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Clear.]
Color : Colorless.
Odor : Alcohol-like.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 78.5°C (173.3°F)

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 5/12

Section 9. Physical and chemical properties

: Closed cup: 13°C (55.4°F) Flash point

Evaporation rate : Not available. Flammability (solid, gas) : Not applicable. Lower and upper explosive : Lower: 4.3% Upper: 19% (flammable) limits

Vapor pressure : 5.3 kPa (40 mm Hg) [room temperature]

Vapor density : 1.59 [Air = 1]

Relative density : 0.85

: Insoluble in the following materials: cold water and hot water. Solubility

Solubility in water : Not available. Partition coefficient: noctanol/water

: Not available.

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available. SADT : Not available. **Viscosity** : Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
2,2'-ethylenedioxydiethyl dimethacrylate	LD50 Oral	Rat	10837 mg/kg	-
3-trimethoxysilylpropyl methacrylate	LD50 Oral	Rat	23504 mg/kg	-

Conclusion/Summary

Based on the criteria of the protocol, this product is considered non-cytotoxic per ISO 10993-5.

Irritation/Corrosion

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version: 1 6/12

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
3-trimethoxysilylpropyl methacrylate	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Silane Primer	skin	Guinea pig	Not sensitizing

Mutagenicity

Not available.

Conclusion/Summary

: Not mutagenic in Ames test.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
ethanol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ethanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	Category 3	Not applicable.	Respiratory tract irritation
2,2'-ethylenedioxydiethyl dimethacrylate	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	3.3	Route of exposure	Target organs
ethanol	Category 2	Not determined	liver

Aspiration hazard

Not available.

Date of issue/Date of revision : 03	3/26/2015 Date	e of previous issue :	No previous validation	Version	: 1	7/12
-------------------------------------	----------------	-----------------------	------------------------	---------	-----	------

Section 11. Toxicological information

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact

: Defatting to the skin. May cause skin dryness and irritation.

Ingestion

: Can cause central nervous system (CNS) depression. Irritating to mouth, throat and

stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact

: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion

: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision: 03/26/2015Date of previous issue: No previous validationVersion: 18/12

Section 11. Toxicological information

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae	96 hours 48 hours 48 hours
	Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	4 days 96 hours 12 weeks

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low
Poly(oxy-1,2-ethanediyl), α,α' - [(1-methylethylidene)di-4,1- phenylene]bis[ω -[(2-methyl-1- oxo-2-propen-1-yl)oxy]-	3.43 to 5.62	2372	high
2,2'-ethylenedioxydiethyl dimethacrylate	1.88	-	low
3-trimethoxysilylpropyl methacrylate	2.1	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 9/12

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1170	UN1170	UN1170
UN proper shipping name	Ethanol solutions	ETHANOL SOLUTION	Ethanol solution
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Additional information	Limited quantity Yes.	Emergency schedules (EmS) F-E, S-D	Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 353
	Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions 24, IB2, T4, TP1	Special provisions 144	Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 364 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y341 Special provisions A3, A58, A180

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: mequinol; oxybenzone

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances

: Not listed

DEA List I Chemicals (Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Date of issue/Date of revision 10/12 : 03/26/2015 Date of previous issue : No previous validation Version: 1

Section 15. Regulatory information

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ethylene oxide	<0.00555	Yes.	1000	-	10	-

SARA 304 RQ : 200200.2 lbs / 90890.9 kg [28248 gal / 106930.5 L]

SARA 311/312

Classification : Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
ethanol Poly(oxy-1,2-ethanediyl), α,α'-[(1- methylethylidene)di-4,1-phenylene]bis[ω-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	60-100 1-5	Yes. No.	No. No.	No. No.	Yes. Yes.	Yes. No.
2,2'-ethylenedioxydiethyl dimethacrylate 3-trimethoxysilylpropyl methacrylate	1-5 1-5	Yes. No.	No.	No.	Yes.	No.

SARA 313

Not applicable.

State regulations

Massachusetts : The following components are listed: ETHYL ALCOHOL

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL

Pennsylvania: The following components are listed: DENATURED ALCOHOL

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	•		Maximum acceptable dosage level
ethylene oxide	Yes.	Yes.	Yes.	Yes.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version :1 11/12

Section 16. Other information

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of

revision

: 03/26/2015

Date of previous issue

: No previous validation

Version Prepared by

: IHS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision

: 03/26/2015 Date of previous issue

: No previous validation

Version: 1

12/12



Kerr Material Safety Data Sheet

Silane Primer

Product and company identification

: Silane Primer **Product name**

Material uses : Dental product: Dental Restoration

Manufacturer : Kerr Corporation

> 1717 West Collins Avenue Orange, CA 92867-5422 Telephone no.: 1-800-KERR-123

Prepared by

In case of emergency : CHEMTREC® (24 hours) U.S.: 1-800-424-9300 International: +1-703-527-3887

Hazards identification

Physical state : Liquid. [Clear.] Color Colorless. **Odor** : Alcohol-like.

Emergency overview

Signal word : DANGER!

Hazard statements FLAMMABLE LIQUID AND VAPOR. INHALATION CAUSES HEADACHES.

DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO

UNCONSCIOUSNESS. CAUSES RESPIRATORY TRACT. EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL

DATA.

Precautions : Health effects are based on the uncured material. Keep away from heat, sparks and

flame. Do not breathe vapor or mist. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for

use. Wash thoroughly after handling. Keep container tightly closed.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. Irritating to respiratory system.

: Can cause central nervous system (CNS) depression. Ingestion : Irritating to skin. May cause sensitization by skin contact. Skin **Eyes** : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data. Once

> sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged or repeated contact can defat the skin and lead to irritation, cracking

and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

2. Hazards identification

Target organs

: Contains material which may cause damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation

: Adverse symptoms may include the following:

nausea or vomiting respiratory tract irritation

coughing headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Ingestion

: No specific data.

Skin

: Adverse symptoms may include the following:

irritation redness dryness cracking

Eyes

: Adverse symptoms may include the following:

pain or irritation watering

watering redness

Medical conditions aggravated by overexposure : Pre-existing skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

Name	CAS number	%
ethanol	64-17-5	60-100
Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-	41637-38-1	1-5
1-oxo-2-propen-1-yl)oxy]- 2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	1-5
	2530-85-0	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

: No special measures are required. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.

Skin contact

: No special measures required. In case of contact, immediately flush skin with plenty of water. Get medical attention if symptoms occur.

Inhalation

: No special measures required. If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Get medical attention if adverse health effects persist or are severe.

Silane Primer

4. First aid measures

Protection of first-aiders

: In case of major fire and large quantities: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Antidote information

Product/ingredient name	Antidote information
No antidote information known	

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product

: Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable

: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable

: Do not use water jet.

Special exposure hazards

: In case of major fire and large quantities: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: Low release. For professional use only. Handling of product in very small amounts or in situations where release is highly unlikely

Environmental precautions

: Low release. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

7. Handling and storage

Handling

: No special measures are required for small quantities under normal and intended conditions of product use. For professional use only. Put on appropriate personal protective equipment (see Section 8). Handle with care and dispose in a safe manner.

7. Handling and storage

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
	US ACGIH 4/2014 AB 4/2009 BC 7/2013 ON 1/2013 QC 1/2014	- 1000 - - 1000	- 1880 - - 1880	- - - -	1000 - 1000 1000	- - - -	- - - -	- - - -	- - - -	- - -	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures

 No special measures are required for small quantities under normal and intended conditions of product use.

Hygiene measures

: No special measures are required for small quantities under normal and intended conditions of product use.

Personal protection
Respiratory

: No special measures are required for small quantities under normal and intended conditions of product use.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin

: No special measures are required for small quantities under normal and intended conditions of product use.

Environmental exposure controls

: No special measures are required for small quantities under normal and intended conditions of product use.

9. Physical and chemical properties

Physical state : Liquid. [Clear.]

Flash point : Closed cup: 13°C (55.4°F)

Auto-ignition temperature : Not available.

Flammable limits : Lower: 4.3%

Upper: 19%

Color : Colorless.

Odor : Alcohol-like.

pH : Not available.

Boiling/condensation point : 78.5°C (173.3°F)

Melting/freezing point : Not available.

Relative density : 0.85

Density : Not available.

Vapor pressure : 5.3 kPa (40 mm Hg) [room temperature]

Vapor density : 1.59 [Air = 1]
Odor threshold : Not available.
Evaporation rate : Not available.
Viscosity : Not available.

Solubility : Insoluble in the following materials: cold water and hot water.

LogK_{ow}: Not available.

10. Stability and reactivity

Chemical stability

: The product is stable.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-ethylenedioxydiethyl dimethacrylate	LD50 Oral	Rat	10837 mg/kg	-
ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m³ 7 g/kg	4 hours
3-trimethoxysilylpropyl methacrylate	LD50 Oral	Rat	23504 mg/kg	-

Conclusion/Summary

 Based on the criteria of the protocol, this product is considered non-cytotoxic per ISO 10993-5.

Chronic toxicity

Not available.

Irritation/Corrosion

Silane Primer

11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
3-trimethoxysilylpropyl methacrylate	Eyes - Mild irritant	Rabbit	_	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	_	24 hours 500 milligrams	-

Sensitizer

3	Route of exposure	Species	Result
Silane Primer	skin	Guinea pig	Not sensitizing

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanol	A3	1	-	-	-	-

Mutagenicity

Not available.

Conclusion/Summary

: Not mutagenic in Ames test.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water Acute LC50 42000 μg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	96 hours 48 hours 48 hours 4 days 96 hours 12 weeks

Persistence/degradability

Not available.

Silane Primer

12. Ecological information

Partition coefficient: n-

octanol/water

: Not available.

Bioconcentration factor

: Not available.

Mobility

Taxisity of the proof

: Not available.

Toxicity of the products of

Other adverse effects

: Not available.

biodegradation

: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN1170	ETHANOL SOLUTION	3	II	&	Explosive Limit and Limited Quantity Index 1 Passenger Carrying Road or Rail Index
IMDG Class	UN1170	ETHANOL SOLUTION	3	II	<u>&</u>	Emergency schedules (EmS) F-E, S-D Special provisions 144
IATA-DGR Class	UN1170	Ethanol solution	3	II		Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 353 Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 364 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y341 Special provisions A3, A58, A180

PG*: Packing group

Regulatory information 15.

United States inventory

(TSCA 8b)

All components are listed or exempted.

WHMIS (Canada) : Class B-2: Flammable liquid

Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Ethanol

CEPA Toxic substances : None of the components are listed. Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined. Korea inventory: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): Not determined. Taiwan inventory (CSNN): Not determined.

Chemical Weapons

Convention List Schedule

I Chemicals

Chemical Weapons Convention List Schedule

II Chemicals

Chemical Weapons

Convention List Schedule

III Chemicals

: Not listed

: Not listed

: Not listed


Other information 16.

Label requirements

: FLAMMABLE LIQUID AND VAPOR. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material

Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of issue : 3/26/2015.

Silane Primer

16. Other information

Date of previous issue : No previous validation.

Version : 1

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



SAFETY DATA SHEET

Section 1. Product And Company Identification

Product Name: Silane Primer

Product Use: Dental product: Dental restoration

Manufacturer: Kerr Corporation

1717 W. Collins Ave. Orange, CA 92867-5422

U.S.A.

Information Phone Number: 1-800-841-1428 (Customer Service)

Chemical Emergency Phone Number (Chemical Spills, Leaks, Fire, Exposure or Accident only):

CHEMTREC 1-800-424-9300 (in the US) 1-703-527-3887 (Outside the US)

SDS Date of Preparation/Revision: April 1, 2019

Section 2. Hazards Identification

GHS Classification:

Flammable Liquid Category 2
Skin Irritation Category 2
Skin Sensitization Category 1
Eye Irritation Category 2A
Specific Target Organ Toxicity Single Exposure Category 3
Specific Target Organ Toxicity Repeated Exposure Category 2

Label Elements:

Danger!



Hazard Phrases

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness and dizziness.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Phrases:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep container tightly closed.

Use explosion-proof electrical, ventilating, lighting, and all material-handling equipment.

Use only non-sparking tools.



Take precautionary measures against static discharge.

Do not breathe vapors.

Wash exposed skin thoroughly after handling.

Wear protective gloves and eye protection.

Contaminated work clothing should not be allowed out of the workplace.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists get medical attention.

In case of fire: Use water fog, alcohol foam carbon dioxide or dry chemical to extinguish.

Store in a well ventilated place.

Store locked up.

Dispose of contents and container in accordance with local and national regulations.

Section 3. Composition/Information on Ingredients

Component	CAS No.	Amount
Ethanol	64-17-5	60-100%
(1-methylethylidene)bis[4,1-phenyleneoxy(2-	1565-94-2	5-10%
hydroxy-3,1-propanediyl)] bismethacrylate		
Poly(oxy-1,2-ethanediyl), α,α'-[(1-	41637-38-1	1-5%
methylethylidene)di-4,1-phenylene]bis[ω-[(2-		
methyl-1-oxo-2-propen-1-yl)oxy]-		
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	1-5%
3-trimethoxysilylpropyl methacrylate	2530-85-0	1-5%

Section 4. First Aid Measures

Inhalation: Move to fresh air if symptoms occur and seek medical attention if symptoms persist.

Skin Contact: Take off contaminated clothing. Rinse skin with plenty of water. Get medical attention is irritation develops and persists.

Eye Contact: Hold eye open and rinse slowly and gently with water for several minutes. Remove contact lenses, if present, then continue rinsing. Get medical attention if irritation persists.

Ingestion: If swallowed, rinse mouth with water. If symptoms develop, get medical attention.

Most important symptoms and effects, acute and delayed: Causes moderate to severe eye irritation. Skin contact may cause dryness and irritation. May cause allergic skin reaction (sensitization.) Ingestion can cause central nervous system depression and irritating to mouth, throat and stomach. Inhalation may cause drowsiness and dizziness.

Indication of immediate medical attention and special treatment, if needed: Immediate medical attention is not required.



Section 5. Fire Fighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Combustion may produce carbon dioxide, carbon monoxide, and metal oxides.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Cool fire-exposed containers with water. Contain water used in firefighting from entering sewers or natural waterways.

Section 6: Accidental Release Measures

Personal precautions, Protective equipment, and Emergency procedures: Evacuate spill area and keep unprotected personnel away. Avoid contact with eyes, skin and clothing. Wear appropriate protective clothing and equipment. Do not breathe vapors.

Environmental Precautions: Avoid releases to the environment. Report spill as required by local and federal regulations.

Methods and Materials for Containment and Cleaning up: Prompt cleanup and removal are necessary. For small spills, take up in non-combustible absorbent material and shovel into container for disposal. For large spills, scoop solid spill into closing containers. This material and its container must be disposed of in a safe way, and as per local legislation. Notify authorities if product enters sewers or public waters. Wash off with plenty of water.

Section 7. Handling and Storage

Precautions for Safe Handling: Prevent contact with eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke in the work area. Do not breathe vapors. Use with adequate ventilation. Remove and wash contaminated clothing before reuse.

Empty containers retain product residues which can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area away from direct sunlight. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Section 8. Exposure Controls / Personal Protection

Exposure Limits

Chemical	Exposure Limit		
Ethanol	1000 ppm TWA OSHA PEL		
	1000 ppm STEL ACGIH TLV		



(1-methylethylidene)bis[4,1-phenyleneoxy(2-	None Established
hydroxy-3,1-propanediyl)] bismethacrylate	
Poly(oxy-1,2-ethanediyl), α,α'-[(1-	None Established
methylethylidene)di-4,1-phenylene]bis[ω-[(2-	
methyl-1-oxo-2-propen-1-yl)oxy]-	
2,2'-ethylenedioxydiethyl dimethacrylate	None Established
3-trimethoxysilylpropyl methacrylate	None Established

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, mechanical ventilation such as local exhaust may be needed to minimize exposure. Use explosion proof electrical equipment and wiring where required.

Respiratory Protection: None under normal use conditions with adequate ventilation. For operations where the occupational exposure limits are exceeded, an approved respirator with a respirable dust cartridge or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with applicable regulations and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Hand protection: Impervious gloves are suggested to prevent skin contact. Contact your glove supplier for selection assistance.

Eye Protection: Chemical safety goggles are recommended if contact is possible.

Skin Protection: Wear protective clothing as needed to avoid skin contact and contamination of personal clothing.

Hygiene measures: Suitable eye and skin washing facilities should be available in the work area.

Section 9. Physical and Chemical Properties

Appearance:Pale yellow liquidOdor:Alcohol-like odorOdor Threshold:Not availablepH:Not availableMelting/FreezingNot availableBoiling78.5°C (173.3°F)Point:Point/Range:

Flash Point: 13°C (55.4°F) (Closed **Evaporation** Not available

cup) Rate:

Flammability: (Solid, Not applicable Flammability LEL: 4.3% Limits: UEL: 19%

Vapor Pressure: 5.3 kPa (40 mmHg at Vapor 1.59 kg/m³

room temperature) **Density:**

Relative Density: 0.85 Solubilities: Insoluble in water

Partition Coefficient: Not available Autoignition Not available (N-Octanol/Water) Temperature:

Decomposition Not available **Viscosity:** Not available

Temperature:

Section 10. Stability and Reactivity

Reactivity: The product is not expected to be reactive.



Chemical Stability: Stable under normal storage and handling conditions. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not polymerize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible Materials: Oxidizing materials.

Hazardous decomposition products: Thermal decomposition will produce mercury oxide, mercury vapors, and metal oxides.

Section 11. Toxicological Information

Potential Health Effects:

Inhalation: Can cause central nervous system depression. May cause drowsiness, dizziness, and respiratory irritation.

Skin Contact: Defatting to the skin. May cause skin dryness and irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Can cause central nervous system depression. May be irritating to mouth, throat and stomach.

Chronic Hazards: May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Skin Sensitization: No adverse effects expected. Components are not sensitizers.

Respiratory Sensitization: No data available. This product is not expected to cause respiratory sensitization.

Germ Cell Mutagenicity: None of the components have shown mutagenic activity in animal studies.

Carcinogen: Ethanol is listed as "Carcinogenic to Humans" (Group 1) by IARC. None of the other components are listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH, or OSHA.

Developmental / Reproductive Toxicity: None of the components have been shown to cause reproductive or developmental toxicity.

Specific Target Organ Toxicity (Single Exposure): Single exposure to ethanol, Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]-, 2,2'-ethylenedioxydiethyl dimethacrylate may cause respiratory tract irritation. Single exposure to ethanol may also cause narcotic effects.

Specific Target Organ Toxicity (Repeated Exposure): Repeated exposure to methanol may cause damage to the liver.

Aspiration Toxicity: Not an aspiration hazard.

Acute Toxicity Values:

Ethanol: LD50 Oral rat: 7060 mg/kg; LC50 Inhalation rat: 124.7 mg/L/4 hr

Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-

yl)oxy]-: LD50 Oral rat: >2000 mg/kg; LD50 Dermal rat: >2000 mg/kg 2,2'-ethylenedioxydiethyl dimethacrylate: LD50 Oral rat: 10837 mg/kg

3-trimethoxysilylpropyl methacrylate: LD50 Oral rat: 23504 mg/kg; LD50 Dermal rabbit: >15000 mg/kg



Section 12. Ecological Information

Toxicity:

Ethanol: 96 hr EC50 Ulva pertusa 17.921 mg/L; 48 hr EC50 Daphnia magna- 2000 μg/L; 48 hr LC50 Crustaceans 25.5 mg/L; 96 hr LC50 Oncorhynchus mykiss >10000 μg/L Poly(oxy-1,2-ethanediyl), α , α '-[(1-methylethylidene)di-4,1-phenylene]bis[ω-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-: 96 hr LD50 Fish >100 mg/L; 48 hr EC50 Daphnia magna >100 mg/L; 72 hr Algae >100 mg/L

Persistence and degradability: Ethanol is readily biodegradable.

Bioaccumulative Potential:

Ethanol: log P_{ow} -0.35, potential for bioaccumulative is low.

 $Poly(oxy-1,2-ethanediyl),\ \alpha,\alpha'-[(1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methyl-1-oxo-2-propen-1-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene)di-4,1-phenylene]bis[\omega-[(2-methylethylidene]bis[w-[(2-methylethylidene)di-4,1-phenylene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethylidene]bis[w-[(2-methylethyli$

yl)oxy]- has a BCF of 2372, log P_{ow} 3.43 – 5.62, potential for bioaccumulative is high.

2,2'-ethylenedioxydiethyl dimethacrylate: log Pow 1.88, potential for bioaccumulative is low.

3-trimethoxysilylpropyl methacrylate: log P_{ow} 2.1, potential for bioaccumulative is low.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

Section 13. Disposal Considerations

Disposal: For unused product, dispose of in accordance with Federal and local regulations.

Container Disposal: Dispose of empty container in accordance with Federal and local regulations.

Section 14. Transport Information

	UN Number	UN Proper Shipping Name	Hazard Class(s)	Packing Group	Environmental Hazards
US DOT	UN1170	Ethanol solution	3	II	None
EU	UN1170	Ethanol solution	3	II	None
ADR/RID					
IMDG	UN1170	Ethanol solution	3	П	None
IATA/ICAO	UN1170	Ethanol solution	3	II	None

Special Precautions for User: None identified

Transport in Bulk According to Annex II MARPOL 73/78 and the IBC Code: Not applicable – product is transported only in packaged form.

Section 15. Regulatory Information

U.S. Federal Regulations:

EPA SARA 311/312 Hazard Classification: Refer to Section 2 for OSHA Hazard Classification.

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None



Protection Of Stratospheric Ozone: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements; however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

International Inventories

US EPA TSCA Inventory: All of the components of this product are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory or exempt.

Canada CEPA: All of the components of this material are listed on the DSL or exempt.

Section 16. Other Information

Effective Date: April 1, 2019 Supersedes Date: March 26, 2015

Revision Summary: All Sections - New SDS format

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of preparation, however, KERR Corporation makes no warranty with respect to the accuracy or suitability of the recommendations, and assumes no liability to any use thereof.