## **SAFETY DATA SHEETS**

## This SDS packet was issued with item:

074491577

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

074491452 074491478 074491569 074491684 074491692

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

073580008 074491627 074491635 074491643 074491650 074491668 074491676



Page 1/9

#### Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021

Reviewed on 08/26/2021

Tel.: +49 (0)800 4372522

#### 1 Identification

- · Product identifier
  - · Trade name: iBond Self Etch

- · Application of the substance / the mixture Dental bonding material
- · Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

Emergency telephone number:

Emergency CONTACT (24-Hour-Number) ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

#### 2 Hazard identification

Classification of the substance or mixture

Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour.

Skin Irritation - Category 2 H315 Causes skin irritation.

Eve Irritation - Category 2A H319 Causes serious eye irritation.

Skin Sensitizer - Category 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness.

Category 3

· Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

acetone

4-methacryloxyethyltrimellitic acid anhydride

2-hydroxyethyl methacrylate

Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)



Page 2/9

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021

Reviewed on 08/26/2021

## Trade name: iBond Self Etch

(Contd. of page 1)

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up. Classification system

NFPA ratings for USA (scale 0-4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-Ratings (Scale 0-4)



Health = 2 Fire = 3 Reactivity = 0

· Other hazards -

#### 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
  - · Description: Composition based on methacrylates

· Dangerous components:			
67-64-1	acetone	25-50% w/w *	
	Flammable Liquids - Category 2, H225 Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336		
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diyl bismethacrylate Skin Sensitizer - Category 1B, H317	10-25% w/w *	
70293-55-9	4-methacryloxyethyltrimellitic acid anhydride Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317	10-25% w/w *	
868-77-9	2-hydroxyethyl methacrylate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317	≥0.1-<1% w/w *	

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.

#### 4 First-aid measures

- · Description of first aid measures
  - · After inhalation Supply fresh air and to be sure call for a doctor.
  - · After skin contact immediately wash with water and soap and rinse thoroughly.
  - · After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

(Contd. on page 3)

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.



Page 3/9

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021

Reviewed on 08/26/2021

## Trade name: iBond Self Etch

(Contd. of page 2)

- · Information for doctor
  - · Most important symptoms and effects, both acute and delayed No further relevant information available.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
  - Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
  - · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information -

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 13 for disposal information.

See Section 8 for information on personal protection equipment.

-

#### 7 Handling and storage

- Handling
  - · Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
  - Storage
    - Requirements to be met by storerooms and receptacles: Store in a cool location.
    - Information about storage in one common storage facility: Not required.
    - · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from exposure to the light.

· Specific end use(s) No further relevant information available.

CA



Page 4/9

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021 Reviewed on 08/26/2021

Trade name: iBond Self Etch

(Contd. of page 3)

#### 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

EL STEL: 500 ppm TWA: 250 ppm EV STEL: 750 ppm TWA: 500 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

#### Personal protective equipment

· General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment: Not required.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to

avoid possible sensitization.

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

Eye protection: Safety glasses

· Body protection: Light weight protective clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
  - General Information
    - · Appearance:

Form: Fluid Yellowish

(Contd. on page 5)



Page 5/9

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021 Reviewed on 08/26/2021

Trade name: iBond Self Etch

	(Contd. of page
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	undetermined
· Boiling point/Boiling range:	55 °C (131 °F)
· Flash point:	-19 °C (-2.2 °F)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	465 °C (869 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.
· Explosion limits:	
·Lower:	2.6 Vol %
· Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	247 hPa (185.3 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Partly miscible
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
dynamic:	Not determined.
· kinematic:	Not determined.
Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available. · Possibility of hazardous reactions No dangerous reactions known
- Conditions to avoid No further relevant information available.
  Incompatible materials: No further relevant information available.
  Hazardous decomposition products: none



Page 6/9

#### Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021 Reviewed on 08/26/2021

Trade name: iBond Self Etch

(Contd. of page 5)

## 11 Toxicological information

- · Information on toxicological effects

Acute	Acute toxicity.					
· LD/	· LD/LC50 values that are relevant for classification:					
67-64-1 acetone						
Oral	LD50	5800 mg/kg (rat)				
Dermal	LD50	>15800 mg/kg (rabbit) weight of evidence				
Inhalative	LC50/4 h	76 mg/l (rat) weight of evidence				
72869-86-	72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate					
Oral	LD50	>5000 mg/kg (rat) (OECD 401)				
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)				
70293-55-	70293-55-9 4-methacryloxyethyltrimellitic acid anhydride					
Oral	LD50	>2000 mg/kg (mouse)				
Dermal	LD50	>2000 mg/kg (mouse)				
868-77-9	868-77-9 2-hydroxyethyl methacrylate					
Oral	LD50	5564 mg/kg (rat)				
Dermal	LD50	>5000 mg/kg (can)				
Duis	. Drimary irritant offoat:					

- · Primary irritant effect:
  - on the skin: No irritant effect.
- on the eye: Irritating effect.
   Sensitization: Sensitization possible through skin contact.
   Additional toxicological information: Irritant
- - · Carcinogenic categories
    - · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· Reproductive toxicity Based on available data, the classification criteria are not met.

## 12 Ecological information

· Toxicity

(Contd. on page 7)



Page 7/9

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021 Reviewed on 08/26/2021

Trade name: iBond Self Etch

(Contd. of page 6)

868-77-9 2-hydroxyethyl methacrylate

EC50/48h 380 mg/l (daphnia)

LC50/96h >100 mg/l (fish)

SDB von Evonik für 64715842 (11.04.2016)

EC50 >3000 mg/l (bacteria)

16 h

NOEC / 21d | 24.1 mg/l (daphnia) ErC50 / 72 h | 836 mg/l (algae)

NOEC / 72h | 400 mg/l (algae) (OECD 201)

#### Persistence and degradability

67-64-1 acetone

biodegradability 90.9 % /28d (nd) (OECD 301D)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

biodegradability 22 % /28d (nd) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

- · Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- · Additional ecological information:
  - General notes: Do not allow product to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
  - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

· UN-Number · DOT/TDG UN1090 · ADR, IMDG, IATA 1090

· UN proper shipping name

ADR 1090 ACETONE, solution ACETONE, solution

(Contd. on page 8)



Page 8/9

#### Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021 Reviewed on 08/26/2021

Trade name: iBond Self Etch

(Contd. of page 7)

· Transport hazard class(es)

· DOT/TDG (Transport dangerous goods):



3 Flammable liquids · Class

· Label

· ADR



· Class 3 (F1) Flammable liquids

· Label

· IMDG, IATA



3 Flammable liquids · Class

· Label

Packing group
DOT/TDG, ADR, IMDG, IATA

· Environmental hazards:

· Marine pollutant:

· Special precautions for user Warning: Flammable liquids

Hazard identification number (Kemler

code): · EMS Number: F-E, S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· UN "Model Regulation": UN1090, Acetone, solution, 3, II

#### 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

(Contd. on page 9)



Page 9/9

#### Safety Data Sheet according to HPR, Schedule 1

Printing date 08/26/2021

Reviewed on 08/26/2021

Trade name: iBond Self Etch

(Contd. of page 8)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Date of the latest revision of the safety data sheet 08/26/2021 / 3

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent Biogeographics and Toxic

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

\* Data compared to the previous version altered.