SAFETY DATA SHEETS

This SDS packet was issued with item:

075032362

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071363225

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

070482851 075032388 075032396 078915475 273011306 273013013 273016703 273019543



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-8287-4
 Version Number:
 8.00

 Issue Date:
 03/09/20
 Supercedes Date:
 02/21/20

SECTION 1: Identification

1.1. Product identifier

3MTM ScotchbondTM Universal (41258)

Product Identification Numbers

LE-F100-1014-6, LE-F100-1014-7, LE-F100-1014-9, 70-2011-3903-0 7000055178

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark |





Hazard Statements

Flammable liquid and vapor.

Causes serious eye damage.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to

extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-HYDROXYETHYL METHACRYLATE	868-77-9	15 - 25 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	15 - 25 Trade Secret *
DIMETHACRYLATE (BISGMA)		
2-PROPENOIC ACID, 2-METHYL-, REACTION	1207736-18-2	10 - 20 Trade Secret *
PRODUCTS WITH 1,10-DECANEDIOL AND		
PHOSPHOROUS OXIDE (P2O5)		

Page 2 **of** 12

ETHANOL	64-17-5	10 - 15 Trade Secret *
WATER	7732-18-5	10 - 15 Trade Secret *
2-PROPENOIC ACID, 2-METHYL-, 3-	122334-95-6	7 - 13 Trade Secret *
(TRIMETHOXYSILYL)PROPYL ESTER, REACTION		
PRODUCTS WITH VITREOUS SILICA		
COPOLYMER OF ACRYLIC AND ITACONIC ACID	25948-33-8	1 - 5 Trade Secret *
CAMPHORQUINONE	10373-78-1	< 2 Trade Secret *
DIMETHYLAMINOBENZOAT(-4)	10287-53-3	< 2 Trade Secret *
(DIMETHYLAMINO)ETHYL METHACRYLATE	2867-47-2	< 1 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

lous Decomposition of By 11 outles	
Substance	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHANOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal
				carcin.
ETHANOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid Color Yellow

Specific Physical Form:Viscous LiquidOdorCharacteristic OdorOdor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data Available

Boiling Point >= 78 °C

Flash Point 30.5 °C [Test Method:Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data AvailableDensity1 - 1.2 g/cm3

Specific Gravity 1 - 1.2 [Ref Std:WATER=1]

Solubility in Water Appreciable No Data Available Solubility- non-water Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity Not Applicable Molecular weight No Data Available **Volatile Organic Compounds** No Data Available

SECTION 10: Stability and reactivity

Page 5 **of** 12

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal	Species	No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
1	-	D 112	
2-HYDROXYETHYL METHACRYLATE 2-HYDROXYETHYL METHACRYLATE	Dermal Ingestion	Rabbit	LD50 > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE		Rat	LD50 5,564 mg/kg
(BISGMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Rat	LD50 > 11,700 mg/kg
(BISGMA)			
ETHANOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHANOL	Inhalation- Vapor (4 hours)	Rat	LC50 124.7 mg/l
ETHANOL	Ingestion	Rat	LD50 17,800 mg/kg
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Ingestion	Rat	LD50 > 2,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	Rat	LD50 > 5,000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
CAMPHORQUINONE	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
CAMPHORQUINONE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIMETHYLAMINOBENZOAT(-4)	Dermal	Rat	LD50 > 2,000 mg/kg
DIMETHYLAMINOBENZOAT(-4)	Ingestion	Rat	LD50 > 2,000 mg/kg
(DIMETHYLAMINO)ETHYL METHACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
(DIMETHYLAMINO)ETHYL METHACRYLATE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.436 mg/l
(DIMETHYLAMINO)ETHYL METHACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg

Page 7 **of** 12

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	No significant irritation
2-HYDROXYETHYL METHACRYLATE	Rabbit	Minimal irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Rabbit	No significant irritation
ETHANOL	Rabbit	No significant irritation
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	In vitro	Corrosive
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	data	
2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL	Rabbit	No significant irritation
ESTER, REACTION PRODUCTS WITH VITREOUS SILICA		
DIMETHYLAMINOBENZOAT(-4)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
	ļ .	
Overall product	In vitro	Corrosive
	data	
2-HYDROXYETHYL METHACRYLATE	Rabbit	Moderate irritant
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In vitro	No significant irritation
	data	
ETHANOL	Rabbit	Severe irritant
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	In vitro	Corrosive
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	data	
2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL	Rabbit	No significant irritation
ESTER, REACTION PRODUCTS WITH VITREOUS SILICA		
DIMETHYLAMINOBENZOAT(-4)	Rabbit	Mild irritant

Skin Sensitization

Skiii Schshization		
Name	Species	Value
2-HYDROXYETHYL METHACRYLATE	Human	Sensitizing
	and	
	animal	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Mouse	Not classified
ETHANOL	Human	Not classified
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	Professio	Sensitizing
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	nal	
	judgeme	
	nt	
2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL	Human	Not classified
ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-HYDROXYETHYL METHACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Not mutagenic
ETHANOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHANOL	In vivo	Some positive data exist, but the data are not sufficient for classification
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	In Vitro	Not mutagenic
2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	In Vitro	Not mutagenic

Page 8 **of** 12

Carcinogenicity

Name	Route	Species	Value
ETHANOL	Ingestion	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
2-PROPENOIC ACID, 2-METHYL-, 3-	Not	Mouse	Some positive data exist, but the data are not
(TRIMETHOXYSILYL)PROPYL ESTER, REACTION	Specified		sufficient for classification
PRODUCTS WITH VITREOUS SILICA			

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
ETHANOL	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ETHANOL	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHANOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHANOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHANOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
2-PROPENOIC ACID, 2- METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
COPOLYMER OF	Ingestion	nervous system	Not classified	Rat	NOAEL	

Page 9 of

ACRYLIC AND			5,000 mg/kg	
ITACONIC ACID				

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
ETHANOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHANOL	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ETHANOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHANOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
2-PROPENOIC ACID, 2- METHYL-, 3- (TRIMETHOXYSILYL)P ROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

_ 10 ...

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product—that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Page 11 **of** 12

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 29-8287-4
 Version Number:
 8.00

 Issue Date:
 03/09/20
 Supercedes Date:
 02/21/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Page 12 **of** 12