# **SAFETY DATA SHEETS**

# This SDS packet was issued with item: 075033352

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075033337 075033501

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075032602 075032628 075033345 075033360 075033378 075033386 075033394 075033519 075033527 075033535 075033543 075033550 075033568 079396238 079396241 079396244 079396247 079396250 079396253 079396263 079396266 079396269 079396272 079396275 079396278 273011066



# **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:**3M™ ESPE™ RELYX™ VENEER CEMENT REFILLS**MANUFACTURER:**3M**DIVISION:**3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

 Issue Date:
 09/27/12

 Supercedes Date:
 01/03/12

Document Group: 16-1920-4

### **Product Use:**

Intended Use:Dental ProductLimitations on Use:For use only by dental professionalsSpecific Use:Dental veneer cement

# **SECTION 2: INGREDIENTS**

### **Ingredient**

SILANE TREATED CERAMIC TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) SILANE TREATED SILICA FUNCTIONALIZED DIMETHACRYLATE POLYMER TRIPHENYLANTIMONY 
 C.A.S. No.
 % by Wt

 444758-98-9
 55 - 65

 109-16-0
 10 - 20

 1565-94-2
 10 - 20

 248596-91-0
 1 - 10

 None
 < 5</td>

 603-36-1
 < 0.2</td>

# **SECTION 3: HAZARDS IDENTIFICATION**

### **3.1 EMERGENCY OVERVIEW**

 Specific Physical Form: Paste

 Odor, Color, Grade: Characteristic odor, various shades

 General Physical Form: Solid

 Immediate health, physical, and environmental hazards: May cause allergic skin reaction.

 This document has been

 prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of

### MATERIAL SAFETY DATA SHEET 3MTM ESPETM RELYXTM VENEER CEMENT REFILLS 09/27/12

the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### **3.2 POTENTIAL HEALTH EFFECTS**

### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

# **SECTION 4: FIRST AID MEASURES**

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER CEMENT REFILLS 09/27/12

# Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air.

### **6.2.** Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### **Clean-up methods**

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Avoid skin contact. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Wash hands after handling and before eating.

### 7.2 STORAGE

Store away from areas where product may come into contact with food or pharmaceuticals. Store in a cool, dry place.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1 ENGINEERING CONTROLS

Use in an enclosed process area is recommended. Not applicable. Do not use in a confined area or areas with little or no air movement.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact. The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid skin contact. See Section 7.1 for additional information on skin protection.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

### 8.2.4 Prevention of Swallowing

### MATERIAL SAFETY DATA SHEET 3MTM ESPETM RELYXTM VENEER CEMENT REFILLS 09/27/12

Not applicable. Do not ingest. Wash hands after handling and before eating.

### 8.3 EXPOSURE GUIDELINES

None Established

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Odor, Color, Grade: General Physical Form: Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL) Boiling Point Density Vapor Density

**Vapor Pressure** 

Specific Gravity pH Melting point

Solubility in Water Evaporation rate Volatile Organic Compounds Kow - Oct/Water partition coef Percent volatile VOC Less H2O & Exempt Solvents Viscosity Paste Characteristic odor, various shades Solid *Not Applicable* Not Applicable *Not Applicable Not Applicable Not Applicable* 1.102 g/cm3 *Not Applicable* 

Not Applicable

1.102 [*Ref Std:* WATER=1] *No Data Available No Data Available* 

Negligible Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid None known

**10.2 Materials to avoid** None known

Hazardous Polymerization: Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER CEMENT REFILLS 09/27/12

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

# ECOTOXICOLOGICAL INFORMATION

Not determined.

# CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of waste product in a sanitary landfill. For quantities <100 lbs. (50kg): dispose of waste product in a sanitary landfill. For larger quantities: incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

### EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

### **ID** Number(s):

LE-F100-0702-2, 70-2010-3183-1, 70-2010-3184-9, 70-2010-3185-6, 70-2010-3186-4, 70-2010-3187-2, 70-2010-3188-0, 70-2010-3236-7, 70-2010-3237-5, 70-2010-3238-3, 70-2010-3239-1, 70-2010-3240-9, 70-2010-3241-7, 70-2010-8790-8

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: REGULATORY INFORMATION**

### **US FEDERAL REGULATIONS**

Contact 3M for more information.

### **311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER CEMENT REFILLS 09/27/12

Contact 3M for more information.

### **INTERNATIONAL REGULATIONS**

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:** 

Section 7: Storage information was modified.

Section 8: Engineering controls information was modified.

Section 8: Prevention of swallowing information was modified.

Section 2: Ingredient table was modified.

Section 6: Methods for cleaning up information was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

### 3M USA MSDSs are available at www.3M.com



# **Safety Data Sheet**

### Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-1920-4	Version Number:	12.05
Issue Date:	11/16/22	Supercedes Date:	11/02/22

### **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>TM</sup> RelyX<sup>TM</sup> Veneer Cement Refills

### **Product Identification Numbers**

LE-F100-0702-2, 70-2010-3183-1, 70-2010-3184-9, 70-2010-3185-6, 70-2010-3186-4, 70-2010-3187-2, 70-2010-3188-0, 70-2010-3236-7, 70-2010-3237-5, 70-2010-3238-3, 70-2010-3239-1, 70-2010-3240-9, 70-2010-8790-8, 70-2014-0138-0, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3236-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-3206-7, 70-2010-7, 70-2010-7, 70-2010-7, 70-2010-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 70-2000-7, 7 2014-0139-8, 70-2014-0140-6, 70-2014-0141-4, 70-2014-0142-2, 70-2014-0143-0, 70-2014-2065-3, 70-2014-2066-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2065-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2014-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70-2005-1, 70 2014-2067-9, 70-2014-2068-7, 70-2014-2069-5 7000003150, 7000003151, 7000003152, 7000003153, 7000128792, 7000128793, 7000054259, 7000054260, 7000054261, 7000054262, 7000054263, 7010388159, 7010343319, 7010388160, 7010304350, 7010388161, 7010343320

### 1.2. Recommended use and restrictions on use

**Recommended use** Dental Product, Veneer cement **Restrictions on use** 

For use only by dental professionals

1.3. Supplier's details	
MANUFACTURER:	3M
<b>DIVISION:</b>	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B. Skin Sensitizer: Category 1. Reproductive Toxicity: Category 1B.

**2.2. Label elements Signal word** Danger

Symbols Exclamation mark | Health Hazard |

### Pictograms



Hazard Statements Causes eye irritation. May cause an allergic skin reaction. May damage fertility or the unborn child.

### **Precautionary Statements**

### **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Silane Treated Ceramic	444758-98-9	55 - 65 Trade Secret *
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	1565-94-2	10 - 20 Trade Secret *
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	10 - 20 Trade Secret *
Silane Treated Silica	248596-91-0	1 - 10 Trade Secret *
Reacted Polycaprolactone Polymer	None	1 - 10 Trade Secret *
Titanium Dioxide	13463-67-7	< 1 Trade Secret *
Diphenyliodonium Hexafluorophosphate	58109-40-3	< 0.5 Trade Secret *
N,N-DIMETHYLBENZOCAINE	10287-53-3	< 0.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	
Carbon monoxide	
Carbon dioxide	

<u>Condition</u> During Combustion During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human
				carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Safety Glasses with side shields

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

### **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Solid
Color	White
Specific Physical Form:	Paste
Odor	Characteristic Odor
Odor threshold	No Data Available
рН	No Data Available
Melting point	No Data Available
Boiling Point	Not Applicable
Flash Point	No flash point
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Density	1.102 g/cm3
Specific Gravity	1.102 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	Not Applicable
Molecular weight	No Data Available
Volatile Organic Compounds	Not Applicable
Percent volatile	Not Applicable
VOC Less H2O & Exempt Solvents	Not Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

# **10.2.** Chemical stability Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

# **10.4.** Conditions to avoid None known.

# **10.5. Incompatible materials** None known.

### 10.6. Hazardous decomposition products

<u>Substance</u> None known. **Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

### Additional Health Effects:

### **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### **Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg

Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Silane Treated Ceramic	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Silane Treated Ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Rat	LD50 10,837 mg/kg
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	Rat	LD50 > 11,700 mg/kg
Silane Treated Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Reacted Polycaprolactone Polymer	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
Reacted Polycaprolactone Polymer	Ingestion	similar compoun ds	LD50 estimated to be 2,000 - 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
N,N-DIMETHYLBENZOCAINE	Dermal	Rat	LD50 > 2,000 mg/kg
N,N-DIMETHYLBENZOCAINE	Ingestion	Rat	LD50 > 2,000 mg/kg
Diphenyliodonium Hexafluorophosphate	Ingestion	Rat	LD50 32 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Silane Treated Ceramic	similar	No significant irritation
	compoun ds	
Triethylene Glycol Dimethacrylate (TEGDMA)	Guinea	Mild irritant
	pig	
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Rabbit	No significant irritation
Silane Treated Silica	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Titanium Dioxide	Rabbit	No significant irritation
N,N-DIMETHYLBENZOCAINE	Rabbit	No significant irritation
Diphenyliodonium Hexafluorophosphate	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Silane Treated Ceramic	similar compoun ds	Mild irritant
Triethylene Glycol Dimethacrylate (TEGDMA)	Professio nal judgeme nt	Moderate irritant
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	In vitro data	No significant irritation
Silane Treated Silica	Professio nal	No significant irritation

	judgeme	
	nt	
Titanium Dioxide	Rabbit	No significant irritation
N,N-DIMETHYLBENZOCAINE	Rabbit	No significant irritation
Diphenyliodonium Hexafluorophosphate	Rabbit	Mild irritant

### **Skin Sensitization**

Name	Species	Value
Silane Treated Ceramic	similar	Not classified
	compoun	
	ds	
Triethylene Glycol Dimethacrylate (TEGDMA)	Human	Sensitizing
	and	
	animal	
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Mouse	Not classified
Titanium Dioxide	Human	Not classified
	and	
	animal	
N,N-DIMETHYLBENZOCAINE		Not classified

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
N,N-DIMETHYLBENZOCAINE	In vivo	Not mutagenic
N,N-DIMETHYLBENZOCAINE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diphenyliodonium Hexafluorophosphate	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Silane Treated Ceramic	Inhalation	similar	Some positive data exist, but the data are not
		compoun	sufficient for classification
		ds	
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Mouse	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Inhalation	Rat	Carcinogenic

### **Reproductive Toxicity**

### **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
N,N-DIMETHYLBENZOCAINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation

N,N-DIMETHYLBENZOCAINE	Ingestion	Not classified for development	Rat	NOAEL 50	premating
				mg/kg/day	into lactation
N,N-DIMETHYLBENZOCAINE	Ingestion	Toxic to male reproduction	Rat	NOAEL 50 mg/kg/day	53 days

### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Diphenyliodonium Hexafluorophosphate	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Silane Treated Ceramic	Inhalation	pulmonary fibrosis	Not classified	similar compoun ds	NOAEL Not available	
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	kidney and/or bladder   blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	endocrine system   hematopoietic system   liver   heart   skin   gastrointestinal tract   bone, teeth, nails, and/or hair   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
N,N- DIMETHYLBENZOCAIN E	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 74 mg/kg/day	28 days
N,N- DIMETHYLBENZOCAIN E	Ingestion	liver   heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

### EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### **15.1. US Federal Regulations**

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

Physical Hazards	
Not applicable	
Health Hazards	
Reproductive toxicity	
Respiratory or Skin Sensitization	
Serious eye damage or eye irritation	

### **Additional TSCA Information**

<b>Components</b>	CAS No	Additional Information
Silane Treated Silica	248596-91-0	Allowed use(s): Coating additive.

### **15.2. State Regulations**

Contact 3M for more information.

### **15.3.** Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

### This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: Other information**

### **NFPA Hazard Classification**

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	16-1920-4	Version Number:	12.05
Issue Date:	11/16/22	Supercedes Date:	11/02/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

### 3M USA SDSs are available at www.3M.com



Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

SECTION: 1. Product an	d company ide	entification
1.1. Product identifier		
Product form	:	Substance
Trade name	:	Carbon Monoxide
Chemical name	:	Carbon monoxide
CAS-No.	:	630-08-0
Formula	:	CO
1.2. Relevant identified u	ses of the substa	nce or mixture and uses advised against
Use of the substance/mixture	:	Industrial use; Use as directed.
1.3. Details of the supplie	er of the safety da	ta sheet
		Linde Inc. 10 Riverview Drive Danbury, CT 06810-6268, USA www.lindeus.com
		Linde Inc. 1-844-44LINDE (1-844-445-4633)
1.4. Emergency telephon	e number	
Emergency number	:	Onsite Emergency: 1-800-645-4633
		CHEMTREC, 24 hr/day 7 days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887 (collect calls accepted, Contract 17729)
<b>SECTION 2: Hazard iden</b>	tification	
2.1. Classification of the	substance or mix	ture
GHS-US classification		
Flam. Gas 1HiPress. Gas (Comp.)HiAcute Tox. 3 (Inhalation:gas)HiRepr. 1AHi	220 280 331 360 372	
2.2. Label elements		
GHS US labelling		
Hazard pictograms (GHS US)	:	CHS02 CHS04 CHS06 CHS08
Signal word (GHS US)	:	Danger
Hazard statements (GHS US)		H220 - EXTREMELY FLAMMABLE GAS H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED H331 - TOXIC IF INHALED H360 - MAY DAMAGE FERTILITY OR THE UNBORN CHILD H372 - CAUSES DAMAGE TO ORGANS (CENTRAL NERVOUS SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR CGA-HG10 - ASPHYXIATING EVEN WITH ADEQUATE OXYGEN.
Precautionary statements (GHS	US) :	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keen surge from best, bet surfaces, analysis, onen flomes and other insisten sources. No



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 01/07/2022 Supersedes: 01/29/2021 Version: 2.1

	<ul> <li>P264 - Wash exposed skin thoroughly after handling</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271+P403 - Use and store only outdoors or in a well-ventilated place.</li> <li>P280 - Wear protective clothing, protective gloves, eye protection, face protection.</li> <li>P377 - LEAKING GAS FIRE: Do not extinguish, unless leak can be stopped safely.</li> <li>P381 - Eliminate all ignition sources if safe to do so.</li> <li>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P311 - Call a poison center or doctor.</li> <li>P308+P313 - If exposed or concerned: Get medical advice/attention.</li> <li>P405 - Store locked up.</li> <li>P501 - Dispose of contents/container in accordance with container Supplier/owner instructions</li> <li>CGA-PG05 - Use a back flow preventive device in the piping.</li> <li>CGA-PG12 - Do not open valve until connected to equipment prepared for use.</li> <li>CGA-PG06 - Close valve after each use and when empty.</li> <li>CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).</li> </ul>
2.3. Other hazards	
Other hazards which do not result in classification	: Chemical asphyxiant. Exposure to low concentrations for extended periods may result in dizziness or unconsciousness, and may lead to death.

2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Name	Product identifier	%
Carbon monoxide (Main constituent)	(CAS-No.) 630-08-0	100

### 3.2. Mixtures

Not applicable

<b>SECTION 4: First aid measure</b>	es de la companya de
4.1. Description of first aid meas	sures
First-aid measures after inhalation	<ul> <li>Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.</li> </ul>
First-aid measures after skin contact	: Wash with plenty of soap and water. IF SKIN IRRITATION OCCURS: Get medical advice/attention.
First-aid measures after eye contact	Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately. If eye irritation persists: Get immediate medical attention.
First-aid measures after ingestion	: Not expected to be a primary route of exposure.
4.2. Most important symptoms a	and effects, both acute and delayed
Symptoms/effects	: Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Prolonged exposure to low concentrations of carbon monoxide can kill.
4.3. Indication of any immediate	medical attention and special treatment needed
	No additional information available

SECTION	N 5: Firefighting measures	
5.1. E	extinguishing media	
Suitable ext	tinguishing media	: Carbon dioxide, Dry chemical, Water spray or fog.

EN (English)



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

5.2.	Special hazards arising from the su	ibstance or mixture
Fire haz	ard	: EXTREMELY FLAMMABLE GAS. Carbon monoxide cannot be detected by odor. May form explosive mixtures with air. Toxic, flammable gas may spread. Before entering area, especially a confined area, check atmosphere with an appropriate gas-specific device. Reduce gas with fog or fine water spray. Shut off source of gas flow if safe to do so. Ventilate area or move container to a well-ventilated area.
Explosio	on hazard	: EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.
Reactivi	ty	: No reactivity hazard other than the effects described in sub-sections below.
5.3.	Advice for firefighters	
Firefight	ing instructions	: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
Protecti	on during firefighting	: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.
Special	protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Specific	methods	If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.
Other in	formation	: Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by TC.).
SECT	ON 6: Accidental release mea	sures
6.1.	Personal precautions, protective ed	quipment and emergency procedures
General	measures	Cannot be detected by odor. <b>Danger: Flammable, liquefied gas.</b> FORMS EXPLOSIVE MIXTURES WITH AIR. Immediately evacuate all personnel from danger area. Use self- contained breathing apparatus where needed. Remove all sources of ignition if safe to do so. Reduce vapors with fog or fine water spray, taking care not to spread liquid with water. Shut off flow if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable vapors may spread from leak and could explode if reignited by sparks or flames. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with an appropriate device.
6.1.1.	For non-emergency personnel	
		No additional information available
6.1.2.	For emergency responders	
		No additional information available
6.2.	Environmental precautions	
		Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with container supplier/owner instructions.
6.3.	Methods and material for containm	ent and cleaning up
		No additional information available
6.4.	Reference to other sections	
		See also sections 8 and 13.



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.
	Use in a closed system.
	Avoid using pure nickel. Corrosion of pure nickel in carbon monoxide atmospheres exceeds 50 mil/yr (1.27 mm/yr) at room temperature.
	Wear leather safety gloves and safety shoes when handling cylinders. Protect containers from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.
7.2. Conditions for safe storage, including	g any incompatibilities
Storage conditions	: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g, NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.
	<b>OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:</b> When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### 7.3. Specific end use(s)

None.

### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters		
Carbon monoxide (630-08-0)		
ACGIH	ACGIH OEL TWA [ppm]	25 ppm
USA OSHA	OSHA PEL TWA [1]	55 mg/m³
USA OSHA	OSHA PEL TWA [2]	50 ppm
USA IDLH	IDLH [ppm]	1200 ppm
8.2. Exposure controls		
Appropriate engineering controls		system with sufficient flow velocity to maintain an sbreathing zone. Mechanical/General measures: Use in a
Hand protection	: Wear working gloves when handling	gas containers.
Eye protection	: Wear safety glasses with side shields	S.

EN (English)



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

Skin and body protection	Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible.
Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets or exceeds the requirements of the appropriate Health and Safety Regulations. Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere.
Other information	: Consider the use of flame resistant anti-static safety clothing.

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties	
Physical state	: Gas
Appearance	: Colorless, odorless gas.
Molecular mass	: 28 g/mol
Colour	: Colourless
Odour	: Odourless.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: -205.1 °C
Freezing point	: No data available
Boiling point	: -191.5 °C
Flash point	: Not applicable.
Critical temperature	: -139.8 °C
Auto-ignition temperature	: 605 °C
Decomposition temperature	: 400 °C
Flammability (solid, gas)	: 12.5 – 74 vol %
Vapour pressure	: Not applicable.
Critical pressure	: 3499 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.2501 kg/m³ (at 0 °C)
Relative gas density	: 1
Solubility	: Water: 41 g/l (at 20 °C)
Partition coefficient n-octanol/water (Log Pow)	: 1.78
Partition coefficient n-octanol/water (Log Kow)	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Explosive limits	: No data available
9.2. Other information	
Gas group	: Compressed gas
Additional information	: None.
SECTION 10: Stability and reactivity	

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

ossibility of hazardous reactions	Stable under normal conditions.
ossibility of hazardous reactions	
	May occur. Can form explosive mixture with air. Oxidizing agents.
onditions to avoid	
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
compatible materials	
	Oxidizing agents, Oxygen, Flammables, Metal oxides, halogenated fluorides, metals in the presence of moisture and/or sulfur compounds.
azardous decomposition products	
	Carbon monoxide will decompose above 752°F (400°C) to form carbon dioxide and carbon.

### **SECTION 11: Toxicological information**

11.1. Information on toxicological effects		
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified : TOXIC IF INHALED.	

Carbon monoxide ( \f )630-08-0	
LC50 Inhalation - Rat [ppm]	1880 ppm/4h
ATE US (gases)	1880 ppmv/4h
Skin corrosion/irritation :	Not classified
	pH: Not applicable.
Serious eye damage/irritation :	Not classified
	pH: Not applicable.
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity	: MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
STOT-single exposure	: Not classified
STOT-repeated exposure	: CAUSES DAMAGE TO ORGANS (CENTRAL NERVOUS SYSTEM) THROUGH PROLONGED OR REPEATED EXPOSURE.
Aspiration hazard	: Not classified

### **SECTION 12: Ecological information**

12.1.ToxicityEcology - general

: Classification criteria are not met. No ecological damage caused by this product.

# 12.2. Persistence and degradability Carbon monoxide (630-08-0) Persistence and degradability Will not undergo hydrolysis. Not readily biodegradable. Not applicable for inorganic products. 12.3. Bioaccumulative potential Carbon monoxide (630-08-0) Partition coefficient n-octanol/water (Log Pow) 1.78 Partition coefficient n-octanol/water (Log Kow) Not applicable. Not applicable.



Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/07/2022 Supersedes: 01/29/2021 Version: 2.1

Carbon monoxide (630-08-0)	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). See section 9.
12.4. Mobility in soil	
Carbon monoxide (630-08-0)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
12.5. Other adverse effects	
Effect on the ozone layer	: None.
Global warming potential [CO2=1]	: 1.9

SECTION 13: Disposal consideration	
13.1. Waste treatment methods	15
Product/Packaging disposal recommendations	: Do not attempt to dispose of residual or unused quantities. Return container to supplier.
SECTION 14: Transport information	
In accordance with DOT	
Transport document description (DOT)	: UN1016 Carbon monoxide, compressed, 2.3
UN-No.(DOT)	: UN1016
Proper Shipping Name (DOT)	: Carbon monoxide, compressed
Class (DOT)	: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
Hazard labels (DOT)	: Poison Gas 2.3 - Poison gas 2.1 - Flammable gas
	2 2 2
DOT Special Provisions (49 CFR 172.102)	: 4 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone D (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.
Additional information	
Emergency Response Guide (ERG) Number	: 119 (UN1016);168 (NA9202)
Other information	: No supplementary information available.
Special transport precautions	<ul> <li>Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:</li> <li>Ensure there is adequate ventilation Ensure that containers are firmly secured Ensure valve is closed and not leaking Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> </ul>
Transport by sea	
UN-No. (IMDG)	: 1016
Proper Shipping Name (IMDG)	: CARBON MONOXIDE, COMPRESSED
Class (IMDG)	: 2 - Gases
Division (IMDG)	: 2.3 - Toxic gases
MFAG-No	: 119
Air transport	
UN-No. (IATA)	: 1016
Proper Shipping Name (IATA)	: Carbon monoxide, compressed
Class (IATA)	: 2 - Gases
EN (English)	SDS ID: P-4576 7/5



# Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

**Civil Aeronautics Law** 

: Gases under pressure/Gases toxic under pressure(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

### 15.1. US Federal regulations

Carbon monoxide (630-08-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

### 15.2. International regulations

### CANADA

### Carbon monoxide (630-08-0)

Listed on the Canadian DSL (Domestic Substances List)

### **EU-Regulations**

### Carbon monoxide (630-08-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### 15.2.2. National regulations

### Carbon monoxide (630-08-0)

2 LIC State regulati

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

- Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
- Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
- Listed on the Japanese ISHL (Industrial Safety and Health Law)
- Listed on KECL/KECI (Korean Existing Chemicals Inventory)
- Listed on NZIOC (New Zealand Inventory of Chemicals)
- Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

- Listed on INSQ (Mexican National Inventory of Chemical Substances)
- Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations		
Carbon monoxide(630-08-0)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	Yes	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) List	

This product can expose you to Carbon monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Safety Data Sheet P-4576

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/07/2022Supersedes: 01/29/2021Version: 2.1

SECTION 16: Other information	
Other information	: Prior to using any plastics, confirm their compatibility with this chemical.
	When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.
	Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.
	The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.
	Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-844-44-Linde (1-844-445-4633); Address: Linde Call Center, Linde Inc, P.O. Box 44, Tonawanda, NY 14151-0044).
	Linde and the Linde wordmark are trademarks or registered trademarks of Linde Inc. or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.
Revision date	Copyright © 2022, Linde Inc. : 01/07/2022
NFPA health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA instability	<ul> <li>: 0 - Material that in themselves are normally stable, even under fire conditions.</li> </ul>

### SDS US (GHS HazCom 2012) - Linde 2022

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.