# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

075033386

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075033337 075033501

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075032602 075033345 075033352 075033360 075033378 075033394 075033519 075033527 075033535 075033543 075033550 075033568 079396238 079396241 079396244 079396247 079396250 079396253 079396263 079396266 079396269 079396272 079396275 079396278 273011066



# **Material Safety Data Sheet**

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER TRY-IN PASTE

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 06/03/09 **Supercedes Date:** 01/20/09

**Document Group:** 16-1922-0

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals

Specific Use: Dental veneer try-in paste

# **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYETHYLENE GLYCOL	25322-68-3	80 - 95
CERAMIC POWDER	66402-68-4	5 - 15
TITANIUM DIOXIDE	13463-67-7	< 2

# **SECTION 3: HAZARDS IDENTIFICATION**

#### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Characteristic odor, various shades

General Physical Form: Solid

Immediate health, physical, and environmental hazards: No immediate health, physical or environmental hazards are anticipated. See Section 3.2 for other hazards that can be associated with the ingredients in this product in a non-emergency situation. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this

#### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER TRY-IN PASTE 06/03/09

document may vary depending on the potential for exposure.

#### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNo Data AvailableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Avoid prolonged or repeated skin contact. Wash hands after handling and before eating.

### 7.2 STORAGE

Store in a cool place.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable.

# **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields.

#### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

# 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

# 8.2.4 Prevention of Swallowing

Do not ingest. Wash hands after handling and before eating.

#### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<b>Type</b>	<u>Limit</u>	Additional Information
POLYETHYLENE GLYCOLS	AIHA	TWA, as aerosol	10 mg/m3	
TITANIUM DIOXIDE	ACGIH	TWA	10 mg/m3	Table A4
TITANIUM DIOXIDE	CMRG	TWA, as respirable	5 mg/m3	
		dust		
TITANIUM DIOXIDE	OSHA	TWA, Vacated, as	10 mg/m3	
		dust		
TITANIUM DIOXIDE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
THE CITY OF THE COURT OF THE CO				

VAC Vacated PEL:Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Paste

Odor, Color, Grade: Characteristic odor, various shades

General Physical Form: Solid

Autoignition temperatureNo Data AvailableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableBoiling pointNot ApplicableDensity1.3 g/cm3Vapor DensityNot Applicable

Vapor Pressure Not Applicable

Specific Gravity 1.3 [Ref Std: WATER=1]

pH Not ApplicableMelting point No Data Available

Solubility in Water Appreciable

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: None known

Page 4 of 7

#### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER TRY-IN PASTE 06/03/09

Hazardous Polymerization: Hazardous polymerization will not occur.

# **Hazardous Decomposition or By-Products**

<u>Substance</u> <u>Condition</u>

Carbon monoxide During Combustion
Carbon dioxide During Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Reclaim if feasible. For quantities <100 lbs. (50kg): dispose of waste product in a sanitary landfill. For larger quantities: incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

#### **ID** Number(s):

LE-F100-0702-1, 70-2010-3189-8, 70-2010-3190-6, 70-2010-3191-4, 70-2010-3192-2, 70-2010-3193-0, 70-2010-3194-8, 70-2010-319

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

#### US FEDERAL REGULATIONS

#### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER TRY-IN PASTE 06/03/09

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

#### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes:

Section 1: Product name was modified. Page Heading: Product name was modified.

Section 14: ID Number(s) Template 1 was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Page 7 of 7



# **Safety Data Sheet**

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 16-1922-0
 Version Number:
 7.00

 Issue Date:
 02/25/16
 Supercedes Date:
 12/05/14

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> ESPE<sup>TM</sup> RELYX<sup>TM</sup> VENEER TRY-IN PASTE

#### **Product Identification Numbers**

LE-F100-0702-1, 70-2010-3189-8, 70-2010-3190-6, 70-2010-3191-4, 70-2010-3192-2, 70-2010-3193-0, 70-2010-3194-8, 70-2010-3194

#### 1.2. Recommended use and restrictions on use

### Recommended use

Dental Product, Veneer try-in paste

#### **Restrictions on use**

For use only by dental professionals

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Oral Care Solutions Division

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

#### Signal word

Not applicable.

# **Symbols**

Not applicable.

Page 1 of 9

#### **Pictograms**

Not applicable.

#### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYETHYLENE GLYCOL	25322-68-3	80 - 95 Trade Secret *
CERAMIC POWDER	66402-68-4	5 - 15 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	< 2 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide

### **Condition**

During Combustion
During Combustion

Page 2 of 9

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

tor the component.				
Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
TITANIUM DIOXIDE	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human
				carcin
TITANIUM DIOXIDE	13463-67-7	CMRG	TWA(as respirable dust):5	
			mg/m3	
TITANIUM DIOXIDE	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
POLYETHYLENE GLYCOL	25322-68-3	AIHA	TWA(as particulate):10	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

# 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Page 3 of 9

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**General Physical Form:** Solid **Specific Physical Form:** Paste

Odor, Color, Grade: Characteristic odor, various shades

**Odor threshold** No Data Available Not Applicable pН No Data Available **Melting point Boiling Point** Not Applicable **Flash Point** Not Applicable **Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) Vapor Pressure Not Applicable **Vapor Density** Not Applicable

Density 1.3 g/cm<sup>3</sup>

Specific Gravity 1.3 [Ref Std: WATER=1]

Solubility in Water Appreciable Solubility- non-water No Data Available Partition coefficient: n-octanol/ water Not Applicable No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** Viscosity No Data Available Molecular weight No Data Available Percent volatile Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

#### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured

#### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

product. Once properly mixed and/or cured, the product is safe for its intended use.

#### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Additional Health Effects:**

#### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value

Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
POLYETHYLENE GLYCOL	Dermal	Rabbit	LD50 > 20,000 mg/kg
POLYETHYLENE GLYCOL	Ingestion	Rat	LD50 32,770 mg/kg
CERAMIC POWDER	Dermal		LD50 estimated to be > 5,000 mg/kg
CERAMIC POWDER	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		
	(4 hours)		
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
POLYETHYLENE GLYCOL	Rabbit	Minimal irritation
CERAMIC POWDER	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
POLYETHYLENE GLYCOL	Rabbit	Mild irritant
CERAMIC POWDER	Rabbit	Mild irritant
TITANIUM DIOXIDE	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
POLYETHYLENE GLYCOL	Guinea	Not sensitizing
	pig	
TITANIUM DIOXIDE	Human	Not sensitizing
	and	
	animal	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Germ Cen Mutagementy		
Name	Route	Value
POLYETHYLENE GLYCOL	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL	In vivo	Not mutagenic
CERAMIC POWDER	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
POLYETHYLENE GLYCOL	Ingestion	Rat	Not carcinogenic
CERAMIC POWDER	Inhalation	Multiple animal	Some positive data exist, but the data are not sufficient for classification
		species	sufficient for classification
TITANIUM DIOXIDE	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic

# Reproductive Toxicity

# Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
POLYETHYLENE GLYCOL	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
POLYETHYLENE GLYCOL	Ingestion	Not toxic to male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
POLYETHYLENE GLYCOL	Not Specified	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		NOEL N/A	
POLYETHYLENE GLYCOL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 562 mg/animal/da y	during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POLYETHYLENE GLYCOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POLYETHYLENE GLYCOL	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
POLYETHYLENE GLYCOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,640 mg/kg/day	13 weeks
POLYETHYLENE GLYCOL	Ingestion	heart   endocrine system   hematopoietic system   liver   nervous system	All data are negative	Rat	NOAEL 5,640 mg/kg/day	13 weeks
CERAMIC POWDER	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	
CERAMIC POWDER	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

# **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

# 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

#### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

Page 8 of 9

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 16-1922-0
 Version Number:
 7.00

 Issue Date:
 02/25/16
 Supercedes Date:
 12/05/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9