SAFETY DATA SHEETS

This SDS packet was issued with item:

075033410

N/A



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 30-4499-7
 Version Number:
 1.03

 Issue Date:
 03/06/20
 Supercedes Date:
 02/14/18

Product identifier

3MTM ESPETM 8716TK RelyXTM Veneer Cement Trial Kit with Universal Etchant/Adhesive

ID Number(s):

70-2010-8801-3, 70-2014-1212-2

7000129005, 7100156387

Recommended use

Dental Product, Dental veneer kit

Restrictions on use

For use by dental professionals only.

Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

 $16\hbox{-}1922\hbox{-}0, 29\hbox{-}8286\hbox{-}6, 16\hbox{-}1920\hbox{-}4, 29\hbox{-}8287\hbox{-}4$

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may

have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 16-1920-4
 Version Number:
 12.03

 Issue Date:
 02/17/20
 Supercedes Date:
 05/18/18

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM RELYXTM VENEER CEMENT REFILLS

Product Identification Numbers

 $\begin{array}{c} \text{LE-F100-0702-2}, \, 70\text{-}2010\text{-}3183\text{-}1, \, 70\text{-}2010\text{-}3184\text{-}9, \, 70\text{-}2010\text{-}3185\text{-}6, \, 70\text{-}2010\text{-}3186\text{-}4, \, 70\text{-}2010\text{-}3187\text{-}2, \, 70\text{-}2010\text{-}3188\text{-}0, \, \\ 70\text{-}2010\text{-}3236\text{-}7, \, 70\text{-}2010\text{-}3237\text{-}5, \, 70\text{-}2010\text{-}3238\text{-}3, \, 70\text{-}2010\text{-}3239\text{-}1, \, 70\text{-}2010\text{-}3240\text{-}9, \, 70\text{-}2010\text{-}8790\text{-}8, \, 70\text{-}2014\text{-}0138\text{-}0, \, 70\text{-}2014\text{-}0139\text{-}8, \, 70\text{-}2014\text{-}0140\text{-}6, \, 70\text{-}2014\text{-}0141\text{-}4, \, 70\text{-}2014\text{-}0142\text{-}2, \, 70\text{-}2014\text{-}0143\text{-}0} \\ 7000003150, \, 7000003151, \, 7000003152, \, 7000003153, \, 7000128792, \, 7000128793, \, 7000054259, \, 7000054260, \, 7000054261, \, 7000054262, \, 7000054263, \, 7010388159, \, 7010343319, \, 7010388160, \, 7010304350, \, 7010388161, \, 7010343320 \\ \end{array}$

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Veneer cement

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark

Pictograms



Hazard Statements

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------------------------------------|-------------|------------------------|
| Silane Treated Ceramic | 444758-98-9 | 55 - 65 Trade Secret * |
| Triethylene Glycol Dimethacrylate (TEGDMA) | 109-16-0 | 10 - 20 Trade Secret * |
| Bisphenol A Diglycidyl Ether Dimethacrylate | 1565-94-2 | 10 - 20 Trade Secret * |
| (BISGMA) | | |
| Silane Treated Silica | 248596-91-0 | 1 - 10 Trade Secret * |
| Reacted Polycaprolactone Polymer | None | 1 - 10 Trade Secret * |
| Titanium Dioxide | 13463-67-7 | < 1 Trade Secret * |
| Diphenyliodonium Hexafluorophosphate | 58109-40-3 | < 0.5 Trade Secret * |
| Triphenylantimony | 603-36-1 | < 0.5 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------|------------|--------|-----------------------------|----------------------------|
| Titanium Dioxide | 13463-67-7 | ACGIH | TWA:10 mg/m3 | A4: Not class. as human |
| | | | | carcin |
| Titanium Dioxide | 13463-67-7 | OSHA | TWA(as total dust):15 mg/m3 | |
| ANTIMONY COMPOUNDS | 603-36-1 | ACGIH | TWA(as Sb):0.5 mg/m3 | |
| ANTIMONY COMPOUNDS | 603-36-1 | OSHA | TWA(as Sb):0.5 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateSolidColorMulticolor

Specific Physical Form: Paste

Odor Characteristic Odor Odor threshold No Data Available Hq No Data Available **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** Not Applicable Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) **Vapor Pressure** Not Applicable Vapor Density Not Applicable 1.102 g/cm3 **Density**

Specific Gravity 1.102 [Ref Std:WATER=1]

Solubility in Water Negligible

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water Not Applicable **Autoignition temperature** Not Applicable **Decomposition temperature** No Data Available Viscosity Not Applicable No Data Available Molecular weight **Volatile Organic Compounds** Not Applicable Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

| <u>Ingredient</u> | CAS No. | Class Description | Regulation |
|-------------------|------------|-------------------------------|---------------------------------------------|
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------------------------------|-----------|-----------|------------------------------------------------------|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Silane Treated Ceramic | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Silane Treated Ceramic | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Dermal | Professio | LD50 estimated to be > 5,000 mg/kg |
| | | nal | |

Page 6 **of** 11

| | | judgeme nt | |
|------------------------------------------------------|---------------------------------------|-----------------------------------|------------------------------------------|
| Triethylene Glycol Dimethacrylate (TEGDMA) | Ingestion | Rat | LD50 10,837 mg/kg |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Ingestion | Rat | LD50 > 11,700 mg/kg |
| Silane Treated Silica | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Silane Treated Silica | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Reacted Polycaprolactone Polymer | Dermal | Professio nal judgeme nt | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Reacted Polycaprolactone Polymer | Ingestion | similar compoun ds | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Diphenyliodonium Hexafluorophosphate | Ingestion | Rat | LD50 32 mg/kg |
| Triphenylantimony | Inhalation- Dust/Mist | | LC50 estimated to be 1 - 5 mg/l |
| Triphenylantimony | Dermal | Rat | LD50 > 2,000 mg/kg |
| Triphenylantimony | Ingestion | Rat | LD50 82.5 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------------------------------------|-----------|---------------------------|
| | | |
| Silane Treated Ceramic | similar | No significant irritation |
| | compoun | |
| | ds | |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Guinea | Mild irritant |
| | pig | |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Rabbit | No significant irritation |
| Silane Treated Silica | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| Titanium Dioxide | Rabbit | No significant irritation |
| Diphenyliodonium Hexafluorophosphate | Rabbit | No significant irritation |
| Triphenylantimony | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value | |
|------------------------------------------------------|-----------|---------------------------|--|
| | | | |
| Silane Treated Ceramic | similar | Mild irritant | |
| | compoun | | |
| | ds | | |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Professio | Moderate irritant | |
| | nal | | |
| | judgeme | | |
| | nt | | |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | In vitro | No significant irritation | |
| | data | | |
| Silane Treated Silica | Professio | No significant irritation | |
| | nal | | |
| | judgeme | | |
| | nt | | |
| Titanium Dioxide | Rabbit | No significant irritation | |
| Diphenyliodonium Hexafluorophosphate | Rabbit | Mild irritant | |

Page 7 of

| 3MTM ESPETM RELVXTM | VENEER CEMENT REFILLS | 02/17/20 |
|---------------------|-----------------------|----------|
| | | |

| - | Triphenylantimony | Rabbit | Mild irritant |
|---|-------------------|--------|---------------|

Skin Sensitization

| Name | Species | Value |
|------------------------------------------------------|---------|----------------|
| Silane Treated Ceramic | similar | Not classified |
| | compoun | |
| | ds | |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Human | Sensitizing |
| | and | |
| | animal | |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Mouse | Not classified |
| Titanium Dioxide | Human | Not classified |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------------------------------------------|----------|------------------------------------------------|
| | | |
| Triethylene Glycol Dimethacrylate (TEGDMA) | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | In Vitro | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |
| Diphenyliodonium Hexafluorophosphate | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------------------------------|------------|-------------------------------|------------------------------------------------------------------------------|
| Silane Treated Ceramic | Inhalation | similar compoun ds | Some positive data exist, but the data are not sufficient for classification |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Dermal | Mouse | Not carcinogenic |
| Titanium Dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---------------------------------------------------------|-----------|----------------------------------------|---------|--------------------------|----------------------|
| Triethylene Glycol Dimethacrylate (TEGDMA) | Ingestion | Not classified for female reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Ingestion | Not classified for male reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Ingestion | Not classified for development | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------------------------|------------|------------------------|----------------|------------------|-------------------------|----------------------|
| Diphenyliodonium Hexafluorophosphate | Inhalation | respiratory irritation | Not classified | Not available | Irritation Equivocal | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|--------------------------|-----------------------------|-----------------------|
| Silane Treated Ceramic | Inhalation | pulmonary fibrosis | Not classified | similar compoun ds | NOAEL Not available | |
| Triethylene Glycol Dimethacrylate (TEGDMA) | Dermal | kidney and/or bladder blood | Not classified | Mouse | NOAEL 833 mg/kg/day | 78 weeks |
| Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA) | Ingestion | endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

| Physical Hazards | |
|------------------|--|
| Not applicable | |

Health Hazards Respiratory or Skin Sensitization Serious eye damage or eye irritation

Additional TSCA Information

| Components | CAS No | Additional Information |
|-----------------------|-------------|-----------------------------------|
| Silane Treated Silica | 248596-91-0 | Allowed use(s): Coating additive. |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 16-1920-4
 Version Number:
 12.03

 Issue Date:
 02/17/20
 Supercedes Date:
 05/18/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 16-1922-0
 Version Number:
 7.02

 Issue Date:
 07/26/21
 Supercedes Date:
 06/05/18

SECTION 1: Identification

1.1. Product identifier

3MTM RelyXTM Veneer Try-In Paste

Product Identification Numbers

LE-F100-0702-1, 70-2010-3189-8, 70-2010-3190-6, 70-2010-3191-4, 70-2010-3192-2, 70-2010-3193-0, 70-2010-3194-8, 7000003154, 7000003155, 7000003156, 7000003157, 7000054258, 7000128794

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Veneer try-in paste

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------------|------------|------------------------|
| Polyethylene Glycol | 25322-68-3 | 80 - 95 Trade Secret * |
| Ceramic Powder | 66402-68-4 | 5 - 15 Trade Secret * |
| Titanium Oxide | 13463-67-7 | < 1 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

Page 2 **of** 9

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------|------------|--------|-----------------------------|----------------------------|
| Polyethylene Glycol | | AIHA | TWA:10 mg/m3 | |
| Titanium Oxide | | ACGIH | TWA:10 mg/m3 | A4: Not class. as human |
| | | | | carcin |
| Titanium Oxide | | OSHA | TWA(as total dust):15 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid Color White

Specific Physical Form: Paste

Odor Characteristic Odor **Odor threshold** No Data Available pН Not Applicable **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** Not Applicable **Evaporation rate** Not Applicable Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) **Vapor Pressure** Not Applicable **Vapor Density** Not Applicable Density 1.3 g/cm3

Specific Gravity 1.3 [Ref Std:WATER=1]

Solubility in Water Appreciable Solubility- non-water No Data Available Partition coefficient: n-octanol/ water Not Applicable **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Molecular weight No Data Available Percent volatile Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

Page 4 of

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|----------------|------------|-------------------------------|---------------------------------------------|
| Titanium Oxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---------------------|-----------|---------|------------------------------------------------|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Polyethylene Glycol | Dermal | Rabbit | LD50 > 20,000 mg/kg |
| Polyethylene Glycol | Ingestion | Rat | LD50 32,770 mg/kg |
| Ceramic Powder | Dermal | | LD50 estimated to be > 5,000 mg/kg |

| 07/26/21 | 07 | /26 | /21 |
|----------|----|-----|-----|
|----------|----|-----|-----|

| Ceramic Powder | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
|----------------|-------------|--------|------------------------------------------|
| Titanium Oxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Oxide | Inhalation- | Rat | LC50 > 6.82 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Titanium Oxide | Ingestion | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------|---------|---------------------------|
| | | |
| Polyethylene Glycol | Rabbit | Minimal irritation |
| Ceramic Powder | Rabbit | No significant irritation |
| Titanium Oxide | Rabbit | No significant irritation |

Serious Eve Damage/Irritation

| 00110 tab 2-j v 2 taming v 2111001011 | | | | | |
|---------------------------------------|---------|---------------------------|--|--|--|
| Name | Species | Value | | | |
| Polyethylene Glycol | Rabbit | Mild irritant | | | |
| Ceramic Powder | Rabbit | Mild irritant | | | |
| Titanium Oxide | Rabbit | No significant irritation | | | |

Skin Sensitization

| Name | Species | Value |
|---------------------|---------|----------------|
| Polyethylene Glycol | Guinea | Not classified |
| | pig | |
| Titanium Oxide | Human | Not classified |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------|----------|------------------------------------------------|
| | | |
| Polyethylene Glycol | In Vitro | Not mutagenic |
| Polyethylene Glycol | In vivo | Not mutagenic |
| Ceramic Powder | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Titanium Oxide | In Vitro | Not mutagenic |
| Titanium Oxide | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---------------------|------------|-------------------------------|------------------------------------------------------------------------------|
| Polyethylene Glycol | Ingestion | Rat | Not carcinogenic |
| Ceramic Powder | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Titanium Oxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium Oxide | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---------------------|-----------|----------------------------------------|---------|--------------------------|----------------------|
| Polyethylene Glycol | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,125 mg/kg/day | during gestation |

| 3MTM RelyXTM | Veneer Try-In Paste | 07/26/2 |
|--------------|---------------------|---------|
|--------------|---------------------|---------|

| Polyethylene Glycol | Ingestion | Not classified for male reproduction | Rat | NOAEL 5699 | 5 days |
|---------------------|------------------|----------------------------------------------------|-------|--------------------------------|---------------------|
| | | | | +/- 1341 | |
| | | | | mg/kg/day | |
| Polyethylene Glycol | Not Specified | Not classified for reproduction and/or development | | NOEL N/A | |
| Polyethylene Glycol | Ingestion | Not classified for development | Mouse | NOAEL 562 mg/animal/da y | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|------------|------------------------|----------------|---------|---------------------|----------------------|
| Polyethylene Glycol | Inhalation | respiratory irritation | Not classified | Rat | NOAEL 1.008 mg/l | 2 weeks |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|------------|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------------|-----------------------------|-----------------------|
| Polyethylene Glycol | Inhalation | respiratory system | Not classified | Rat | NOAEL 1.008 mg/l | 2 weeks |
| Polyethylene Glycol | Ingestion | kidney and/or bladder heart endocrine system hematopoietic system liver nervous system | Not classified | Rat | NOAEL 5,640 mg/kg/day | 13 weeks |
| Ceramic Powder | Inhalation | pulmonary fibrosis | Not classified | Multiple animal species | NOAEL not available | |
| Ceramic Powder | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |
| Titanium Oxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Oxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 16-1922-0
 Version Number:
 7.02

 Issue Date:
 07/26/21
 Supercedes Date:
 06/05/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Page 9 **of** 9



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-8287-4
 Version Number:
 8.00

 Issue Date:
 03/09/20
 Supercedes Date:
 02/21/20

SECTION 1: Identification

1.1. Product identifier

3MTM ScotchbondTM Universal (41258)

Product Identification Numbers

LE-F100-1014-6, LE-F100-1014-7, LE-F100-1014-9, 70-2011-3903-0 7000055178

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark |





Hazard Statements

Flammable liquid and vapor.

Causes serious eye damage.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to

extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------------------------------|--------------|------------------------|
| 2-HYDROXYETHYL METHACRYLATE | 868-77-9 | 15 - 25 Trade Secret * |
| BISPHENOL A DIGLYCIDYL ETHER | 1565-94-2 | 15 - 25 Trade Secret * |
| DIMETHACRYLATE (BISGMA) | | |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION | 1207736-18-2 | 10 - 20 Trade Secret * |
| PRODUCTS WITH 1,10-DECANEDIOL AND | | |
| PHOSPHOROUS OXIDE (P2O5) | | |

Page 2 **of** 12

| ETHANOL | 64-17-5 | 10 - 15 Trade Secret * |
|-----------------------------------------|-------------|------------------------|
| WATER | 7732-18-5 | 10 - 15 Trade Secret * |
| 2-PROPENOIC ACID, 2-METHYL-, 3- | 122334-95-6 | 7 - 13 Trade Secret * |
| (TRIMETHOXYSILYL)PROPYL ESTER, REACTION | | |
| PRODUCTS WITH VITREOUS SILICA | | |
| COPOLYMER OF ACRYLIC AND ITACONIC ACID | 25948-33-8 | 1 - 5 Trade Secret * |
| CAMPHORQUINONE | 10373-78-1 | < 2 Trade Secret * |
| DIMETHYLAMINOBENZOAT(-4) | 10287-53-3 | < 2 Trade Secret * |
| (DIMETHYLAMINO)ETHYL METHACRYLATE | 2867-47-2 | < 1 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|--------------------------|-------------------|
| Formaldehyde | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Irritant Vapors or Gases | During Combustion |
| Oxides of Nitrogen | During Combustion |
| | |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | ent C.A.S. No. Agency Limit type A | | Additional Comments | |
|------------|------------------------------------|-------|----------------------------|----------------------|
| ETHANOL | 64-17-5 | ACGIH | STEL:1000 ppm | A3: Confirmed animal |
| | | | | carcin. |
| ETHANOL | 64-17-5 | OSHA | TWA:1900 mg/m3(1000 ppm) | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid Color Yellow

Specific Physical Form:Viscous LiquidOdorCharacteristic OdorOdor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data Available

Boiling Point >= 78 °C

Flash Point 30.5 °C [Test Method:Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data AvailableDensity1 - 1.2 g/cm3

Specific Gravity 1 - 1.2 [Ref Std:WATER=1]

Solubility in Water Appreciable No Data Available Solubility- non-water Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity Not Applicable Molecular weight No Data Available **Volatile Organic Compounds** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

12

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------------------------|------------------------------------------------|
| Overall product | Dermal | Species | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 1 | _ | D 112 | |
| 2-HYDROXYETHYL METHACRYLATE 2-HYDROXYETHYL METHACRYLATE | Dermal Ingestion | Rabbit | LD50 > 5,000 mg/kg |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE | | Rat | LD50 5,564 mg/kg |
| (BISGMA) | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE | Ingestion | Rat | LD50 > 11,700 mg/kg |
| (BISGMA) | ļ | | |
| ETHANOL | Dermal | Rabbit | LD50 > 15,800 mg/kg |
| ETHANOL | Inhalation- Vapor (4 hours) | Rat | LC50 124.7 mg/l |
| ETHANOL | Ingestion | Rat | LD50 17,800 mg/kg |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| COPOLYMER OF ACRYLIC AND ITACONIC ACID | Ingestion | Rat | LD50 > 5,000 mg/kg |
| COPOLYMER OF ACRYLIC AND ITACONIC ACID | Dermal | similar health hazards | LD50 estimated to be > 5,000 mg/kg |
| CAMPHORQUINONE | Dermal | Professio nal judgeme nt | LD50 estimated to be 2,000 - 5,000 mg/kg |
| CAMPHORQUINONE | Ingestion | Rat | LD50 > 2,000 mg/kg |
| DIMETHYLAMINOBENZOAT(-4) | Dermal | Rat | LD50 > 2,000 mg/kg |
| DIMETHYLAMINOBENZOAT(-4) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| (DIMETHYLAMINO)ETHYL METHACRYLATE | Dermal | Rat | LD50 > 2,000 mg/kg |
| (DIMETHYLAMINO)ETHYL METHACRYLATE | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.436 mg/l |
| (DIMETHYLAMINO)ETHYL METHACRYLATE | Ingestion | Rat | LD50 > 2,000 mg/kg |

Page 7 **of** 12

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|-----------------------------------------------------------|----------|---------------------------|
| | | |
| Overall product | Rabbit | No significant irritation |
| 2-HYDROXYETHYL METHACRYLATE | Rabbit | Minimal irritation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Rabbit | No significant irritation |
| ETHANOL | Rabbit | No significant irritation |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- | In vitro | Corrosive |
| DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | data | |
| 2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL | Rabbit | No significant irritation |
| ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | | |
| DIMETHYLAMINOBENZOAT(-4) | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------------------------------------------------------------------------------------------------------|--------------------|---------------------------------------------|
| Overall product | In vitro data | Corrosive |
| 2-HYDROXYETHYL METHACRYLATE BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Rabbit In vitro | Moderate irritant No significant irritation |
| ETHANOL | data Rabbit | Severe irritant |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | In vitro data | Corrosive |
| 2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Rabbit | No significant irritation |
| DIMETHYLAMINOBENZOAT(-4) | Rabbit | Mild irritant |

Skin Sensitization

| Skiii Schshization | | |
|-----------------------------------------------------------|-----------|----------------|
| Name | Species | Value |
| 2-HYDROXYETHYL METHACRYLATE | Human | Sensitizing |
| | and | |
| | animal | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Mouse | Not classified |
| ETHANOL | Human | Not classified |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- | Professio | Sensitizing |
| DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | nal | |
| | judgeme | |
| | nt | |
| 2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL | Human | Not classified |
| ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------------------------------------------------------------------------------------------|----------|------------------------------------------------------------------------------|
| | | |
| 2-HYDROXYETHYL METHACRYLATE | In vivo | Not mutagenic |
| 2-HYDROXYETHYL METHACRYLATE | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | In Vitro | Not mutagenic |
| ETHANOL | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| ETHANOL | In vivo | Some positive data exist, but the data are not sufficient for classification |
| 2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | In Vitro | Not mutagenic |
| 2-PROPENOIC ACID, 2-METHYL-, 3-(TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | In Vitro | Not mutagenic |

Page 8 **of** 12

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------------------------|-----------|----------|------------------------------------------------|
| ETHANOL | Ingestion | Multiple | Some positive data exist, but the data are not |
| | | animal | sufficient for classification |
| | | species | |
| 2-PROPENOIC ACID, 2-METHYL-, 3- | Not | Mouse | Some positive data exist, but the data are not |
| (TRIMETHOXYSILYL)PROPYL ESTER, REACTION | Specified | | sufficient for classification |
| PRODUCTS WITH VITREOUS SILICA | | | |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|----------------------------------------------------------------------------------------------------------------|------------|----------------------------------------|---------|--------------------------|------------------------------|
| 2-HYDROXYETHYL METHACRYLATE | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |
| 2-HYDROXYETHYL METHACRYLATE | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |
| 2-HYDROXYETHYL METHACRYLATE | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |
| ETHANOL | Inhalation | Not classified for development | Rat | NOAEL 38 mg/l | during gestation |
| ETHANOL | Ingestion | Not classified for development | Rat | NOAEL 5,200 mg/kg/day | premating & during gestation |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| 2-PROPENOIC ACID, 2-METHYL-, 3- (TRIMETHOXYSILYL)PROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-------------------------------------------------------------------------------------------------------------------|------------|--------------------------------------|------------------------------------------------------------------------------|-------------------------------|------------------------|----------------------|
| ETHANOL | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | LOAEL 2.6 mg/l | 30 minutes |
| ETHANOL | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL 9.4 mg/l | not available |
| ETHANOL | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL not available | |
| ETHANOL | Ingestion | kidney and/or bladder | Not classified | Dog | NOAEL 3,000 mg/kg | |
| 2-PROPENOIC ACID, 2- METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5) | Inhalation | respiratory irritation | May cause respiratory irritation | similar health hazards | NOAEL Not available | |
| COPOLYMER OF | Ingestion | nervous system | Not classified | Rat | NOAEL | |

Page 9 of

| ACRYLIC AND | | | 5,000 mg/kg | |
|---------------|--|--|-------------|--|
| ITACONIC ACID | | | | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------------------------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------|-----------------------------|--------------------------|
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| ETHANOL | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Rabbit | LOAEL 124 mg/l | 365 days |
| ETHANOL | Inhalation | hematopoietic system immune system | Not classified | Rat | NOAEL 25 mg/l | 14 days |
| ETHANOL | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 8,000 mg/kg/day | 4 months |
| ETHANOL | Ingestion | kidney and/or bladder | Not classified | Dog | NOAEL 3,000 mg/kg/day | 7 days |
| 2-PROPENOIC ACID, 2- METHYL-, 3- (TRIMETHOXYSILYL)P ROPYL ESTER, REACTION PRODUCTS WITH VITREOUS SILICA | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| COPOLYMER OF ACRYLIC AND ITACONIC ACID | Ingestion | endocrine system hematopoietic system liver | Not classified | Rat | NOAEL 200 mg/kg/day | 28 days |
| COPOLYMER OF ACRYLIC AND ITACONIC ACID | Ingestion | heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 2,000 mg/kg/day | 28 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

_ 10 ...

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product—that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Page 11 **of** 12

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

8.00 **Document Group:** 29-8287-4 **Version Number: Issue Date:** 03/09/20 **Supercedes Date:** 02/21/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

12



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-8286-6
 Version Number:
 5.00

 Issue Date:
 09/02/21
 Supercedes Date:
 09/16/20

SECTION 1: Identification

1.1. Product identifier

3MTM ScotchbondTM Universal Etchant (41263)

Product Identification Numbers

ID Number UPC ID Number UPC LE-F100-1014-5 LE-F100-1040-4

70-2011-3906-3 70-2011-4006-1

70-2011-4007-9

7000055181, 7000055191, 7100007505

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Etching gel

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Corrosive to metal: Category 1.

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1C.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion |

Pictograms



Hazard Statements

May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary Statements

Prevention:

Keep only in original container.

Wear protective gloves, protective clothing, and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------------------------------|-------------|------------------------|
| WATER | 7732-18-5 | 50 - 65 Trade Secret * |
| PHOSPHORIC ACID | 7664-38-2 | 30 - 40 Trade Secret * |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | 112945-52-5 | 1 - 10 Trade Secret * |
| CRYSTALLINE FREE | | |
| POLYETHYLENE GLYCOL | 25322-68-3 | 1 - 5 Trade Secret * |
| ALUMINUM OXIDE | 1344-28-1 | < 2 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain—a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-------------------------------|------------|--------|----------------------------|----------------------------|
| SILICA, AMORPHOUS | 112945-52- | OSHA | TWA:20 millions of | |
| | 5 | | particles/cu. ft.;TWA | |
| | | | concentration:0.8 mg/m3 | |
| ALUMINUM OXIDE | 1344-28-1 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| Aluminum, insoluble compounds | 1344-28-1 | ACGIH | TWA(respirable fraction):1 | A4: Not class. as human |
| | | | mg/m3 | carcin |
| POLYETHYLENE GLYCOL | 25322-68-3 | AIHA | TWA:10 mg/m3 | |
| PHOSPHORIC ACID | 7664-38-2 | ACGIH | TWA:1 mg/m3;STEL:3 | |
| | | | mg/m3 | |
| PHOSPHORIC ACID | 7664-38-2 | OSHA | TWA:1 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eve/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquidColorBlue

Specific Physical Form: Gel

Odor Slight Odor, Characteristic Odor

Odor thresholdNo Data Available

pH < 1

Melting pointNot ApplicableBoiling PointNo Data Available

Flash Point > 100 °C [Test Method: Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data AvailableDensity1.1 - 1.2 g/ml

Specific Gravity 1.1 - 1.2 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Molecular weight No Data Available **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong bases

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------|-----------|---------|------------------------------------------------------|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| PHOSPHORIC ACID | Dermal | Rabbit | LD50 2,740 mg/kg |
| PHOSPHORIC ACID | Ingestion | Rat | LD50 1,530 mg/kg |

Page 6 **of** 10

| SYNTHETIC AMORPHOUS SILICA, FUMED, | Dermal | Rabbit | LD50 > 5,000 mg/kg |
|------------------------------------|-------------|--------|------------------------------------|
| CRYSTALLINE FREE | | | |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | Inhalation- | Rat | LC50 > 0.691 mg/l |
| CRYSTALLINE FREE | Dust/Mist | | |
| | (4 hours) | | |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | Ingestion | Rat | LD50 > 5,110 mg/kg |
| CRYSTALLINE FREE | | | |
| POLYETHYLENE GLYCOL | Dermal | Rabbit | LD50 > 20,000 mg/kg |
| POLYETHYLENE GLYCOL | Ingestion | Rat | LD50 32,770 mg/kg |
| ALUMINUM OXIDE | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| ALUMINUM OXIDE | Inhalation- | Rat | LC50 > 2.3 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| ALUMINUM OXIDE | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | | Value |
|-----------------------------------------------------|--------|---------------------------|
| PHOSPHORIC ACID | Rabbit | Corrosive |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL | Rabbit | Minimal irritation |
| ALUMINUM OXIDE | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|-----------------------------------------------------|------------|---------------------------|
| | | |
| PHOSPHORIC ACID | official | Corrosive |
| | classifica | |
| | tion | |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL | Rabbit | Mild irritant |
| ALUMINUM OXIDE | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|-----------------------------------------------------|---------|----------------|
| PHOSPHORIC ACID | Human | Not classified |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Human | Not classified |
| | and | |
| | animal | |
| POLYETHYLENE GLYCOL | Guinea | Not classified |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|-----------------------------------------------------|----------|---------------|
| | | |
| PHOSPHORIC ACID | In Vitro | Not mutagenic |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL | In vivo | Not mutagenic |
| ALUMINUM OXIDE | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|------------------------------------------------|------------|---------|------------------------------------------------|
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE | Not | Mouse | Some positive data exist, but the data are not |
| FREE | Specified | | sufficient for classification |
| POLYETHYLENE GLYCOL | Ingestion | Rat | Not carcinogenic |
| ALUMINUM OXIDE | Inhalation | Rat | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------------------------------------------|------------------|----------------------------------------------------|---------|-------------------------------------|-----------------------------|
| PHOSPHORIC ACID | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| PHOSPHORIC ACID | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| PHOSPHORIC ACID | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| POLYETHYLENE GLYCOL | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,125 mg/kg/day | during gestation |
| POLYETHYLENE GLYCOL | Ingestion | Not classified for male reproduction | Rat | NOAEL 5699 +/- 1341 mg/kg/day | 5 days |
| POLYETHYLENE GLYCOL | Not Specified | Not classified for reproduction and/or development | | NOEL N/A | |
| POLYETHYLENE GLYCOL | Ingestion | Not classified for development | Mouse | NOAEL 562 mg/animal/da y | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------|------------|------------------------|------------------------------------------------------------------------------|---------|------------------------|-----------------------|
| PHOSPHORIC ACID | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| POLYETHYLENE GLYCOL | Inhalation | respiratory irritation | Not classified | Rat | NOAEL 1.008 mg/l | 2 weeks |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------------------------------------------|------------|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------|-----------------------------|-----------------------|
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| POLYETHYLENE GLYCOL | Inhalation | respiratory system | Not classified | Rat | NOAEL 1.008 mg/l | 2 weeks |
| POLYETHYLENE GLYCOL | Ingestion | kidney and/or bladder heart endocrine system hematopoietic system liver nervous system | Not classified | Rat | NOAEL 5,640 mg/kg/day | 13 weeks |
| ALUMINUM OXIDE | Inhalation | pneumoconiosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| ALUMINUM OXIDE | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Page 8 of

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

| Physical Hazards |
|------------------|
|------------------|

Corrosive to metal

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|--------------------------------|------------------|------------------|
| ALUMINUM OXIDE | 1344-28-1 | Trade Secret < 2 |
| ALUMINUM OXIDE (ALUMINUM OXIDE | 1344-28-1 | Trade Secret < 2 |
| (FIBROUS FORMS ONLY)) | | |

15.2. State Regulations

Contact 3M for more information.

10

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 29-8286-6
 Version Number:
 5.00

 Issue Date:
 09/02/21
 Supercedes Date:
 09/16/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Page 10 of 10