

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

075038450

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

075038526

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

075038351 075038385 075038393 075038401 075038427 075038443 075038468 075038476



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	05-6374-2	<b>Version Number:</b>	26.00
<b>Issue Date:</b>	02/25/16	<b>Supersedes Date:</b>	11/26/14

### SECTION 1: Identification

#### 1.1. Product identifier

3303P 3M™ ESPE™ VITREMER GLASS IONOMER PRIMER.

#### Product Identification Numbers

LE-F100-0082-7, 70-2010-0431-7, 70-2010-0518-1, 70-2010-1333-4, 70-2010-1793-9, 70-2010-8916-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Primer

##### Restrictions on use

For use only by dental professionals

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Oral Care Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Flammable Liquid: Category 2.

Acute Toxicity (oral): Category 4.

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (central nervous system): Category 3.

#### 2.2. Label elements

**Signal word**

Danger

### Symbols

Flame | Exclamation mark |

### Pictograms



### Hazard Statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Causes eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

### Precautionary Statements

#### Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Rinse mouth.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Hazards not otherwise classified

None.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-HYDROXYETHYL METHACRYLATE	868-77-9	45 - 55 Trade Secret *
ETHYL ALCOHOL	64-17-5	35 - 45 Trade Secret *
COPOLYMER OF ITACONIC AND ACRYLIC ACIDS	25948-33-8	10 - 15 Trade Secret *
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	58109-40-3	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide

#### Condition

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHYL ALCOHOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
ETHYL ALCOHOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### Respiratory protection

None required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Liquid
Odor, Color, Grade:	Clear to yellow in color, slight acrylate odor
Odor threshold	<i>No Data Available</i>
pH	2.9 - 4
Melting point	<i>Not Applicable</i>
Boiling Point	>=67 °C
Flash Point	62 °F [ <i>Test Method:</i> Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<=27 psia [@ 131 °F]
Vapor Density	<i>No Data Available</i>
Density	<i>No Data Available</i>
Specific Gravity	1.03 [ <i>Ref Std:</i> WATER=1]
Solubility in Water	Moderate
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	9 - 13 centistoke
Molecular weight	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

#### 10.5. Incompatible materials

Strong acids  
Strong bases  
Strong oxidizing agents

#### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 11.1. Information on Toxicological effects

##### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

##### Ingestion:

Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Additional Information:**

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE 300 - 2,000 mg/kg
ETHYL ALCOHOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHYL ALCOHOL	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
ETHYL ALCOHOL	Ingestion	Rat	LD50 17,800 mg/kg
2-HYDROXYETHYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Ingestion	Rat	LD50 5,564 mg/kg
COPOLYMER OF ITACONIC AND ACRYLIC ACIDS	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
COPOLYMER OF ITACONIC AND ACRYLIC ACIDS	Ingestion	Rat	LD50 > 5,000 mg/kg
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Ingestion	Rat	LD50 32 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
ETHYL ALCOHOL	Rabbit	No significant irritation
2-HYDROXYETHYL METHACRYLATE	Rabbit	Minimal irritation
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
ETHYL ALCOHOL	Rabbit	Moderate irritant
2-HYDROXYETHYL METHACRYLATE	Rabbit	Moderate irritant
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
ETHYL ALCOHOL	Human	Some positive data exist, but the data are not sufficient for classification
2-HYDROXYETHYL METHACRYLATE	Human and animal	Sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**



Name	Route	Value
ETHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYL ALCOHOL	In vivo	Some positive data exist, but the data are not sufficient for classification
2-HYDROXYETHYL METHACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
ETHYL ALCOHOL	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	Not toxic to development	Rat	NOAEL 38 mg/l	during gestation
ETHYL ALCOHOL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 3,000 mg/kg	
COPOLYMER OF ITACONIC AND ACRYLIC ACIDS	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,000 mg/kg	
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	Irritation Equivocal	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	liver	Some positive data exist, but the	Rabbit	LOAEL 124	365 days

			data are not sufficient for classification		mg/l	
ETHYL ALCOHOL	Inhalation	hematopoietic system   immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 25 mg/l	14 days
ETHYL ALCOHOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 3,000 mg/kg/day	7 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - Yes   Pressure Hazard - No   Reactivity Hazard - No   Immediate Hazard - Yes   Delayed Hazard - No

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 16: Other information

#### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 3 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	05-6374-2	<b>Version Number:</b>	26.00
<b>Issue Date:</b>	02/25/16	<b>Supersedes Date:</b>	11/26/14

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 05-6374-2  
**Issue Date:** 07/27/21

**Version Number:** 27.02  
**Supersedes Date:** 02/09/18

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Vitremer™ Core Buildup/Restorative Primer (3303P)

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
LE-F100-0082-7		70-2010-0431-7	+H-44412-3602+-0
70-2010-0518-1	+H-44412-46120-0	70-2010-1333-4	+H-44440-3422%-0
70-2010-1793-9	+H-44446-6092B-0	70-2010-8916-9	
70-2014-0670-2			

7000054177, 7000054642, 7100143168

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Primer

##### Restrictions on use

For use only by dental professionals

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Oral Care Solutions Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

**2.2. Label elements****Signal word**

Danger

**Symbols**

Flame | Exclamation mark |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

**Precautionary Statements****Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

Keep container tightly closed.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep cool.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
2-HYDROXYETHYL METHACRYLATE	868-77-9	45 - 55 Trade Secret *
ETHYL ALCOHOL	64-17-5	35 - 45 Trade Secret *
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	25948-33-8	10 - 30 Trade Secret *
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	58109-40-3	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHYL ALCOHOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
ETHYL ALCOHOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use in a well-ventilated area.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

See Section 7.1 for additional information on skin protection.

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

**Color**

Transparent Yellow

**Specific Physical Form:**

Liquid

**Odor**

Slight Acrylate

**Odor threshold***No Data Available***pH**

2.9 - 4

**Melting point***Not Applicable***Boiling Point** $\geq 67^{\circ}\text{C}$ **Flash Point** $62^{\circ}\text{F}$  [*Test Method: Closed Cup*]**Evaporation rate***No Data Available***Flammability (solid, gas)**

Not Applicable

**Flammable Limits(LEL)***No Data Available***Flammable Limits(UEL)***No Data Available***Vapor Pressure** $\leq 27$  psia [ $@ 131^{\circ}\text{F}$ ]**Vapor Density***No Data Available***Density***No Data Available***Specific Gravity**1.03 [*Ref Std: WATER=1*]**Solubility in Water**

Moderate

**Solubility- non-water***No Data Available***Partition coefficient: n-octanol/ water***No Data Available***Autoignition temperature***No Data Available***Decomposition temperature***No Data Available***Viscosity**

9 - 13 centistoke

**Molecular weight***No Data Available***Percent volatile***No Data Available***SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

Sparks and/or flames

**10.5. Incompatible materials**

Strong acids

Strong bases



Strong oxidizing agents

#### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg

ETHYL ALCOHOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHYL ALCOHOL	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
ETHYL ALCOHOL	Ingestion	Rat	LD50 17,800 mg/kg
2-HYDROXYETHYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Ingestion	Rat	LD50 5,564 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	Ingestion	Rat	LD50 > 5,000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Ingestion	Rat	LD50 32 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
ETHYL ALCOHOL	Rabbit	No significant irritation
2-HYDROXYETHYL METHACRYLATE	Rabbit	Minimal irritation
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
ETHYL ALCOHOL	Rabbit	Severe irritant
2-HYDROXYETHYL METHACRYLATE	Rabbit	Moderate irritant
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	Mild irritant

### Skin Sensitization

Name	Species	Value
ETHYL ALCOHOL	Human	Not classified
2-HYDROXYETHYL METHACRYLATE	Human and animal	Sensitizing

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
ETHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYL ALCOHOL	In vivo	Some positive data exist, but the data are not sufficient for classification
2-HYDROXYETHYL METHACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
ETHYL ALCOHOL	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure
------	-------	-------	---------	-------------	----------

					Duration
ETHYL ALCOHOL	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ETHYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHYL ALCOHOL	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
ETHYL ALCOHOL	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHYL ALCOHOL	Inhalation	hematopoietic system   immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ETHYL ALCOHOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	Ingestion	endocrine system   hematopoietic system   liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
COPOLYMER OF ACRYLIC AND ITACONIC ACIDS	Ingestion	heart   bone, teeth, nails, and/or hair   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 05-6374-2  
**Issue Date:** 07/27/21

**Version Number:** 27.02  
**Supersedes Date:** 02/09/18

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)