SAFETY DATA SHEETS

This SDS packet was issued with item: 075038674

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075034202 075034210 075034228 075035001 075035019 075035027 075035035 075035506 075035514 075035522 075035530 075035548 075035555 075036322 075036413 075036421 075036439 075038625 075038633 075038641 075038658 075038666 075038682 075038690 075038732 075038740 075038757 079367442 079367444 079367446 079367450 079367452 079367458 079367461 079367464 079367467 079367478 079367481 273007026 273009774 273015030 273016431 273016443 273020314 273022590 273023185



Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder**MANUFACTURER:**3M**DIVISION:**3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

 Issue Date:
 01/15/13

 Supercedes Date:
 10/08/12

Document Group: 18-0262-8

Product Use:

Intended Use: Limitations on Use: Specific Use:

Dental Product For use only by dental professionals. Dental universal luting material.

SECTION 2: INGREDIENTS

| <u>C.A.S. No.</u> | <u>% by Wt</u> |
|-------------------|---|
| 65997-17-3 | 85 - 95 |
| 122334-95-6 | 5 - 10 |
| 72846-00-5 | 1 - 5 |
| 1305-62-0 | < 3 |
| 7775-27-1 | < 1 |
| 13463-67-7 | < 0.5 |
| | 65997-17-3 122334-95-6 72846-00-5 1305-62-0 7775-27-1 |

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Powder

Odor, Color, Grade: Odorless powders of different colors.

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause allergic skin reaction. May cause allergic respiratory reaction. Contains a chemical or chemicals which can cause cancer. This document has been prepared in accordance with the U.S.

MATERIAL SAFETY DATA SHEET 3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 01/15/13

OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| <u>Ingredient</u> | <u>C.A.S. No.</u> | Class Description | Regulation |
|-------------------|-------------------|-------------------------------|---|
| TITANIUM DIOXIDE | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL)

Not Applicable Not Applicable No Data Available No Data Available

MATERIAL SAFETY DATA SHEET 3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 01/15/13

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid eye contact with dust or airborne particles. Avoid prolonged or repeated skin contact.

7.2 STORAGE

Not applicable.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Not applicable. Do not use in a confined area or areas with little or no air movement.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

MATERIAL SAFETY DATA SHEET 3M[™] ESPE[™] RelyX[™] Unicem Aplicap/Maxicap Powder 01/15/13

The following eye protection(s) are recommended: Safety Glasses with side shields

8.2.2 Skin Protection

Avoid skin contact. Avoid prolonged or repeated skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves not normally required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Not applicable. Do not ingest.

8.3 EXPOSURE GUIDELINES

| Ingredient | <u>Authority</u> | Type | <u>Limit</u> | Additional Information |
|------------------------|------------------|--------------------|--------------|------------------------|
| CALCIUM HYDROXIDE | ACGIH | TWA | 5 mg/m3 | |
| CALCIUM HYDROXIDE | OSHA | TWA, respirable | 5 mg/m3 | |
| | | fraction | | |
| CALCIUM HYDROXIDE | OSHA | TWA, as total dust | 15 mg/m3 | |
| SILANIZED GLASS POWDER | Manufacturer | TWA, as dust | 10 mg/m3 | |
| | determined | | | |
| PERSULFATE COMPOUNDS | ACGIH | TWA, as persulfate | 0.1 mg/m3 | |
| TITANIUM DIOXIDE | ACGIH | TWA | 10 mg/m3 | |
| TITANIUM DIOXIDE | CMRG | TWA, as respirable | 5 mg/m3 | |
| | | dust | | |
| TITANIUM DIOXIDE | OSHA | TWA, as total dust | 15 mg/m3 | |
| | | | | |

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Odor, Color, Grade: General Physical Form: Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL) Boiling Point Density Vapor Density

Vapor Pressure

Specific Gravity pH Powder Odorless powders of different colors. Solid Not Applicable Not Applicable No Data Available Not Applicable > 1 g/ml Not Applicable Not Applicable

No Data Available Not Applicable

MATERIAL SAFETY DATA SHEET 3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 01/15/13

Melting point

Solubility in Water Evaporation rate Kow - Oct/Water partition coef Viscosity No Data Available

Negligible Not Applicable No Data Available Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid None known

10.2 Materials to avoid None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance None known. Condition During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: For quantities <100 lbs. (50kg): dispose of waste product in a sanitary landfill. For larger quantities: incinerate in an industrial or commercial facility in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

MATERIAL SAFETY DATA SHEET 3M[™] ESPE[™] RelyX[™] Unicem Aplicap/Maxicap Powder 01/15/13

SECTION 14:TRANSPORT INFORMATION

LE-FSF6-5681-1, LE-FSF6-5681-2, LE-FSFD-5682-2

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

Ingredient TITANIUM DIOXIDE <u>C.A.S. No.</u> 13463-67-7 Classification **Carcinogen

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 3: Potential effects from skin contact information was modified. Section 3: Potential effects from inhalation information was modified. Section 13: Waste disposal method information was modified.

MATERIAL SAFETY DATA SHEET 3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 01/15/13

Section 2: Ingredient table was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 3: Carcinogenicity table was modified.
Section 15: California proposition 65 ingredient information was modified.
Section 6: Personal precautions information was modified.
Section 6: Environmental procedures information was modified.
Section 6: Methods for cleaning up information was modified.
Copyright was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 18-0262-8 | Version Number: | 10.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 09/11/19 | Supercedes Date: | 01/17/18 |

SECTION 1: Identification

1.1. Product identifier

. ...

3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder

| Product Identification | Numbers | | |
|------------------------|---------------------------|----------------|-----|
| ID Number | UPC | ID Number | UPC |
| LE-FSF6-5681-1 | | LE-FSF6-5681-2 | |
| LE-FSFD-5682-2 | | | |
| 1.2. Recommended us | e and restrictions on use | | |

Recommended use Dental Product, Universal luting material. **Restrictions on use** For use only by dental professionals.

1.3. Supplier's details

| MANUFACTURER: | 3M |
|------------------|---|
| DIVISION: | Oral Care Solutions Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |
| | |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A. Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1. Carcinogenicity: Category 2. **2.2. Label elements Signal word** Danger

Symbols Health Hazard |

Pictograms



Hazard Statements

Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

IF exposed or concerned: Get medical advice/atte

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|-------------|------------------------|
| Glass powder (65997-17-3), surface modified with 2- | None | 85 - 95 Trade Secret * |
| propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester | | |
| (2530-85-0), bulk material | | |
| SILANE TREATED SILICA | 122334-95-6 | 1 - 10 Trade Secret * |
| CALCIUM HYDROXIDE | 1305-62-0 | < 3 Trade Secret * |
| SUBSTITUTED PYRIMIDINE | 72846-00-5 | 1 - 5 Trade Secret * |

3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 09/11/19

| SODIUM PERSULFATE | 7775-27-1 | < 1 Trade Secret * |
|-------------------|------------|----------------------|
| Titanium Dioxide | 13463-67-7 | < 0.5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> None known. <u>Condition</u> During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------|------------|--------|------------------------------|-------------------------|
| CALCIUM HYDROXIDE | 1305-62-0 | ACGIH | TWA:5 mg/m3 | |
| CALCIUM HYDROXIDE | 1305-62-0 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| Titanium Dioxide | 13463-67-7 | ACGIH | TWA:10 mg/m3 | A4: Not class. as human |
| | | | _ | carcin |
| Titanium Dioxide | 13463-67-7 | OSHA | TWA(as total dust):15 mg/m3 | |
| PERSULFATE COMPOUNDS | 7775-27-1 | ACGIH | TWA(as persulfate):0.1 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | |
|---|-------------------|
| Physical state | Solid |
| Color | Multicolor |
| Specific Physical Form: | Powder |
| Odor | Odorless |
| Odor threshold | No Data Available |
| рН | Not Applicable |
| Melting point | No Data Available |
| Boiling Point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | Not Applicable |
| Vapor Density | Not Applicable |
| Density | > 1 g/ml |
| Specific Gravity | No Data Available |
| Solubility in Water | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | No Data Available |
| Viscosity | Not Applicable |
| Molecular weight | No Data Available |
| Volatile Organic Compounds | Not Applicable |
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 09/11/19

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

3М^{тм} ESPE^{тм} RelyX^{тм} Unicem Aplicap/Maxicap Powder 09/11/19

| Ingredient | CAS No. | Class Description | Regulation |
|------------------|------------|-------------------------------|---|
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

| Name | Route | Species | Value |
|---|---------------------------------------|-----------------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| SILANE TREATED SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILANE TREATED SILICA | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| SILANE TREATED SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| CALCIUM HYDROXIDE | Dermal | Rabbit | LD50 > 2,500 mg/kg |
| CALCIUM HYDROXIDE | Ingestion | Rat | LD50 7,340 mg/kg |
| SUBSTITUTED PYRIMIDINE | Dermal | Professio nal judgeme nt | LD50 estimated to be 2,000 - 5,000 mg/kg |
| SUBSTITUTED PYRIMIDINE | Ingestion | Rat | LD50 > 2,000 mg/kg |
| SODIUM PERSULFATE | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| SODIUM PERSULFATE | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 47.93 mg/l |
| SODIUM PERSULFATE | Ingestion | Rat | LD50 895 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------|---------------------------|
| | D.C. | |
| Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)propyl ester (2530-85-0), bulk material | Professio nal | No significant irritation |
| | judgeme | |
| | nt | |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| CALCIUM HYDROXIDE | Human | Corrosive |
| Titanium Dioxide | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|-----------|---------------------------|
| | | |
| Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- | Professio | No significant irritation |
| (trimethoxysilyl)propyl ester (2530-85-0), bulk material | nal | |
| | judgeme | |
| | nt | |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| CALCIUM HYDROXIDE | Rabbit | Corrosive |
| Titanium Dioxide | Rabbit | No significant irritation |

09/11/19

Skin Sensitization

| Name | Species | Value |
|------------------------|---------|----------------|
| SILANE TREATED SILICA | Human | Not classified |
| | and | |
| | animal | |
| SUBSTITUTED PYRIMIDINE | Mouse | Not classified |
| Titanium Dioxide | Human | Not classified |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------------|----------|---------------|
| | | |
| SILANE TREATED SILICA | In Vitro | Not mutagenic |
| SUBSTITUTED PYRIMIDINE | In Vitro | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------|----------|--|
| SILANE TREATED SILICA | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |
| Titanium Dioxide | Ingestion | Multiple | Not carcinogenic |
| | | animal | |
| | | species | |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure |
|-----------------------|-----------|--|---------|-------------|--------------|
| | | | | | Duration |
| SILANE TREATED SILICA | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 | 1 generation |
| | 5 | | | mg/kg/day | - |
| SILANE TREATED SILICA | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 | 1 generation |
| | 5 | - | | mg/kg/day | - |
| SILANE TREATED SILICA | Ingestion | Not classified for development | Rat | NOAEL 1,350 | during |
| | • | * | | mg/kg/day | organogenesi |
| | | | | | s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------|------------|------------------------|--|---------|----------------------|----------------------|
| CALCIUM HYDROXIDE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL 2.5 mg/m3 | 20 minutes |
| SUBSTITUTED PYRIMIDINE | Ingestion | nervous system | Not classified | Rat | NOAEL 2,000 mg/kg | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure |
|--------------------------|------------|------------------------------|--|---------|---------------------|-----------------------|
| | | | | | | Duration |
| SILANE TREATED SILICA | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |

3MTM ESPETM RelyXTM Unicem Aplicap/Maxicap Powder 09/11/19

| Titanium Dioxide Inhalation pulmonary fibrosis Not classified | Human | NOAEL Not available | occupational exposure |
|---|-------|------------------------|--------------------------|
|---|-------|------------------------|--------------------------|

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 18-0262-8 | Version Number: | 10.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 09/11/19 | Supercedes Date: | 01/17/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 17-9608-5 | Version Number: | 8.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 09/11/19 | Supercedes Date: | 01/19/18 |

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM RELYXTM UNICEMTM APLICAP/MAXICAP LIQUID

Product Identification Numbers

LE-FSF6-5681-0, LE-FSFD-5682-1

1.2. Recommended use and restrictions on use

Recommended use Dental Product, For use by dental professionals.

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Oral Care Solutions Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 4. Serious Eye Damage/Irritation: Category 1. Skin Sensitizer: Category 1.

2.2. Label elements Signal word Danger

Symbols

Corrosion | Exclamation mark |

Pictograms



Hazard Statements Combustible liquid.

Causes serious eye damage. May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves and eye/face protection. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|--------------|------------------------|
| 2,6-DI-TERT-BUTYL-P-CRESOL | 128-37-0 | < 0.5 |
| Acetic acid, copper(2+) salt, monohydrate | 6046-93-1 | < 0.2 |
| mixture of mono-, di- and tri-glycerin-dimethacrylate- | 1224866-76-5 | 40 - 50 Trade Secret * |
| ester of phosphoric acid | | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | 109-16-0 | 20 - 35 Trade Secret * |
| SUBSTITUTED DIMETHACRYLATE | 27689-12-9 | 20 - 30 Trade Secret * |
| Methyl Methacrylate | 80-62-6 | < 0.5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

ЗМ^{тм} ESPE^{тм} RELYX^{тм} UNICEM^{тм} APLICAP/MAXICAP LIQUID 09/11/19

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

ЗМ^{тм} ESPE^{тм} RELYX^{тм} UNICEM^{тм} APLICAP/MAXICAP LIQUID 09/11/19

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------|------------|--------|--|---|
| 2,6-DI-TERT-BUTYL-P- | 128-37-0 | ACGIH | TWA(inhalable fraction and | A4: Not class. as human |
| CRESOL | | | vapor):2 mg/m3 | carcin |
| COPPER COMPOUNDS | 6046-93-1 | ACGIH | TWA(as Cu dust or mist):1 mg/m3;TWA(as Cu, fume):0.2 mg/m3 | |
| Methyl Methacrylate | 80-62-6 | ACGIH | TWA:50 ppm;STEL:100 ppm | Dermal Sensitizer, A4: Not class. as human carcin |
| Methyl Methacrylate | 80-62-6 | OSHA | TWA:410 mg/m3(100 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | |
|---|--|
| Physical state | Liquid |
| Color | Yellow |
| Specific Physical Form: | Liquid |
| Odor | Acrylate |
| Odor threshold | No Data Available |
| рН | 2.3 |
| Melting point | No Data Available |
| Boiling Point | > 200 °F |
| Flash Point | 64 °C [<i>Test Method</i> : Tagliabue Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | No Data Available |
| Vapor Density | No Data Available |
| Density | 1.14 g/ml |
| Specific Gravity | 1.14 [<i>Ref Std</i> :WATER=1] |
| Solubility In Water | < 63 g/l |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | No Data Available |
| Molecular weight | No Data Available |
| Percent volatile | No Data Available |
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products

Substance None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-----------|------------------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid | Ingestion | Rat | LD50 > 2,000 mg/kg |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Dermal | Professio nal | LD50 estimated to be > 5,000 mg/kg |

3MTM ESPETM RELYXTM UNICEMTM APLICAP/MAXICAP LIQUID 09/11/19

| | | judgeme nt | |
|-----------------------------------|-------------|---------------|------------------------------------|
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Ingestion | Rat | LD50 10,837 mg/kg |
| SUBSTITUTED DIMETHACRYLATE | Dermal | Professio | LD50 estimated to be > 5,000 mg/kg |
| | | nal | |
| | | judgeme | |
| | | nt | |
| SUBSTITUTED DIMETHACRYLATE | Ingestion | Rat | LD50 > 17,600 mg/kg |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Dermal | Rat | LD50 > 2,000 mg/kg |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Ingestion | Rat | LD50 > 2,930 mg/kg |
| Methyl Methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Methyl Methacrylate | Inhalation- | Rat | LC50 29 mg/l |
| | Vapor (4 | | - |
| | hours) | | |
| Methyl Methacrylate | Ingestion | Rat | LD50 7,900 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| | - | |
| mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid | Rabbit | Minimal irritation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Guinea | Mild irritant |
| | pig | |
| SUBSTITUTED DIMETHACRYLATE | Rabbit | No significant irritation |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Human | Minimal irritation |
| | and | |
| | animal | |
| Methyl Methacrylate | Human | Mild irritant |
| | and | |
| | animal | |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------|-------------------|
| | | |
| mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid | Rabbit | Corrosive |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Professio | Moderate irritant |
| | nal | |
| | judgeme | |
| | nt | |
| SUBSTITUTED DIMETHACRYLATE | Rabbit | Mild irritant |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Rabbit | Mild irritant |
| Methyl Methacrylate | Rabbit | Moderate irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid | Guinea | Not classified |
| | pig | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Human | Sensitizing |
| | and | |
| | animal | |
| SUBSTITUTED DIMETHACRYLATE | Guinea | Not classified |
| | pig | |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Human | Not classified |
| Methyl Methacrylate | Human | Sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

| Name | Species | Value |
|---------------------|---------|----------------|
| Methyl Methacrylate | Human | Not classified |

Germ Cell Mutagenicity

3MTM ESPETM RELYXTM UNICEMTM APLICAP/MAXICAP LIQUID 09/11/19

Name Route Value mixture of mono-, di- and tri-glycerin-dimethacrylate-ester of phosphoric acid In Vitro Not mutagenic TRIETHYLENE GLYCOL DIMETHACRYLATE In Vitro Some positive data exist, but the data are not sufficient for classification SUBSTITUTED DIMETHACRYLATE In Vitro Not mutagenic 2,6-DI-TERT-BUTYL-P-CRESOL In Vitro Not mutagenic 2,6-DI-TERT-BUTYL-P-CRESOL In vivo Not mutagenic Methyl Methacrylate Not mutagenic In vivo Methyl Methacrylate In Vitro Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------------------|------------|-------------------------------|--|
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Dermal | Mouse | Not carcinogenic |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Methyl Methacrylate | Ingestion | Rat | Not carcinogenic |
| Methyl Methacrylate | Inhalation | Human and animal | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------------------------|------------|--|---------|------------------------|-----------------------------|
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Ingestion | Not classified for female reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Ingestion | Not classified for male reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Ingestion | Not classified for development | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Ingestion | Not classified for female reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| 2,6-DI-TERT-BUTYL-P-CRESOL | Ingestion | Not classified for development | Rat | NOAEL 100 mg/kg/day | 2 generation |
| Methyl Methacrylate | Inhalation | Not classified for male reproduction | Mouse | NOAEL 36.9 mg/l | |
| Methyl Methacrylate | Inhalation | Not classified for development | Rat | NOAEL 8.3 mg/l | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|------------|------------------------|----------------------------------|---------|------------------------|-----------------------|
| Methyl Methacrylate | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|-----------|----------------------------------|--|---------|------------------------|----------------------|
| TRIETHYLENE GLYCOL DIMETHACRYLATE | Dermal | kidney and/or bladder blood | Not classified | Mouse | NOAEL 833 mg/kg/day | 78 weeks |
| 2,6-DI-TERT-BUTYL-P- CRESOL | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 250 mg/kg/day | 28 days |
| 2,6-DI-TERT-BUTYL-P- | Ingestion | kidney and/or | Not classified | Rat | NOAEL 500 | 2 generation |

3MTM ESPETM RELYXTM UNICEMTM APLICAP/MAXICAP LIQUID 09/11/19

| CRESOL | | bladder | | | mg/kg/day | |
|--------------------------------|------------|------------------------------|--|-------------------------------|-----------------------------|--------------------------|
| 2,6-DI-TERT-BUTYL-P- CRESOL | Ingestion | blood | Not classified | Rat | LOAEL 420 mg/kg/day | 40 days |
| 2,6-DI-TERT-BUTYL-P- CRESOL | Ingestion | endocrine system | Not classified | Rat | NOAEL 25 mg/kg/day | 2 generation |
| 2,6-DI-TERT-BUTYL-P- CRESOL | Ingestion | heart | Not classified | Mouse | NOAEL 3,480 mg/kg/day | 10 weeks |
| Methyl Methacrylate | Dermal | peripheral nervous system | Not classified | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | NOAEL Not available | 14 weeks |
| Methyl Methacrylate | Inhalation | liver | Not classified | Mouse | NOAEL 12.3 mg/l | 14 weeks |
| Methyl Methacrylate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Respiratory or Skin Sensitization Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 17-9608-5 | Version Number: | 8.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 09/11/19 | Supercedes Date: | 01/19/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com