SAFETY DATA SHEETS

This SDS packet was issued with item:

075184510

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075184528

SAFETY DATA SHEET TOKUYAMA SHIELD FORCE PLUS

1. Identification

Product identifier

Product name TOKUYAMA SHIELD FORCE PLUS

Recommended use of the chemical and restrictions on use

Restriction on use Protective sealant. For dental professionals only.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.

740 Garden View CT., Suite 200 Encinitas, CA 92024 U.S.A.

Tel: +1-760-942-7211 Fax:+1-760-942-7212

Contact person http://www.tokuyama-dental.com/tdc/contact.html

Manufacturer Tokuyama Dental Corporation

38-9, Taitou 1-chome, Taitou-ku, Tokyo

110-0016, Japan TEL: +81-3-3835-2261 FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone Tokuyama Dental America, Inc. Tel: +1-760-942-7211

Days and hours of operation: 9:00-17:00(PST/PDT), Weekdays, except national holidays in

US.

Language: English only.

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product

Regulations and the SDS contains all required information.

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361f STOT SE 3 - H336

Environmental hazards Not Classified

Label elements

Pictogram







Signal word

Hazard statements H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

TOKUYAMA SHIELD FORCE PLUS

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P321 Specific treatment (see medical advice on this label).

P332+P313 If skin irritation occurs: Get medical advice/ attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with local regulations.

3. Composition/information on ingredients

Mixtures

ISOPROPYL ALCOHOL 30-60%

CAS number: 67-63-0

2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-

10-20%

HYDROXY-3,1-PROPANEDIYL)] ESTER

CAS number: 1565-94-2

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXYETHYL

10-30%

ESTER

CAS number: 868-77-9

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXYETHYL ESTER, PHOSPHATE

10-30%

CAS number: 52628-03-2

TOKUYAMA SHIELD FORCE PLUS

2-PROPENOIC ACID, 2-METHYL-, 1,2- 5-10%

ETHANEDIYLBIS(OXY-2,1-ETHANEDIYL) ESTER

CAS number: 109-16-0

BICYCLO[2.2.1]HEPTANE-2,3-DIONE, 1,7,7-TRIMETHYL-,

1-5%

(±)-

CAS number: 10373-78-1

PHOSPHINE OXIDE, DIPHENYL(2,4,6- <1%

TRIMETHYLBENZOYL)-

CAS number: 75980-60-8

2,6-DI-t-BUTYL-4-METHYLPHENOL <1%

CAS number: 128-37-0 M factor (chronic) = 1

PHENOL, 4-METHOXY-

CAS number: 150-76-5

4. First-aid measures

Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any

discomfort continues.

Skin contact Wash skin thoroughly with soap and water. Take off contaminated clothing and wash it before

reuse.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion Suspected of damaging fertility.

Skin contact Skin irritation. Allergic rash.

Eye contact May cause severe eye irritation.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Carbon dioxide or dry powder.

Specific hazards arising from the hazardous product

Specific hazards Irritating gases or vapours. The product is highly flammable.

TOKUYAMA SHIELD FORCE PLUS

Hazardous combustion

products

No known hazardous decomposition products.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

for firefighters

Special protective equipment Wear chemical protective suit.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

> spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Use non-sparking tools. Ground/bond container and receiving equipment. Avoid

the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections

Reference to other sections For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. All handling

> should only take place in well-ventilated areas. Avoid inhalation of vapours/spray and contact with skin and eyes. Take precautionary measures against static discharges. Use explosion-

proof electrical, ventilating and lighting equipment.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Protect from sunlight. Store at temperatures between

0°C/10°F and 32°C/50°F.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ISOPROPYL ALCOHOL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

2,6-DI-t-BUTYL-4-METHYLPHENOL

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

A4

PHENOL, 4-METHOXY-

TOKUYAMA SHIELD FORCE PLUS

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Use explosion-proof electrical,

ventilating and lighting equipment.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Wear protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. Wash

promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Wash contaminated clothing before reuse. Use appropriate skin

cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid

Colour Light green

Odour Characteristic

Odour threshold Not available.

pH pH (diluted solution): 2.3

Melting point Not available.

Initial boiling point and range Not available.

Flash point 20.0°C

Evaporation rate Not available.

Evaporation factor Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Not applicable.

Other flammability Not available.

Vapour pressure Not available.

Vapour density Not available.

Relative density 1.00

Solubility(ies) Not available.

Partition coefficient Not available.

Auto-ignition temperature Not available.

Decomposition Temperature Not available.

TOKUYAMA SHIELD FORCE PLUS

Viscosity Not available.

Explosive properties Not explosive.

Other information Not available.

10. Stability and reactivity

Oxidising properties

Reactivity There are no known reactivity hazards associated with this product. See the other subsections

of this section for further details.

Stability The product is highly flammable.

Possibility of hazardous

reactions

Not known.

Not available.

Conditions to avoid Keep away from heat, sparks and open flame. Protect against direct sunlight.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Heating may generate the following products: Toxic gases or vapours.

11. Toxicological information

Information on toxicological effects

Routes of exposure Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.

Acute toxicity - oral

Notes (oral LD₅₀) Not available.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not available.

Skin corrosion/irritation

Skin corrosion/irritation Not available.

Animal data Not available.

Serious eye damage/irritation

Serious eye damage/irritation Not available.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Not available.

Germ cell mutagenicity

Genotoxicity - in vitro

Not available.

Genotoxicity - in vivo

Not available.

Carcinogenicity

TOKUYAMA SHIELD FORCE PLUS

Carcinogenicity Not available.

IARC carcinogenicity Some of the ingredients are listed or exempt.

NTP carcinogenicity Some of the ingredients are listed or exempt.

OSHA Carcinogenicity None of the ingredients are listed.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity - Not available.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Not available.

Toxicological information on ingredients

ISOPROPYL ALCOHOL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

2,6-DI-t-BUTYL-4-METHYLPHENOL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Toxicity Not available.

Ecological information on ingredients

2,6-DI-t-BUTYL-4-METHYLPHENOL

Chronic aquatic toxicity

M factor (chronic) 1

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

TOKUYAMA SHIELD FORCE PLUS

Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN number

UN No. (TDG) 1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133

UN No. (DOT) UN1133

UN proper shipping name

Proper shipping name (TDG) ADHESIVES, containing flammable liquid

Proper shipping name (IMDG) ADHESIVES, containing flammable liquid

Proper shipping name (ICAO) ADHESIVES, containing flammable liquid

Proper shipping name (DOT) Adhesives, a containing flammable liquid

Transport hazard class(es)

DOT class 3

DOT hazard label 3

TDG class 3

TDG label(s) 3

IMDG class 3

ICAO class/division 3

DOT transport label



Transport labels



Packing group

TDG packing group II
IMDG packing group II
ICAO packing group II

TOKUYAMA SHIELD FORCE PLUS

DOT packing group Ш

Special precautions for user

EmS F-E, S-D

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Regulatory References According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as

> amended) and the requirements of the Hazardous Product Regulations (HPR) Hazardous Products Regulations - SOR/2015-17. Transportation of Dangerous Goods Regulations -

SOR/2015-100.

16. Other information

Training advice Ensure operatives are trained to minimize exposure. Only trained personnel should use this

material.

Revision comments This is first issue.

Revision date 20/03/2018

Revision 1

Hazard statements in full H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be replied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.