

SAFETY DATA SHEETS

This SDS packet was issued with item:

076030647

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

076030639

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

076030621 076030654

Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Product Name: Duraliner II Powder Clear

Company Identification:

Reliance Dental Mfg., LLC.

5805 W. 117th Place

Alsip, IL 60803

For Product Information, call: 708-597-6694 **For Medical Information, call:** 800-535-5053

Section 2 - Hazards Identification

Classification of the substance or mixture

Hazard Class – Physical, Health, Environmental

Eye Damage/Irritation

Category

2B

OSHA Defined Hazards

Combustible dust, may form combustible dust concentrations in air, explosion hazard

Label Elements - *Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information*

Signal Word

Warning

Signal Word Warning

Hazards Statements

H320 Causes eye irritation

-

Precautionary Statements-Prevention, Response & Disposal

P240 Ground and bond container and receiving equipment

P264 Wash hands and exposed skin thoroughly after handling

P305+P351 IF IN EYES: Rinse continuously with water for several
+P338 minutes. Remove contact lenses if present and easy to do
continue rinsing

P337+P313 Get medical advice/attention

Section 3 - Composition, Information on Ingredients

Chemical Name

2-Propenoic acid, 2-methyl-
Ethyl ester, homopolymer

CAS #

9003-42-3

Weight - %

90 - 100

GHS Ratings

Eye Damage/irritation 2B(H320)

Section 4 - First Aid Measures

| | |
|-----------------------|--|
| General advice | Provide the SDS to medical personnel for treatment. |
| Inhalation: | Remove victim to fresh air. Seek immediate medical attention. |
| Eye Contact: | If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician. |
| Skin Contact: | Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. |
| Clothing: | Remove contaminated clothing, wash thoroughly before reuse. |
| Ingestion: | If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately. |

Section 5 - Fire Fighting Measures

| | |
|---|---|
| Suitable Extinguishing Media: | Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide. |
| Unsuitable Extinguishing Media: | Water may not be effective in extinguishing this fire. |
| Specific Hazards Arising from the Chemical: | Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures. |
| Special Fire Fighting Procedures: | Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus. |
| Protective Equipment and Precautions for Firefighters: | Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts. |

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

| | |
|-----------------------------|---|
| Personal Precautions | Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse. |
|-----------------------------|---|

Environmental Precautions

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800)424-8802.

Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

Methods for Cleaning Up

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

Section 7 - Handling and Storage

PRECAUTIONS FOR HANDLING

Advice on Safe handling:

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

Conditions for Safe Storage, Including any Incompatibilities

Storage conditions:

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned or destroyed.

Incompatible Materials:

Strong oxidizers, strong oxidizing agents

Section 8 - Exposure Controls, Personal Protection

Chemical Name/CAS No.

2-Propenoic acid, 2-methyl-Ethyl ester, homopolymer
9003-42-3

OSHA Exposure Limits

ACGIH Exposure Limits

Other Exposure Limits

Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personnel Protective Equipment (PPE)

Respiratory Protection

A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye/Face Protection

Wear safety glasses, chemical goggles when splashing is possible, when dealing with this materials. If necessary, refer to 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and Body Protection

Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use **proper glove removal technique (without touching glove's outer surface)** to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full Contact:

Material: Nitrile rubber
Minimum Layer thickness: 0.4 mm
Break through time: 480 min.

Splash Contact:

Material: Nitrile rubber
Minimum Layer thickness: 0.11 mm
Break through time: 120 min.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

Section 9 - Physical and Chemical Properties

| | |
|---------------------------------------|---------------------|
| APPEARANCE: | Fine white powder. |
| ODOR: | Faint odor in bulk. |
| FLASH POINT: | 577°F, 303°C |
| FLAMMABLE LIMIT (AIR VOLUME %) | N/A |
| AUTOIGNITION TEMPERATURE: | N/A |
| EVAPORATION RATE | No data available. |
| BOILING RANGE (LOW-HIGH) | N/A |
| SPECIFIC GRAVITY: | 0.00 |

Section 10 - Stability and Reactivity

| | |
|--|--|
| MATERIAL STABILITY: | Stable |
| INCOMPATIBILITY (MATERIALS TO AVOID): | Strong oxidiziers |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Methacrylate Monomer and Oxides of Carbon when burned. |
| POSSIBILITY OF HAZARDOUS REACTIONS: | Hazardous polymerization will not occur. |

Section 11 - Toxicological Information

MIXTURE TOXICITY

Component Toxicity

Routes of Exposure: Inhalation and Eye Contact

Target Organs: No data available

Effects of Overexposure:

Product Components Listed as Carcinogenic

| CAS Number | Description | %Weight | Carcinogen Rating |
|------------|-------------|---------|-------------------|
| None | | | No data available |

Section 12 - Ecological Information

Component Ecotoxicity

Section 13 - Disposal Considerations

WASTE DISPOSAL METHOD

Disposal of Wastes: Dispose of properly in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

Contaminated Packaging: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations.

Section 14 - Transport Information

| Agency Class | Proper Shipping Name | UN Number | Packing Group | Hazard |
|--------------|-----------------------------|-----------|---------------|--------|
| DOT | Not Regulated, Polymer, NOS | | | |
| IATA | Not Regulated, Polymer, NOS | | | |
| IMDG | Not Regulated, Polymer, NOS | | | |

Section 15 - Regulatory Information

State of California Safe drinking Water and Toxic Enforcement Act of 1986

(Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

-None

SARA 313 None

US State Right-to-know Regulations

-None

| Country | Regulations | All Components Listed |
|---------|------------------------|-----------------------|
| | Canada | Yes |
| | EINECS | Yes |
| | SARA Hazard categories | No |
| | TSCA Inventory | Yes |

Section 16 - Additional Information

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:

| | |
|--------------------------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 1 |
| REACTIVITY: | 0 |
| PERSONAL PROTECTIVE EQUIPMENT: | B |

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

| | |
|---------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 1 |
| REACTIVITY: | 0 |

HMIS & NFPA Hazard Rating

* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

B = Gloves and Safety Glasses or Chemical Goggles.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, process, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such materials used in combination with any other materials on in any process, unless specified in the text.

Revised October 2, 2017

Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Product Name: Duraliner II Powder

Company Identification:

Reliance Dental Mfg., LLC.

5805 W. 117th Place

Alsip, IL 60803

For Product Information, call: 708-597-6694 **For Medical Information, call:** 800-535-5053

Section 2 - Hazards Identification

Classification of the substance or mixture

Hazard Class - *Physical, Health, Environmental*

Category

Eye Damage/Irritation

2A

Skin sensitizer

1

OSHA Defined Hazards

Combustible dust, may form combustible dust concentrations in air, explosion hazard

Label Elements - *Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information*



Signal Word

Warning

Hazards Statements

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

Precautionary Statements - *Prevention, Response, & Disposal*

P240 Ground and bond container and receiving equipment

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash hands and exposed skin thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective gloves/protective clothing/eye protection/face protection

P321 Specific treatment (see ... on this label)

P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with soap and water

P305+P351 IF IN EYES: Rinse continuously with water for several

+P338 minutes. Remove contact lenses if present and easy to do – continue rinsing

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P337+P313 Get medical advice/attention

P501 Dispose of contents/container to an authorized disposal facility

Section 3 - Composition, Information on Ingredients

| Item | Chemical Name | CAS # | WT/WT% | GHS Ratings |
|------|---|------------|--------|---|
| | 2-Propenoic acid, 2-methyl-, ethyl ester, homopolymer | 9003-42-3 | 90–100 | Eye Damage/Irritation 2B (H320) |
| | Benzoyl Peroxide | 94-36-0 | 1–5 | Eye Damage/Irritation 2A (H319) Skin Sensitizer 1 (H317) |
| | Titanium Dioxide (CI 77891) | 13463-67-7 | 0-1 | |

Section 4 - First Aid Measures

| | |
|------------------------|--|
| General Advice: | Provide the SDS to medical personnel for treatment. |
| Inhalation: | Remove victim to fresh air. Seek immediate medical attention. |
| Eye Contact: | If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician. |
| Skin Contact: | Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. |
| Clothing: | Remove contaminated clothing, wash thoroughly before reuse. |
| Ingestion: | If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately. |

Section 5 - Fire Fighting Measures

| | |
|---|---|
| Suitable Extinguishing Media: | Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide. |
| Unsuitable Extinguishing Media: | Water may not be effective in extinguishing this fire. |
| Specific Hazards Arising from the Chemical: | Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures. |
| Special Fire Fighting Procedures: | Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus. |
| Protective Equipment and Precautions for Firefighters: | Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts. |

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

| | |
|-----------------------------------|--|
| Personal Precautions: | Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse. |
| Environmental Precautions: | Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. |

Methods and Material for Containment and Cleaning Up

| | |
|---------------------------------|--|
| Methods for Containment: | Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply. |
| Methods for Cleaning Up: | Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste. |

Section 7 - Handling and Storage

Precautions for Safe Handling

| | |
|---------------------------------|---|
| Advice on Safe Handling: | Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. |
|---------------------------------|---|

Conditions for Safe Storage, Including any Incompatibilities

| | |
|--------------------------------|---|
| Storage Conditions: | Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned, or destroyed. |
| Incompatible Materials: | Strong oxidizers, strong oxidizing agents. |

Section 8 - Exposure Controls, Personal Protection

| Chemical name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|---|---------------------------|-----------------------|-----------------------|
| 2-Propenoic acid, 2-methyl, ethyl ester, homopolymer 9003-42-3 | | | |
| Benzoyl Peroxide 94-36-0 | 5 mg/m3 TWA | 5 mg/m3 TWA | NIOSH: 5 mg/m3 TWA |
| Titanium Dioxide (CI 77891) 13463-67-7 | 15 mg/m3 TWA (total dust) | 10 mg/m3 TWA | |

Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personnel Protective Equipment (PPE)

Respiratory Protection: A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye/Face Protection: Wear safety glasses, chemical goggles when splashing is possible, when dealing with this material. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and Body Protection: Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact:

Material: Nitrile rubber
Minimum layer thickness: 0.4 mm
Break through time: 480 min

Splash contact:

Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 120 min

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

Section 9 - Physical and Chemical Properties

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pink

Physical State: Powder

4 of 6

Duraliner II Powder

Odor: Faint

Flash Point: 577 F, 303 C

Flammable Limit (Air Volume%, 0% Lower/Upper) **Evaporation Rate** No data available

Boiling Range (low - high) N/A

Section 10 - Stability and Reactivity

Material stability:

Stable

Incompatible materials:

Strong oxidizers

Hazardous decomposition products:

Methacrylate Monomer and Oxides of Carbon when burned.

Possibility of hazardous reactions:

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Component Toxicity

Routes of Exposure

Inhalation, Eye Contact, Ingestion

Target Organs

Eyes, Lungs, Skin, Respiratory System

Effects of Overexposure

| | |
|---------------|--|
| Inhalation: | Overexposure by inhalation of titanium dioxide may include mild and temporary upper respiratory irritation with cough and shortness of breath. |
| Skin contact: | No data found |
| Eye Contact: | No data found |
| Ingestion: | No data found |

Product Components Listed as Carcinogenic

| CAS Number | Description | % Weight | Carcinogen Rating |
|------------|-----------------------------|-------------|--|
| 13463-67-7 | Titanium Dioxide (CI 77891) | 0.1 to 1.0% | Titanium Dioxide (CI 77891) NIOSH: Potential occupational carcinogen IARC: Possible human carcinogen OSHA: Listed |

Section 12 - Ecological Information

Component Ecotoxicity

Section 13 - Disposal Considerations

Waste Treatment Methods

Disposal of Wastes

Dispose waste material in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations

Section 14 - Transport Information

| Agency | Proper Shipping Name | UN Number | Packing Group | Hazard Class |
|--------|-----------------------------|-----------|---------------|--------------|
| DOT | Not Regulated, Polymer, NOS | | | |
| IATA | Not Regulated, Polymer, NOS | | | |
| IMDG | Not Regulated, Polymer, NOS | | | |

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986

(Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- 13463-67-7 Titanium Dioxide (CI 77891) 0.1 to 1.0% Carcinogen

SARA 313: Benzoyl Peroxide 94-36-0

US State Right-to-Know Regulations - None

| Country | Regulation | All Components Listed |
|---------|------------------------|-----------------------|
| | EINECS | Yes |
| | SARA Hazard categories | No |
| | TSCA Inventory | Yes |

Section 16 - Additional Information

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:

| | |
|--------------------------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 1 |
| REACTIVITY: | 0 |
| PERSONAL PROTECTIVE EQUIPMENT: | B |

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

| | |
|---------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 1 |
| REACTIVITY: | 0 |

HMIS & NFPA Hazard Rating

*= Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

B = Gloves and Safety Glasses or Chemical Goggles.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, process, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such materials used in combination with any other materials on in any process, unless specified in the text.

Revised October 2, 2017