

SAFETY DATA SHEETS

This SDS packet was issued with item:

076749840

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

076749816

REVISION DATE 15/01/2013

MATERIAL SAFETY DATA SHEET

TOKUYAMA REBASE II Adhesive

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME TOKUYAMA REBASE II Adhesive

PRODUCT USE Denture Liner, a component of kit. For dental professionals only.

SUPPLIER Tokuyama Dental America Inc. MANUFACTURER Tokuyama Dental Corporation
Tel: (877) 378 3548 (Toll-Free) 38-9, Taitou 1-chome, Taitou-ku,
Tokyo, Japan
TEL: +81-3-3835-7201

CONTACT PERSON <http://www.tokuyama-dental.com/contact.htm>

EMERGENCY TELEPHONE

Washington
National Capital Poison Center
3201 New Mexico Avenue, Suite 310 Washington, DC 20016
Telephone: +1 202 362 3867
Emergency telephone: 1 800 222 1222
Fax: +1 202 362 8377
E-mail: pc@poison.org
Web site: <http://www.poison.org>

San Francisco
California Poison Control System
at San Francisco General Hospital
University of California San Fransico, Box 1369
1001 Potrero Avenue, Bidg 5 Rm 2A21
San Francisco, California 94143-1369
Telephone: +1 415 643 3200
Emergency telephone: 1 800 222 1222
Fax: +1 415 502 6010
E-mail: coadmin@calpoison.org
Web site: <http://www.calpoison.org>

<http://www.who.int/ipcs/poisons/centre/en/>

2 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

INHALATION

Irritating to respiratory system. Vapors may cause drowsiness and dizziness.

INGESTION

Slightly irritating. : DIGESTIVE SYSTEM.

SKIN CONTACT

Slightly irritating. Product has a defatting effect on skin. Prolonged contact may cause redness and irritation.

EYE CONTACT

Irritating and may cause redness and pain.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %
ACETONE	200-662-2	67-64-1	30-60%
ETHYL ACETATE	205-500-4	141-78-6	30-60%

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once.

REVISION DATE 15/01/2013

TOKUYAMA REBASE II Adhesive**INGESTION**

Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam. Carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapors.

SPECIFIC HAZARDS

When heated and in case of fire, irritating vapours/gases may be formed.

PROTECTIVE MEASURES IN FIRE

Wear full protective clothing.

FLASH POINT (°C) -14°C

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this material safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE**HANDLING**

All handling to take place in well-ventilated area.

STORAGE

Store in a cool, dark place (0-25°C, 32-77°F). Keep away from heat, direct sunlight, sparks and open flames.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT	STD	TWA (8-hrs)		STEL (15 min)		Notes
ACETONE	PEL	1000 ppm	2400 mg/m3			
ACETONE	ACGIH	500 ppm		750 ppm		A4
ETHYL ACETATE	ACGIH	400 ppm				
ETHYL ACETATE	PEL	400 ppm	1400 mg/m3			
COMPONENT						IDLH
ACETONE						2500 ppm
ETHYL ACETATE						2000 ppm

ACGIH=American Conference of Governmental Industrial Hygienists.

A4: Not Classifiable as a Human Carcinogen.

PROTECTIVE EQUIPMENT

REVISION DATE 15/01/2013

TOKUYAMA REBASE II Adhesive**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

HAND PROTECTION

Wear protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear liquid
COLOR	Yellowish
ODOR	Characteristic
BOILING POINT (°C)	57°C
FLASH POINT (°C)	-14°C

10 STABILITY AND REACTIVITY

STABILITY

HIGHLY FLAMMABLE!

CONDITIONS TO AVOID

Keep away from heat, sparks and open flame. Protect against direct sunlight.

MATERIALS TO AVOID

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Toxic gases are generated when heated.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

No data on possible toxic effects have been found.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No data on possible environmental effects have been found.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

REVISION DATE 15/01/2013

TOKUYAMA REBASE II Adhesive



DOT PROPER SHIPPING NAME	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
TDG SHIPPING NAME	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
IDENTIFICATION No.	1133
TUNNEL RESTRICTION CODE	(D/E)
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
DOT HAZARD CLASS	3
DOT PACKING GROUP	II
U.S DOT HAZARD LABEL	Flammable Liquid
UN NO. SEA	1133
IMDG CLASS	3
IMDG PACK GR.	II
EMS	F-E, S-D
UN NO. AIR	1133
ICAO CLASS	3
AIR PACK GR.	II
TDG CLASS	3
TDG LABEL(S)	3
TDG PACKING GROUP	II

15 REGULATORY INFORMATION

INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
ACETONE	DSL	Yes.						
ETHYL ACETATE	DSL	Yes.						

COMPONENT	TSCA 12(b) Export Notification
ACETONE	Yes.
ETHYL ACETATE	Yes.

US FEDERAL REGULATIONS

COMPONENT	SARA 302-TPQ	CERCLA-RQ	SARA 313
ACETONE	Not Listed	5 000 lbs	No.
ETHYL ACETATE	Not Listed	5 000 lbs	No.

CLEAN AIR ACT

COMPONENT	CAA Accidental Release Prevention
ACETONE	Not Listed
ETHYL ACETATE	Not Listed

REVISION DATE 15/01/2013

TOKUYAMA REBASE II Adhesive

US STATE REGULATIONS

COMPONENT	CAS	CA	FL	MA	MN	NJ	PA	RI
ACETONE	67-64-1	Not Listed	Yes.	Yes.	Yes.	Yes.	Yes.	Yes.
ETHYL ACETATE	141-78-6	Not Listed	Yes.	Yes.	Yes.	Yes.	Yes.	Yes.

REGULATORY REFERENCES

29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

16 OTHER INFORMATION

REVISION DATE

15/01/2013

DISCLAIMER

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such.

Revision Date 08/05/2017

Revision 2

SAFETY DATA SHEET

TOKUYAMA REBASE II Adhesive

1. IDENTIFICATION

Product Name	TOKUYAMA REBASE II Adhesive
Identified uses	Denture Liner, a component of kit. For dental professionals only.
Supplier	Tokuyama Dental America Inc. Tel: (877) 378 3548 (Toll-Free)
Contact Person	http://www.tokuyama-dental.com/tdc/contact.html
Manufacturer	Tokuyama Dental Corporation 38-9, Taitou 1-chome, Taitou-ku, Tokyo 110-0016, Japan TEL: +81-3-3835-2261
Emergency Telephone	California Poison Control System - San Francisco Division San Francisco General Hospital Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco Emergency telephone number: 1 800 222 1222 E-mail address: coadmin@calpoison.org http://www.calpoison.org National Capital Poison Center 3201 New Mexico Ave, Ste 310, Washington DC Emergency telephone number: 1 800 222 1222 Telephone number: +1 202 362 3867 Facsimile number: +1 202 362 8377 E-mail address: pc@poison.org http://www.poison.org

2. HAZARD(S) IDENTIFICATION

Appearance	Clear liquid
Color	Yellowish
Odor	Characteristic
GHS Pictogram	



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.

TOKUYAMA REBASE II Adhesive

P403+233

Store in a well-ventilated place. Keep container tightly closed.

P501

Dispose of contents/container in accordance with local regulations.

Contains

ACETONE

ETHYL ACETATE

GHS Classification

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	Eye Irrit. 2 - H319; STOT SE 3 - H336
Environment	Not classified.

Hazard Not Otherwise Classified (HNOC)

Repeated exposure may cause skin dryness or cracking.

OSHA Regulatory Status

This Product is Hazardous under the OSHA Hazard Communication Standard.

General Information

May cause irritation to the respiratory system. Vapors may cause drowsiness and dizziness. IF SWALLOWED: Slightly irritating. (DIGESTIVE SYSTEM.) This chemical may cause skin/eye irritation. Product has a defatting effect on skin. Prolonged skin contact may cause redness, irritation and dry skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

ACETONE	30-60%
CAS No.: 67-64-1	EC No.: 200-662-2
GHS Classification Flam. Liq. 2 - H225; Eye Irrit. 2 - H319; STOT SE 3 - H336	

ETHYL ACETATE	30-60%
CAS No.: 141-78-6	EC No.: 205-500-4
GHS Classification Flam. Liq. 2 - H225; Eye Irrit. 2 - H319; STOT SE 3 - H336	

4. FIRST-AID MEASURES

Description of first aid measures

General Information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once.

Ingestion

Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention if any discomfort continues.

Skin Contact

Wash the skin immediately with soap and water.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

Most important symptoms and effects, both acute and delayed

Inhalation

Irritating to respiratory system. Vapors may cause drowsiness and dizziness.

Ingestion

Slightly irritating. (DIGESTIVE SYSTEM.)

Skin Contact

Slightly irritating. Product has a defatting effect on skin. Prolonged contact may cause redness and irritation.

TOKUYAMA REBASE II Adhesive

Eye Contact

Irritating and may cause redness and pain.

Indication of any immediate medical attention and special treatment needed

Notes To The Physician

CAUTION! First aid personnel must be aware of own risk during rescue! Wear suitable protective clothing.

5. FIRE-FIGHTING MEASURES

Auto Ignition Temperature (°C)

Not available.

Flammability Limit - Lower(%)

Not available.

Flammability Limit - Upper(%)

Not available.

Flash point (°C) -14°C

Extinguishing Media

Fire can be extinguished using: Foam. Carbon dioxide or dry powder.

Specific Hazards

When heated and in case of fire, irritating vapors/gases may be formed.

Special Fire Fighting Procedures

Avoid breathing fire vapors.

Protective Equipment For Fire-Fighters

Wear full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear protective clothing as described in Section 8 of this material safety data sheet.

Environmental Precautions

Do not allow to enter drains, sewers or watercourses.

Spill Clean Up Methods

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

Reference to other sections

For personal protection, see section 8.

7. HANDLING AND STORAGE

Handling

All handling to take place in well-ventilated area.

Storage

Store in a cool, dark place (0-25°C, 32-77°F). Keep away from heat, direct sunlight, sparks and open flames.

Storage Class

Flammable liquid storage.

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT	STD	TWA (8-hrs)		STEL (15 min)		Notes
ACETONE	PEL	1000 ppm	2400 mg/m ³			
ACETONE	ACGIH	500 ppm		750 ppm		A4
ETHYL ACETATE	ACGIH	400 ppm				
ETHYL ACETATE	PEL	400 ppm	1400 mg/m ³			

TOKUYAMA REBASE II Adhesive

COMPONENT	IDLH
ACETONE	2500 ppm
ETHYL ACETATE	2000 ppm

ACGIH=American Conference of Governmental Industrial Hygienists.

A4: Not Classifiable as a Human Carcinogen.

Protective Equipment



Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

In case of inadequate ventilation use suitable respirator.

Hand Protection

Wear protective gloves.

Eye Protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid.
Color	Yellowish
Odor	Characteristic.
Solubility	No information available.
Initial boiling point and boiling range	57°C
Melting point (°C)	Not available.
Relative density	Not available.
Vapor density (air=1)	Not available.
Vapor pressure	Not available.
Evaporation rate	Not available.
pH-Value, Conc. Solution	Not available.
pH-Value, Diluted Solution	Not available.
Viscosity	Not available.
Decomposition temperature (°C)	Not available.
Odour Threshold, Lower	Not available.
Odour Threshold, Upper	Not available.
Flash point	-14°C

TOKUYAMA REBASE II Adhesive

Auto Ignition Temperature (°C)

Not available.

Flammability Limit - Lower(%)

Not available.

Flammability Limit - Upper(%)

Not available.

Partition Coefficient

(N-Octanol/Water)

Not available.

Explosive properties

Not available.

Other Flammability

Not available.

Oxidising properties

Not available.

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Stability

HIGHLY FLAMMABLE!

Hazardous reactions:

Not available.

Conditions To Avoid

Keep away from heat, sparks and open flame. Protect against direct sunlight.

Materials To Avoid

Strong oxidizing agents.

Hazardous Decomposition Products

Toxic gases are generated when heated.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Not available.

Skin Corrosion/Irritation:

Slightly irritating. Product has a defatting effect on skin. Prolonged skin contact may cause redness and irritation.

Serious eye damage/irritation:

Irritating and may cause redness and pain.

Respiratory or skin sensitisation:

Respiratory sensitisation

Not available.

Skin sensitisation

Not available.

Germ cell mutagenicity:

Not available.

Carcinogenicity:

Acetone

EPA: Data are inadequate for an assessment of human carcinogenic potential

IARC Carcinogenicity

Not listed.

NTP - Carcinogenicity

Not listed.

OSHA - Carcinogenicity

Not listed.

TOKUYAMA REBASE II Adhesive

Reproductive Toxicity:

Not available.

Specific target organ toxicity - single exposure:

Irritating to respiratory system. Vapors may cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

Not available.

Aspiration hazard:

Viscosity

Not available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data on possible environmental effects have been found.

Toxicity

No data available.

Degradability

No data available.

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Not available.

Mobility:

No information available.

Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB Substances.

Other adverse effects

Not known.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

UN No. (DOT/TDG)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133
DOT Proper Shipping Name	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
TDG Proper Shipping Name	ADHESIVES, CONTAINING A FLAMMABLE LIQUID
DOT Hazard Class	3
DOT Hazard Label	Flammable Liquid
TDG Class	3
TDG Label(s)	3
IMDG Class	3
ICAO Class	3
Transport Labels	

TOKUYAMA REBASE II Adhesive



DOT Pack Group II

IMDG Pack Group II

Air Pack Group II

Environmentally Hazardous Substance/Marine Pollutant

No.

EMS F-E, S-D

Special precautions for user Not applicable.

Transport in Bulk according to Annex II of MARPOL 73/78 and the IBC Code Notes

Not applicable.

15. REGULATORY INFORMATION

Regulatory Status (US)

This Product is Hazardous under the OSHA Hazard Communication Standard.

Regulatory References

29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

All ingredients are listed.

ACETONE; 5, 000 lbs (2270 Kg)

ETHYL ACETATE; 5, 000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

None of the ingredients are listed.

CAA Accidental Release Prevention

None of the ingredients are listed.

SARA (311/312) Hazard Categories

Fire Acute

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

All ingredients are listed.

Rhode Island "Right To Know" List

All ingredients are listed.

Minnesota "Right To Know" List

All ingredients are listed.

TOKUYAMA REBASE II Adhesive

New Jersey "Right To Know" List

All ingredients are listed.

Pennsylvania "Right To Know" List

All ingredients are listed.

International Inventories

EU - EINECS/ELINCS

All ingredients are listed or exempt.

Canada – DSL/NDSL

All ingredients are listed or exempt.

US - TSCA

All ingredients are listed or exempt.

US – TSCA 12(b) Export Notification

None of the ingredients are listed.

16. OTHER INFORMATION

Revision Comments

Revision Date	08/05/2017
Revision	2

Disclaimer

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.