

SAFETY DATA SHEETS

This SDS packet was issued with item:

075184999

N/A

SAFETY DATA SHEET

SILICONE REMOVER

1. Identification

Product identifier

Product name SILICONE REMOVER
Chemical name METHYL METHACRYLATE
CAS number 80-62-6

Recommended use of the chemical and restrictions on use

Restriction on use SILICONE REMOVER is an auxiliary agent used to remove the silicone-based materials from the acrylic resin. This product is classified as non medical device because of the limited application with outside of the patient's mouth even though it is used in a dental clinic or dental laboratory.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.
740 Garden View CT., Suite 200 Encinitas, CA 92024 U.S.A.
Tel: +1-760-942-7211
Fax: +1-760-942-7212

Contact person <http://www.tokuyama-dental.com/tdc/contact.html>

Manufacturer Tokuyama Dental Corporation
38-9, Taitou 1-chome, Taitou-ku, Tokyo
110-0016, Japan
TEL: +81-3-3835-2261
FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone Tokuyama Dental America, Inc. Tel: +1-760-942-7211
Days and hours of operation : 9:00-17:00(PST/PDT), Weekdays, except national holidays in US.
Language: English only.

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product Regulations and the SDS contains all required information.


Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Label elements

Pictogram



Signal word Danger

SILICONE REMOVER

Hazard statements	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container in accordance with local regulations.

3. Composition/information on ingredients

Substances

METHYL METHACRYLATE	100%
CAS number: 80-62-6	

Product name	SILICONE REMOVER
Chemical name	METHYL METHACRYLATE
CAS number	80-62-6

4. First-aid measures

Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse.

SILICONE REMOVER

Eye contact Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Skin contact Allergic rash. Skin irritation.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Carbon dioxide or dry powder.

Specific hazards arising from the hazardous product

Specific hazards Irritating gases or vapours.

Hazardous combustion products No known hazardous decomposition products.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours.

Special protective equipment for firefighters Wear chemical protective suit.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

Methods and material for containment and cleaning up

Methods for cleaning up No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Ground/bond container and receiving equipment. Use only non-sparking tools. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections

Reference to other sections For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions All handling should only take place in well-ventilated areas. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

SILICONE REMOVER

Storage precautions Store at temperatures between 0°C/25°F and 32°C/77°F. Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place. Ground/bond container and receiving equipment.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 205 mg/m³

Short-term exposure limit (15-minute): ACGIH 100 ppm 410 mg/m³

A4, DSens

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

DSens = Dermal sensitizer.

Exposure controls

Appropriate engineering controls Provide adequate general and local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Wear protective gloves.

Other skin and body protection Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Take off contaminated clothing and wash it before reuse.

Respiratory protection Wear a respirator fitted with the following cartridge: Organic vapour filter.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear, Colourless
Odour	Characteristic
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	100°C
Flash point	14.5°C
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.

SILICONE REMOVER

Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 12.5% Lower flammable/explosive limit: 1.7%
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	421°C
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not available.
Other information	Not available.

10. Stability and reactivity

Reactivity	May polymerize. See the other subsections of this section for further details.
Stability	The product is highly flammable.
Possibility of hazardous reactions	May polymerize.
Conditions to avoid	Keep away from heat, sparks and open flame. Protect against direct sunlight.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Heating may generate the following products: Toxic gases or vapours.

11. Toxicological information

Information on toxicological effects

Routes of exposure	See section 4. Skin , Eyes , Ingestion , Inhalation
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Not available.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Not available.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Not available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Skin Irrit. 2 - H315 Causes skin irritation.
Animal data	Not available.

SILICONE REMOVER

Serious eye damage/irritation

Serious eye damage/irritation Not available.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Skin Sens. 1 - H317 May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

Carcinogenicity Not available.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Not available.

12. Ecological Information

Toxicity Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

SILICONE REMOVER

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN number

UN No. (TDG)	1247
UN No. (IMDG)	1247
UN No. (ICAO)	1247
UN No. (DOT)	UN1247

UN proper shipping name

Proper shipping name (TDG)	METHYL METHACRYLATE MONOMER, STABILIZED
Proper shipping name (IMDG)	METHYL METHACRYLATE MONOMER, STABILIZED
Proper shipping name (ICAO)	METHYL METHACRYLATE MONOMER, STABILIZED
Proper shipping name (DOT)	METHYL METHACRYLATE MONOMER, STABILIZED

Transport hazard class(es)

DOT class	3
DOT hazard label	3
TDG class	3
TDG label(s)	3
IMDG class	3
ICAO class/division	3

DOT transport label



Transport labels



Packing group

TDG packing group	II
IMDG packing group	II
ICAO packing group	II
DOT packing group	II

Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

Special precautions for user

EmS	F-E, S-D
-----	----------

SILICONE REMOVER

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR) Hazardous Products Regulations - SOR/2015-17. Transportation of Dangerous Goods Regulations - SOR/2015-100.

16. Other information

Training advice Ensure operatives are trained to minimize exposure. Only trained personnel should use this material.

Revision comments This is first issue.

Revision date 20/03/2018

Revision 1

Hazard statements in full H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.