SAFETY DATA SHEETS

This SDS packet was issued with item: 073153715

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

073153723 073153731 073153830 073153848 073153855 073153863 073153905 073153913 073154747

Material Safety Data Sheet

Material Safety Data Sheet					
Page 1 of 4			Form # QF-10-07		
Identity (As used	on Label or List) Press Form Putty	Hazard Class:			
	Se	ection 1			
Manufacturer's M Ellman Intern		Emergency Telephone Number (516) 594-3333			
Address, Number, Street, City, State, Zip 3333 Royal Ave. Oceanside, New York 11572 U.S.A.		Telephone Number For Information (516) 594-3333			
Print Date: 1	/6/09 Update: 12/6/12	Signature of Preparer (optional)			
	Section 2 - Pro	oduct Identification			
Trade Name: H Generic Name: Chemical Name	Silicone Compound				
Hazardous Comp Name(s))	onents (Specific Chemical Identity Common	OSHA PEL	ACGIH TLV	% Optional	
CAS # 00763	1869 Silica, amorphous endor proprietary thickener	15 mg/m3 total dust, 5 mg/m3 respirable fraction 10 mg/m3 total dust, 5	twa 10 mg/m3 inhalable twa 10 mg/m3	wt% 8 wt% 5	
Special Notes: The above components are hazardous as defined in cfr 1910.1200.		mg/m3 respirable fraction			
Section 3 - Effects of Overexposure					
Acute EffectsEye:Direct eye contact may cause temporary discomfort with mild redness and dryness similar to windburn.					
Skin:	A single prolonged exposure (24 to 48 hours) causes no known adverse effect.				
Inhalation:	No irritation to eyes and respiratory passages. No injury is likely from relatively short exposures of less than 8 hours.				
Oral:	Small amounts transferred to the mouth by fingers during use, etc., should not injure. Swallowing large amounts may cause digestive discomfort.				

Repeated Exposure effects

Skin:None known.Inhalation:None Known.Oral:None known.

Special Hazards

This material contains the following components with the special hazards listed below.

<u>Carcinogens</u> None Known. <u>Teratogens</u> None Known. <u>Mutagens</u> None Known.

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

Material Safety Data Sheet

Press Form putty page 2 0f 4

Form # QF-10-07

<u>Reproductive Toxins</u> None Known. <u>Sensitizers</u> None known. Please read additional information below.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions component data and/or expert review of the product.

Section 4 - First Aid Measures				
Eye:	Immediately flu	sh with water.		
Skin:	No first aid should be needed.			
Inhalation:	No first aid should be needed.			
Oral:	Oral: No first aid should be needed.			
Comments: Treat symptomatically				
Section 5 - Fire Fighting Measures				
Flash Point (closed cup) :> 213.98 degrees F / 101.10 Degrees C				
Auto ignition T	emperature:	Not Determined.		
Flammability Limits in Air:		Not Determined.		
Extinguishing media:		Water spray, Carbon dioxide (CO ₂), Dry Chemical, Foam. Water can be used to cool fire exposed containers.		
Fire fighting procedures:		Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Determine the need to evacuate or isolate the area according to your		

Unusual fire Hazards: None.

Hazardous Decomposition products:

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon Oxides and traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde.

local emergency plan.

Section 6 - Accidental Release Measures

Containment/Clean-up:	Disposal of collected product, residues, and clean-up materials may be governmentally regulated.			
	Observe all applicable local, state, and federal waste management regulations. Mop-up or wipe up			
	or soak up with absorbent and contain for salvage or disposal. Clean any remaining slippery			
	surfaces by appropriate techniques, such as: several mopping or swabbing with appropriate solve			
	washing with mild caustic detergents or solutions; or high pressure steam for large areas. For non			
	silicones, use typical industrial cleaning materials. Observe any safety precautions applicable to the			
	cleaning material being used.			

Section 7 - Handling and Storage

Handling and Storage: No special precautions. Use reasonable care.

Material Safety Data Sheet

Press Form Putty page 3 0f 4

Section 8 - Exposure Controls/ Personal Protection

Engineering Controls

Local exhaust:	None should be needed.
General Ventilation:	Recommended.

Personal Protective Equipment for Routine Handling

Eyes:	Use proper protection.
Skin:	Washing at mealtime and end of shift is adequate.
Suitable Gloves:	No special protection is needed.
Inhalation:	No respiratory protection should be needed.
Suitable Respirator:	None should be needed.
Personal Protective Equip	oment for Spills
Eyes:	Use proper protection - Safety glasses as a minimum.
Skin:	Washing at mealtime and end of shift is adequate.
Inhalation:	No respiratory protection should be needed.
Precautionary measures:	Avoid eye contact. Use reasonable care.
Comments:	None

Note: These precautions are for room temperature handling. Use at elevated temperature, or aerosol spray applications may require added precautions.

	Section 9 Physical and Chemical Properties
Physical Form:	Viscous Liquid
Color:	White
Odor:	Odorless
Specific Gravity @ 25C:	1.06
Viscosity:	1000000.00 CST.
Freezing/Melting Point:	Not Applicable.
Boiling Point:	Not Applicable.
Vapor Pressure @ 25C:	Not Determined.
Vapor Density:	Not determined.
Solubility in Water:	Not determined.
pH:	Not Applicable.
Volatile Content:	Not Determined.
	Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

Section 9 Physical and Chemical Properties

Form # QF-10-07

Material Safety Data Sheet

Press Form Putty page 4 0f 4

Form # QF-10-07

Section 10 Stability and Reactivity			
Chemical Stability:	Stable.		
Hazardous Polymerization:	Will not occur.		
Conditions to Avoid:	None.		
Materials to Avoid:	Oxidizing material can cause a reaction.		
Comments:	None		
Section 11 Toxicological Information			
Optional Section - Complete information not yet available.			
Section 12 Ecological Information			
Optional Section - Complete in	0		

Section 13 Disposal Information

RCRA Hazard Class (40CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO

Federal Hazardous waste code: NA

Characteristic Waste: Ignitable: NA

Corrosive: NA

Reactive: NA

TCLP: NA

NA=Not Applicable

State or local laws may impose additional regulatory requirements regarding disposal.

Section 14 Regulatory Information

Contents of this MSDS comply with OSHA Hazard Communication Standard 29CFR 1910.1200 TSCA status: All chemical substances found in this product comply with the toxic substances control act inventory reporting Requirements.

Material Safety Data Sheet

page 1 of 2

Form # QF-10-07 (part 1)

Identity (As used on Label or List)

Hazard Class: PRESS FORM PLASTIC SHEETS (Soft)

010

Section 1

Manufacturer's Name Ellman International, Inc.

Address, Number, Street, City, State, Zip 3333 Royal Ave. Oceanside, New York 11572 U.S.A. Emergency Telephone Number (516) 594-3333

Telephone Number For Information (516) 594-3333 Date prepared 12/6/12

Signature Of Preparer (optional)

Section 2 - Product Identification Trade Name: Press Form Plastic Sheets					
Generic Name:	*Vinyl Acetate				
Chemical Name :	Ethylene Vinyl Acetate Copolymer	•			
	necific Chemical Identity Common Name(s))	OSHA	ACGIH	Other	0/0

Hazardous Components (Specific Chemical Identity Common Name(s))	OSHA	ACGIH	Other	%
	PEL	TLV	Limits	Optional
Exposure Guidelines	15 mg/m3	10 ppm		>99.7
CAS Registry Number 108-05-4	8Hr. TWA,	35 mg/m3		< 0.03
CAS Registry Number 108-05-4	total dust	8 hr TWA,		<0.03
Sancial Natara * Dialaman and tania daminal in maminal and an article 212 af	5mg/m3	A3		
Special Notes: * Disclosure as a toxic chemical is required under section 313 of Tisle III of the Superfund American dependence and Dependence in a file of the Superfund American dependence of 1086 and	8Hr TWA			
Title III of the Superfund Amendments and Reauthorization act of 1986 and	respirable			
40 CFR part 372	dust			

Section 3 - Physical / Chemical Characteristics			
ling Point : Specific Gravity			
N/A	0.93-0.97		
Vapor Pressure (mm Hg)	Melting Point		
Negligible	N/A		
Vapor Density (Air=1)	Boiling Point Evaporation (Butyl Acetate =1)		
Not Applicable	N/A		
Solubility in Water			
Negligible			
Appearances and Odor			
Physical form: Solid, Translucent to white, slight odor mild ester-l	like		

Section 4 - Fire & Explosion Hazard Data					
Flash Point (Method Used)	Flammable Limits	LEL	LEL		
260°C (500°F) Cleveland Method: Open Cup					

Extinguishing Media: Water spray ; Foam; Dry chemical; CO₂

Special Fire Fighting Procedures: Wear self contained breathing apparatus and protective clothing.

Unusual Fire & Explosion Hazards : The solid polymer can be combusted only with great difficulty. An electrostatic charge can potentially build up when pouring pellets. Grounding of equipment is recommended. **Complete combustion** gives carbon dioxide and water. **Incomplete combustion** gives in addition carbon monoxide and hydrocarbon oxidation products including organic acids, aldehydes, and alcohols.

Material Safety Data Sheet

page 2 0f 2 Press Form Sheets

Form # QF-10-07 (part2)

Section 5 - Reactivity Data

Stability: Stable at normal temperatures and storage conditions

Conditions to Avoid: temperatures above 230°C for short residence times or Temperatures above 204°C for long residence times.

Incompatibility (Materials to Avoid) : Material can react with strong oxidizing agents and acids

Hazardous Decomposition or Byproducts: Vinyl Acetate, acetic acid, carbon monoxide and hydrocarbon oxidation products including organic acids, aldehydes and alcohols.

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Route(s) of Entry and Symptoms:

Ingestion: The oral LD-50 test in animals showed that no significant amount of polymer was retained by the animals.

Skin: No data are available. However, based on experience with handling of polymers, no unusual dermatitis hazard is expected from routine handling. Molten Polymer contacting the skin will cause thermal burns.

Eye: Mechanical Irritation.

Inhalation: Polymer is not respirable as marketed. At processing temperatures above $204 \,^{\circ}$ C, fumes irritating to the eye, nose and throat may be produced. Exposure may result in redness tearing, and itching in the eyes together with soreness in the nose and throat with coughing.

Medical Conditions Aggravated by Exposure: None known

Emergency and First Aid Procedures:

If inhaled remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Skin Contact: The compound is not likely to be hazardous by skin contact but cleansing the skin after use is advisable. If molten material gets on skin, cool rapidly with cold water, do not attempt to remove material from skin. Obtain medical treatment for thermal burn.

Eye Contact: In case of contact, immediately flush with plenty of water for 15 minutes. Call a physician.

Ingestion: No specific intervention is indicated as compound is not likely to be hazardous by ingestion. Consult a physician if necessary.

Section 7 - Special Precautions

Steps to be Taken in Case Material is Released or Spilled: Shovel or sweep up.

Waste Disposal Method: Disposal must be in accordance with applicable state/local or federal regulations.

Precautions to be Taken in Handling and Storing : See First aid and personal protective equipment sections. Store in a cool dry place

Other Precautions: None

section 8 - Control Measures

Respiratory Protection (Specify Type): a NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge with a dust /mist filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Ventilation: Local if processing in air below the PEL

Special: Use static control. Static charges may build up and ignite dust or solvent laden atmospheres.

Mechanical (general) N/A

Eye Protection: Safety Glasses

Protective Gloves: N/A

Other Protective Clothing or Equipment: Apron or protective clothing

Information contained in this Material Safety Data Sheet is offered without charge for use by technically qualified personnel at their discretion & risk. All statements, technical information & recommendations contained herein are based on tests & data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed & no warranty of any kind is made with respect thereto. This information is not intended as a license to operate under a recommendation to practice or infringe any patent of this company or other process, composition of matter and use.

Since the company shall have no control over the use of the product described herein, the company assumes no liability of loss or damage incurred from the proper or improper use of such product.